



HG-MCCB

Molded Case Circuit Breakers & Earth Leakage Circuit Breakers

Essential for Today, Potential for Tomorrow

Hyundai Electric solely pursues the growth of our customers' business. From power generation to power distribution, we focus on developing and commercializing products and solutions aimed at increasing the efficiency of energy equipment as well as at proactively monitoring and controlling assets in an integrated manner to improve our customers' productivity and management efficiency. We are well aware that our efforts add to the driving force behind our customers' growth and contribute to the creation and maintenance of a more dynamic world. We focus on achieving innovation and strive to evolve continuously to shape a better tomorrow based on today's technological advancement

Solution

INTEGRIC


Energy Solution

Energy solution business refers to the business of designing, procuring and establishing a system that enables the efficient use of power energy through integrated management of the production, consumption, sales and operation.

Generation(step-up)

Power Plants

- Supplied to more than 70 countries around the world for the past 45 over years since 1978
- Satisfies the various demands of customers through the acquisition of quality certifications from international accredited institute
- Participates in the world's key technical committee such as GIGRE and others, pioneering the establishment of technology standard related to power network



Power Transformer
· up to 800 kV, 1,500 MVA

Gas Insulated Switchgear
· up to 800 kV


- Can be installed in spaces smaller than the open type of substation by using SF₆ gas with outstanding insulation and arc extinguishing characteristics
- Manufacturing advanced products that are resistant to external environment and climate effects through the sealing at the charge part
- Extensive project experiences around the world
- Reduces installation period and cost due to simple installation and transportation, convenient maintenance
- Design considering the safety of the workers as priority

Asset Management Solution

Asset management solution is a business that maximizes the overall business efficiency by systematically managing the performance, risk, maintenance cost and others as well as by providing an asset management solution suitable to the customer's circumstance depending on the product lifecycle (PLC) of various products.

Transmission

Primary Substation/Secondary Substation




Gas Insulated Switchgear
· up to 800 kV

Power Transformer
· up to 800 kV, 1,500 MVA

Shunt Reactor
· up to 765 kV, 300 Mvar

Distribution



Cubicle GIS
· up to 40.5 kV
· IEC, ANSI, GOST, UL

- Produces high quality products using angle-less type
- Multi-functional digital protection relay (HiMAP) applied
- High reliability secured, provides various operation information such as protection, measurement and control
- Firm external box, size and compact, making it safe
- Maintains high quality through stringent quality control system and continuous research and development

Utility

- Can be installed in spaces smaller than the open type of substation by using SF₆ gas with outstanding insulation and arc extinguishing characteristics
- Manufacturing advanced products that are resistant to external environment and climate effects through the sealing at the charge part
- Extensive project experiences around the world
- Reduces installation period and cost due to simple installation and transportation, convenient maintenance
- Design considering the safety of the workers as priority



ECO Transformer
· up to 500 kV, 1,000 MVA

- Eco-friendly oil (Natural/Synthetic)
- Dynamic Pressure Resistant System(DPRS)
- Guarantees excellence in safety

SF₆ Free Gas Insulated Switchgear
· GIS for 170 kV 50 kA 60 Hz
· ECO GIS for 72.5 kV, 145 kV

- Korea's first solely developed technology
- Eco-friendly Novec mixture gas instead of SF₆ gas

Motor & Generator



Synchronous Generator
· Rated Output: < 50 MVA
· Rated Voltage: < 15 kV
· Poles: > 2P

Marine

Marine Solution

- Production of high quality marine devices satisfying the regulations and standards of key marine associations (LRS, ABS, DNV, GL, BV, NK etc.) and world's renowned institutes
- High quality safety secured through the latest equipment and stringent quality control system
- Realization of optimal high efficiency by converging SWGR, Generator, Motor, Telecom, Automation, Intelligent Motor Control Unit and others

GREENTRIC




Marine Switchgear

Marine Motor

Generator

Shaft Generator



- Enhanced reliability and secured safety with production of products based on the world's best equipment and stringent quality system
- Realized high efficiency by selecting slot based on FEM
- Realized small and lightweight with optimal design based on FEM analysis method
- Satisfies the quality standards of international accredited institutes (IEC, IEEE, CSA, NEMA, API etc.)



Molded Case Circuit Breakers & Earth Leakage Circuit Breakers

Characteristics	10
Model Selection Table	28
Accessories	
HGM General Type	72
HGP High Breaking Type	74
Internal Accessories	76
External Accessories	84
Technical Data	
Technical Data (HGM/HGE)	110
Technical Data (HGP)	124
Operation Characteristic Curve	149
Dimensions	166
Order Code	236
Handling and Maintenance Inspection	250
Acquired Standards	257

MCCB

HG Series

Molded Case Circuit Breakers & Earth Leakage Circuit Breakers

Maximized selectivity and safety with wide product range and reinforced breaking performance!




HYUNDAI HGM 125L

125AF	50/60Hz
Ui 1000V	Uimp 8kV
Ue(V)	Icu(kA)
660 / 690V	~ 10kA
480 / 500V	~ 35kA
440 / 460V	~ 55kA
415V	~ 55kA
380V	~ 55kA
220 / 240V	~ 100kA
250V	= 30kA
Ics = Icu	100%

MADE IN KOREA

Rated Short-Circuit Current by AF, ($I_{cs} = 100\% I_{cu}$ at 440/460 V)



Wide Product Range

HGM/HGE 32 AF ~ 800 AF

High Breaking Capacity

16 kA ~ 85 kA (at 460 V), $I_{cs} = 100\% I_{cu}$

Rated Insulation Voltage of 1,000 V

Reinforcement of Protective Coordination

It enables selective breaking.

Adjustable Rated Current (Molded Case Circuit Breaker)

32 ~ 250 AF : 0.8 - 0.9 - 1 Times the Rated Current
400 ~ 800 AF : 0.63 - 0.8 - 1 Times the Rated Current

Adjustable Residual Current (Earth Leakage Circuit Breaker)

100 - 300 - 500 - 1,000 (mA)

Adjustable Residual Current's Non-Operation Hour (Earth Leakage Circuit Breaker)

0 - 200 - 500 - 1,000 (ms)



Molded Case Circuit Breakers



Earth Leakage Circuit Breakers

Characteristics

Enhanced Performance and Various Selectivity

Various Range of Products : 10 Frames, 32 ~ 800 AF

Compatible MCCB, ELCB Dimensions and Common Use of Accessories


Standardization of Product Depth per Frame : 32 ~ 250 AF (68 mm), 400 ~ 800 AF (110 mm)




32, 50, 63, 100 AF

50, 125 AF

160, 250 AF



MCCB



ELCB



400 AF

630, 800 AF

Unit : mm

Characteristics

HGM Molded Case Circuit Breaker

Maximized Insulation Performance

The safety of the product has been maximized through enhanced insulation voltage

- Rated Insulation Voltage, U_i : 1,000 V
- Rated Impulse Withstand Voltage, U_{imp} : 8 kV

High Breaking Capacity

Maximum breaking capacity was realized with high breaking capacity in Korea.

- 16 ~ 30 kA at 460 V (32 ~ 100 AF)
- 20 ~ 55 kA at 460 V (125 ~ 250 AF)
- 38 ~ 85 kA at 460 V (400 ~ 800 AF)


Cable Insulation Performance Suitability

In case there is a presence of abnormal condition such as welding of the main contact after tripping of the circuit breaker by realizing the cable insulation performance in accordance with IEC 60947-2, the handle does not move from ON to OFF position. This makes it safe by preventing the operation of circuit breaker caused by the operator's negligence.

Adjustable Rated Current in all Frames


The adjustable rated current of up to 800 AF provides optimal protection for load variations in customer's equipment.

- Long Time (≤ 250 AF) :
3-step adjusting, 80 % - 90 % - 100 % of rated current
- Long Time (400 AF, 800 AF) :
3-step adjusting, 63 % - 80 % - 100 % of rated current




Sealing Structure (Option) Applied

Dial sealing structure is applied to prevent arbitrary change of the current set value using a protection cover (Prevent operation of thermal magnetic adjustment knob) (Option).



HYUNDAI
HGM 125H
125AF 50/60Hz
 U_i 1000V U_{imp} 8kV

$U_e(V)$	$I_{cu}(kA)$
660 / 690V	~ 8kA
480 / 500V	~ 26kA
440 / 460V	~ 38kA
415V	~ 38kA
380V	~ 42kA
220 / 240V	~ 85kA
250V	= 20kA
$I_{cs} = I_{cu}$	100%




1.0 ← 0.8
|| 0.9 $I_r(x \ln)$

Service Breaking Capacity ($I_{cs} = 100\% \times I_{cu}$)

100 % service breaking capacity has been realized by significantly improving the breaking capacity by restricting accidental current using an internal current limiting device in case of short-circuit accidents.

- 32 ~ 800 AF
- 16 ~ 55 kA @ 460 Vac (Below 250 AF)
- 38 ~ 85 kA @ 460 Vac (400 ~ 800 AF)
- (HGM60, 100 H Type $I_{cs} = 75\% I_{cu}$, HGM60, 100 L Type $I_{cs} = 50\% I_{cu}$)



Various Low Voltage System Protections



HGM Type MCCB realizes current limiting characteristics and outstanding breaking performance and enables various low voltage system protections such as discrimination and cascading.

Discrimination

It is a protection method in which when an accident occurs during load, the downstream circuit breaker that is directly related to the accident circuit operates first so that the other sound branch circuit breaker and the upstream main circuit breaker can feed continuously. It is a low voltage system protection method that can minimize the fault point by selectively preventing faults.

Cascading

In case an accident occurs during load, the upstream main circuit breaker operates earlier than the downstream circuit breaker of the accident circuit for back-up protection. It is an economic protection method. Thus, a circuit breaker with lower breaking capacity than the estimated short-circuit current can be applied.



Characteristics

HGE Earth Leakage Circuit Breaker

Secures Equivalent Breaking Performance with MCCB, Maintains Compatibility with Dimensions and Accessories

- Service Breaking Current, $I_{cs} = 100\% I_{cu}$
- Rated Impulse Withstand Voltage, $U_{imp} : 6\text{ kV}$



Characteristics of Earth Leakage Protection

- Prevention function of damage caused by reverse connection : A circuit capable of preventing damage in PCB and Trip Coil has been applied to prevent damage despite usage during reserve connection caused by the misuse of user.
- The device is safe as it is equipped with a function that prevents unnecessary malfunction of earth leakage circuit breaker caused by temporary drop of voltage and noise signal.
- With the 3-phase power supply method, it safely breaks even during abnormal system voltage caused by open phase.
- By deploying filter circuit in IC, it safely protects the inverter load from grounding.

Adjustable Residual Current / Operating Time

Item	Adjustable Residual Current					Cut-Off Time			
	30 mA	100 mA	300 mA	500 mA	1,000 mA	0 ms	200 ms	500 ms	1,000 ms
Previous (U-ELCB)	Fixed		Adjustable (3 Steps)		-	Fixed	-	-	-
New Product (HG-ELCB)	Fixed		Adjustable (4 Steps)				Adjustable (4 Steps)		

- With adjustable leakage current sensitivity (4 stages), prompt action can be taken without replacing the product depending on the load status.
- Selective protection coordination between upstream circuit breaker and downstream circuit breaker is possible through adjustable residual current and operating time, protecting the circuit safely



Applicable standards and certifications

Applicable Standards

Korean Standards

[KS C 8321 Molded Case Circuit Breaker for Industrial Uses](#)

(Molded Case Circuit Breaker for Industrial Uses)

[KS C 4613 Circuit Breaker Incorporating Residual Current Protection for Industrial Uses \(CBR\)](#)

(Circuit Breaker Incorporating Residual Current Protection for Industrial Uses (CBR))

International Standards

[IEC 60947-1](#)

LLow Voltage Switchgear and Controlgear, Part 1 (General Rules)

[IEC 60947-2](#)

Low Voltage Switchgear and Controlgear, Part 2 (Circuit Breakers)



Approvals and Certifications

HG-Series MCCB has acquired the testing/certification from certified testing institutes registered in STL in accordance with the IEC standard and domestic safety certifications (K 60747-2) and can be installed and applied depending on the usage environment and condition permitted in the standard.

- CB Certification (Certifying Institute, DEKRA)
- Safety Certification
- KS Certification
- Marine Approvals (8 Classifications)



Our services

Testing, Inspections, Certification DEKRA provides certification of management systems as well as technical support, testing and certification of a wide range of products throughout the life cycle.

Vibration/Shock-Proof Test Certification Acquired

Our product has qualified the vibration/shock-proof test in accordance with the IEC 60068-2-6 which is a requirement of IACS, an international vessel inspection institute.

- 5 ~ 13.2 Hz : Displacement (1 mm)
- 13.2 ~ 100 Hz : Acceleration (0.7 g)

HG Series

Molded Case Circuit Breakers (HGP Type)

Realizes optimal protection performance regardless of changes in load situation with rated adjustment design!



Rated Short-Circuit Current by AF (I_{cs} = 100 % I_{cu} at 440/460 V)

150 kA	50DX	125DX	160DX	100X	160X	250X	400X	630X	800X
85 kA									
70 kA	50DH	125DH	160DH	100H	160H	250H	400H	630H	800H
65 kA									
50 DS	125DS	160DS	100S	160S	250S	400S	630S	800S	
36 kA*	50DF	125DF	160DF	100F	160F	250F	400F	630F	800F
	50D AF	125D AF	160D AF	100 AF	160 AF	250 AF	400 AF	630 AF	800 AF

* F type is for overseas sales.

Wide Product Range

HGP 50 AF ~ 800 AF

Realizes Maximum Breaking Capacity in Korea

150 kA (at 460 V)

Reinforcement of Protective Coordination

It enables selective breaking.

Acquisition of Various Certifications

DEKRA, marine and KS certifications have been acquired.

Adjustable Operating Characteristics

Rated Current

3-Steps, 0.8 - 1 Times the Rated Current

(Thermal Magnetic Type)

9-Steps, 0.4 - 1 Times the Rated Current

(Electronic Type)

Instantaneous Current

6-Steps, 5 - 6 - 7 - 8 - 9 - 10 Times the Rated Current

(Thermal Magnetic Type)

9-Steps, 1.5 - 10 Times the Rated Current

(Electronic Type, Short Time Current)



Thermal Magnetic Type



Electronic Type

Characteristics (HGP)

Outstanding Protection Coordination and Maximized Breaking Capacity

Simplified Dimension with 4 Types from 50 ~ 800 AF

Adjustable Rated Currents in all Models

Owes the Outstanding Breaking Capacity in all Frames : 150 kA at 460 V

Various Breaking Coordination such as Selective Breaking and Others

Guaranteed Breaking Capacity in Reverse Connection



Trip Device : Thermal Magnetic Type

50D, 125D, 160D AF

Trip Device : Thermal Magnetic Type, Electronic Type

100, 160, 250 AF



Thermal Magnetic Type



Electronic Type



Trip Device : Thermal Magnetic Type, Electronic Type



Trip Device : Thermal Magnetic Type, Electronic Type

400, 630 AF

800 AF

Unit : mm


Characteristics (HGP)

HGP MCCB Trip Device

- The device to monitor the system and send a breaking signal to protect load and a cable
- The external dimensions and accessories are for common use regardless of the type of a trip device.

- A trip unit is replaceable, which depends on load types and protection characteristics.
(Common use for the circuit breaker body)
- It has various ratings and adjustable functions.

Thermal Magnetic Type



Electronic Type



Type	2.5 ~ 12.5	16 ~ 80	100	125 ~ 800
Thermal Magnetic (Thermal Fixed / Instantaneous Fixed)		●	●	●
Thermal Magnetic (Thermal Adjustable / Instantaneous Fixed)		●	●	●
Thermal Magnetic (Thermal Adjustable / Instantaneous Adjustable)			●	●
Electronic (E, A, N, D Type)			●	●
For Motor Protection, Switch-Disconnector	●	●	●	●



For protecting a cable
and a device
(Thermal Magnetic)

For protecting a cable
and a device
(Electronic Trip Unit)

For motor protection
(Instantaneous)

Switch-Disconnector

- MTM-25-FF : Thermal Fixed / Instantaneous Fixed
- MTM-25-JF : Thermal Adjustable / Instantaneous Fixed
- MTM-25-JJ : Thermal Adjustable / Instantaneous Adjustable



- ETU-25-N : Normal Type
- ETU-25-D : Display Type
- ETU-25-A : Ammeter Type
- ETU-25-E : Energy-meter Type

- MCP-25-OJ : Instantaneous Adjustable

- DSU-25 : No protection

HGP Type ETU (Electrical Trip Unit)

- Equipped with intelligent electronic function for a new era
- Maximizes a system energy efficiency the function of monitoring commutation and power



It checks current status on the front display and product status on the LED window.
(Pre trip alarm)



It monitors the system with a maintenance tool.



It applies a transparent protection cover.
(prevent pollution and operation)

Characteristics (HGP)

HGP Molded Case Circuit Breaker

Maximized Insulation Performance

The safety of the product has been maximized through improved insulation voltage

- Rated Insulation Voltage, U_i : 1,000 V
- Rated Impulse Withstand Voltage, U_{imp} : 8 kV

High Breaking Capacity

Maximum breaking capacity was realized with regards to all frames with high breaking capacity in Korea.

- 150 kA at 460 V (Same performance secured in all frames)


Cable Insulation Performance Suitability

In case there is presence of abnormal condition such as welding of the main contact after tripping the circuit breaker by realizing the cable insulation performance in accordance with IEC 60947-2, the handle does not move from ON to OFF position, making it safe by preventing the operation of circuit breaker caused by the operator's negligence.

Adjustable Rated Current in all Frames


The adjustable rated current of up to 800 AF provides optimal protection for load variations in customer's equipment.

- Rated Current
Thermal Magnetic Type : 0.8 - 1 times the rated current (3 Step)
Electronic Type : 0.4 - 1 times the rated current (9 Step)
- Instantaneous Current
Thermal Magnetic Type : 5 - 6 - 7 - 8 - 9 - 10 times the rated current (6 Step)
Electronic Type : 1.5 - 10 times the rated current (9 Step, Short Time Adjusting)




Sealing Structure (Option) Applied

Dial sealing structure was applied to prevent arbitrary change of the current set value using a protection cover (Prevent operation of thermal magnetic adjustment knob) (Option).




U_e (V)	I_{cu} (kA)
660 / 690V	~ 10kA
480 / 500V	~ 50kA
440 / 460V	~ 70kA
380 / 415V	~ 85kA
220 / 240V	~ 100kA
240V	65kA
$I_{cs} = I_{cu} 100\%$	



Service Breaking Capacity ($I_{cs} = 100\% \times I_{cu}$)

100 % service breaking capacity has been realized by significantly enhancing the breaking capacity by restricting accidental current using an internal current limiting device in case of short-circuit accidents.

- 50 ~ 800 A.F
- 36 ~ 150 kA @ 460 VAC



Guaranteed Breaking Capacity in Reverse Connection

The same breaking performance is guaranteed even if the device is used by mixing LINE (Line side)/LOAD (Load side).


- Realizes integrated barrier circuit breaker that reinforces phase to phase insulation
- Realizes fast breaking operating characteristics by applying instantaneous mechanism part

Various Low Voltage System Protections

HGP Type MCCB realizes current limiting characteristics and outstanding breaking performance and enables various low voltage system protections such as discrimination and cascading.

Discrimination

It is a protection method in which when an accident occurs during load, the downstream circuit breaker that is directly related to the accident circuit operates first so that the other sound branch circuit breaker and the upstream main circuit breaker can feed continuously. It is a low voltage system protection method that can minimize the fault point by selectively preventing faults.




Cascading

In case an accident occurs during load, the upstream main circuit breaker operates earlier than the downstream circuit breaker of the accident circuit for back-up protection. It is an economic protection method that enables circuit breaker with lower breaking capacity than the estimated short-circuit current to be applied.



External Structure and Indications

Molded Case Circuit Breaker (MCCB)



Description of Nameplate at the Side of Product


- U_i : Rated Insulation Voltage
- U_{imp} : Rated Impulse Withstand Voltage
- U_e : Rated Operational Voltage
- I_{cu} : Rated Ultimate Short-Circuit Breaking Capacity (o-co)
- I_{cs} : Rated Service Short-Circuit Breaking Capacity (o-co-co)

Molded Case Circuit Breaker (MCCB)

- | | |
|---------------------------------|------------------------|
| ① Manufacturer and Product Name | ⑤ Load Side Terminal |
| ② Operating Handle | ⑥ Line Side Terminal |
| ③ Rated Current Nameplate | ⑦ CE Marking |
| ④ Rated Current Adjusting Dial | ⑧ Utilization Category |

- | |
|--|
| ⑨ Trip Button |
| ⑩ Cable Insulation Performance Suitability |
| ⑪ Reference Standard |

Earth Leakage Circuit Breakers (ELCB)



Description of Nameplate at the Side of Product


- Ui : Rated Insulation Voltage
- $Uimp$: Rated Impulse Withstand Voltage
- Ue : Rated Operational Voltage
- Icu : Rated Ultimate Short-Circuit Breaking Capacity (o-co)
- Ics : Rated Service Short-Circuit Breaking Capacity (o-co-co)

Earth Leakage Circuit Breakers (ELCB)

- | | | | |
|--|---------------------------|--|---|
| ① Manufacturer and Product Name | ④ Utilization Category | ⑨ Line Side Terminal | ⑫ Rated Non-Operating Time Setting Switch |
| ② Operating Handle | ⑤ Reference Standard | ⑩ Leakage Trip Indication Device | ⑬ Trip Button |
| ③ Cable Insulation Performance Suitability | ⑥ CE Marking | ⑪ Adjustable Residual Current Setting Switch | ⑭ Leakage Test Button |
| | ⑦ Rated Current Nameplate | | |
| | ⑧ Load Side Terminal | | |

External Structure and Indications

Molded Case Circuit Breaker (HGP Type)




Molded Case Circuit Breaker (HGP Type)

- | | | |
|---|--|--|
| ① Operating Handle | ⑤ Instantaneous Operating Current Adjusting Dial | ⑨ Utilization Category |
| ② Manufacturer and Product Name | ⑥ Load Side Terminal | ⑩ Cable Insulation Performance Suitability |
| ③ Rated Current Nameplate | ⑦ Line Side Terminal | ⑪ Reference Standard |
| ④ Long Operating Current Adjusting Dial | ⑧ CE Marking | ⑫ Trip Button |

Description of Nameplate at the Side of Product

- Ui : Rated Insulation Voltage
- Uimp : Rated Impulse Withstand Voltage
- Ue : Rated Operational Voltage
- Icu : Rated Ultimate Short-Circuit Breaking Capacity (o-co)
- Ics : Rated Service Short-Circuit Breaking Capacity (o-co-co)

Molded Case Circuit Breaker (HGP DC Type)



Description of Nameplate at the Side of Product

- Ui : Rated Insulation Voltage
- $Uimp$: Rated Impulse Withstand Voltage
- Ue : Rated Operational Voltage
- Icu : Rated Ultimate Short-Circuit Breaking Capacity (o-co)
- Ics : Rated Service Short-Circuit Breaking Capacity (o-co-co)

Molded Case Circuit Breaker (HGP Type)

- | | | |
|---|--|--|
| ① Operating Handle | ⑤ Instantaneous Operating Current Adjusting Dial | ⑨ Utilization Category |
| ② Manufacturer and Product Name | ⑥ Load Side Terminal | ⑩ Cable Insulation Performance Suitability |
| ③ Rated Current Nameplate | ⑦ Line Side Terminal | ⑪ Reference Standard |
| ④ Long Operating Current Adjusting Dial | ⑧ CE Marking | ⑫ Trip Button |

Model Selection Table

Molded Case Circuit Breaker (HGM Type) : 32 ~ 250 AF


Common Ratings

Rated Insulation Voltage, U_i	1,000 V	Suitability for Isolation	Yes
Rated Operational Voltage, U_e	690 V	Utilization Category	A
Rated Impulse Withstand Voltage, U_{imp}	8 kV	Pollution Degree	3
Protection Function	Overload, Instantaneous, Short-Circuit Protection	Reference Standard	IEC 60947-2

Model Name		HGM30			HGM50			HGM60		
Frame	(AF)	32			50			63		
Number of Poles	(P)	2, 3, 4 ¹⁾			2, 3, 4 ¹⁾			2, 3, 4 ¹⁾		
Rated Current, at 40 °C	(A)	16, 20, 25, 32			16, 20, 25, 32, 40, 50			16, 20, 25, 32, 40, 50, 63		
Rated Ultimate Short-Circuit Breaking Capacity [Icu] (kA rms)										
Short-Circuit Breaking Category Code		E	S	E	S	H	L	E	S	H
AC 660/690 V		2.5	5	2.5	5	8	10	2.5	5	7.5
AC 480/500 V		7.5	10	7.5	10	26	35	7.5	10	14
AC 415/440/460 V		16	20	16	20	38	55	16	20	26
AC 380 V		18	22	18	22	42	55	18	22	30
AC 220/240 V		35	50	35	50	85	100	35	50	50
DC 250 V (2P)		5	10	5	10	20	30	5	10	15
Service Breaking Capacity [$I_{cs} = \% I_{cu}$]		100	100	100	100	100	100	100	100	75
Rated Short-Circuit Making Capacity [Icm] (kA peak)										
AC 660/690 V		4	8	4	8	14	17	4	8	13
AC 480/500 V		13	17	13	17	55	74	13	17	28
AC 415/440/460 V		32	40	32	40	80	121	32	40	55
AC 380 V		36	47	36	47	89	121	36	47	63
AC 220/240 V		74	105	74	105	187	220	74	105	105
DC 250 V (2P)		8	17	8	17	40	63	8	17	30
Endurance [times] (Durability)										
Mechanical		30,000			30,000			30,000		
Electrical (at 460 V)		10,000			10,000			10,000		
Trip Device										
Thermal Magnetic	Long Time [LTD]	Fixed	(1.0) × In			(1.0) × In			(1.0) × In	
		Adjustable	(0.8 - 0.9 - 1.0) × In			(0.8 - 0.9 - 1.0) × In			(0.8 - 0.9 - 1.0) × In	
Accessory										
Internal	Auxiliary Switch	AUX	●		●			●		
	Alarm Switch	ALT	●		●			●		
	Shunt Trip	SHT	●		●			●		
	Under-Voltage Trip	UVT	●		●			●		
External	Rotary Handle	Front Contact TFG	●		●			●		
		Extension TFH	●		●			●		
	Mechanical Open/Close Device	MOT	●		●			●		
	Mechanical Interlock	MIF	●		●			●		
	Handle Locking Device	PLD	●		●			●		
	TDM (LINE/LOAD)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)		● (3P Only)		
	TDM (LINE Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)		● (3P Only)		
	TDF (LINE Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)		● (3P Only)		
	TDA (1 row)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)		● (3P Only)		
	TDA (2 rows)	● (2, 3P Only)	● (2, 3P Only)	● (2, 3P Only)	● (2, 3P Only)	● (2, 3P Only)		● (2, 3P Only)		
Installation and Dimensions										
Connection/ Installation	Front Connection				Terminal Screw					
	Rear Connection				Horizontal/Vertical					
	Plug-in				Switchgear (Line & Load, Line Only), Switchboard					
Dimension (mm)	DIN Rail Installation	Possible if DIN Rail adaptor is used	-			Possible if DIN Rail adaptor is used				
	a (2/3/4P)	50/75/100	50/75/100			60/90/120			50/75/100	
	b	130	130			155			130	
	c	68	68			68			68	
Weight (kg)		2/3/4P	0.6/0.8/1.0	0.6/0.8/1.0	0.8/1.0/1.3				0.6/0.8/1.0	
Detailed Rating and Selection			232 Page	232 Page	232 Page				232 Page	
Characteristic Curve and Appearance			149 / 166 Page	149 / 166 Page	150 / 167 Page				149 / 166 Page	

※ 1) 4 Pole Arrangement : Basic specification of R-S-T-N (N-R-S-T is optional.)

2) As for 2P products, only the neutral pole in the 3P product has been eliminated so the dimension is equivalent to the 3P product.



Trip Unit Characteristics – Thermal Magnetic

Rated Current (A) In		16	20	25	32	40	50	63	75	80	100	125
MCCB	HGM30	●	●	●	●							
	HGM50	●	●	●	●	●	●					
	HGM60	●	●	●	●	●	●	●				
	HGM100	●	●	●	●	●	●	●	●	●	●	
	HGM125	●	●	●	●	●	●	●	●	●	●	●
Moment Characteristics Ir												
Setting Value (A)	Fixed	16	20	25	32	40	50	63	75	80	100	125
	0.8×In	12.8	16	20	25.6	32	40	50.4	60	64	80	100
	0.9×In	14.4	18	22.5	28.8	36	45	56.7	67.5	72	90	112.5
	1.0×In	16	20	25	32	40	50	63	75	80	100	125
Instantaneous Characteristics li												
Setting Value (A)	10×In (Min. 400 A)	400					500	630	750	800	1,000	1,250
	Max. Non-Tripping Current (A)	320					400	504	600	640	800	1,000
	Min. Tripping Current (A)	480					600	756	900	960	1,200	1,500
Neutral Pole Protection												
4P3D		Unprotected										
4P4D		-										

Rated Current (A) In		100	125	150	160	175	200	225	250	300	350	400	500	630	700	800
MCCB	HGM160	●	●	●	●											
	HGM250	●	●	●	●	●	●	●	●	●						
	HGM400								● ¹⁾	●	●	●				
	HGM630										●	●				
	HGM800											●	●			
Moment Characteristics Ir																
Setting Value (A)	Fixed	100	125	150	160	175	200	225	250	300	350	400	500	630	700	800
	0.63×In									189	221	252	315	397	441	504
	0.8×In	80	100	120	128	140	160	180	200	240	280	320	400	504	560	640
	0.9×In	90	112.5	135	144	157.5	180	202.5	225							
	1.0×In	100	125	150	160	175	200	225	250	300	350	400	500	630	700	800
Instantaneous Characteristics li																
Setting Value (A)	10×In	1,000	1,250	1,500	1,600	1,750	2,000	2,250	2,500	3,000	3,500	4,000	5,000	6,300	7,000	8,000
	Max. Non-Tripping Current (A)	800	1,000	1,200	1,280	1,400	1,600	1,800	2,000	2,400	2,800	3,200	4,000	5,040	5,600	6,400
	Min. Tripping Current (A)	1,200	1,500	1,800	1,920	2,100	2,400	2,700	3,000	3,600	4,200	4,800	6,000	7,560	8,400	9,600
Neutral Pole Protection																
4P3D		Unprotected														
4P4D		-														

※ 1) HGM400 250 A is fixed type only.

Model Selection Table

Switch - Disconnector (HGM NA Type) : 50 ~ 800 AF

Switch - disconnector is a switch for disconnection without protective function and as the appearance is equivalent to the circuit breaker, all accessories of the circuit breaker can be shared.

Common Ratings

Rated Insulation Voltage, U_i	1,000 V	Suitability for Isolation	Yes
Rated Operational Voltage, U_e	690 V	Utilization Category	AC 22 A/AC 23 A - DC 22 A/DC 23 A
Rated Impulse Withstand Voltage, U_{imp}	8 kV	Pollution Degree	3
		Reference Standard	IEC 60947-3

Model Name		HGM50NA	HGM100NA	HGM125NA	HGM160NA
Frame	(AF)	50	100	125	160
Number of Poles	(P)	3, 4 ¹⁾	3, 4 ¹⁾	3, 4 ¹⁾	3, 4 ¹⁾
Conventional Free Air Thermal Current, I_{th} at 60 °C	(A)	50	100	125	160
Rated Operational Current [Ie]					
AC 690 V (50/60 Hz)		50	100	125	160
DC 125 V (1 Pole Connection)		50	100	125	160
DC 250 V (2 Pole Connection)		50	100	125	160
Rated Short Circuit Making Current [I_{cm}] (kA Peak @ AC 460)		0.8	1.7	2.1	2.7
Rated Short Time Withstand Current [I_{cw}] (kA rms)		1	1	1	2
Endurance [times] (Durability)					
Mechanical		30,000	30,000	30,000	25,000
In @ 440 V		10,000	10,000	10,000	10,000
Accessory					
Internal	Auxiliary Switch	AUX	●	●	●
	Alarm Switch	ALT	●	●	●
	Shunt Trip	SHT	●	●	●
	Under-Voltage Trip	UVT	●	●	●
External	Rotary Handle	Front Contact TFG	●	●	●
		Extension TFH	●	●	●
	Mechanical Open/Close Device	MOT	●	●	●
	Mechanical Interlock	MIF	●	●	●
	Handle Locking Device	PLD	●	●	●
	Plug-in	TDM (LINE/LOAD)	● (3P Only)	● (3P Only)	● (3P Only)
		TDM (LINE Only)	● (3P Only)	● (3P Only)	● (3P Only)
		TDF (LINE Only)	● (3P Only)	● (3P Only)	-
		TDA (1 row)	● (3P Only)	● (3P Only)	-
		TDA (2 rows)	● (3P Only)	● (3P Only)	-
	Cage Terminal Block	CTB	●	●	●
	Terminal Cover	TCF	●	●	●
	Insulation Barrier	TQQ	●	●	●
	Terminal Bus Bar	TBB	-	-	●
Installation and Dimensions					
Connection/ Installation	Front Connection		Terminal Screw		Terminal Screw, Terminal Bus Bar
	Rear Connection		Horizontal/Vertical		Horizontal/Vertical
	Plug-in		Switchgear (Line & Load, Line Only), Distribution Panel		Switchgear (Line & Load, Line Only)
	DIN Rail Installation	Possible if DIN Rail adaptor is be used		-	-
Dimension (mm)	a (3/4P)	75/100	75/100	90/120	105/140
	b	130	130	155	165
	c	68	68	68	68
Weight (kg)	3/4P	0.8/1.0	0.8/1.0	1.0/1.3	1.3/1.7
Detailed Rating and Selection		232 Page	232 Page	232 Page	232 Page
Characteristic Curve and Appearance		166 Page	166 Page	167 Page	168 Page

* 1) 4 Pole Arrangement : Basic specification of R-S-T-N (N-R-S-T is optional.)

Applicable Field of Switch – Disconnectors

- Bus bar connection and disconnection
- Disconnection of switchgear and control panel
- Switch for emergency power switchover (ATS)

HGM250NA	HGM400NA	HGM630NA	HGM800NA
250	400	630	800
3,4 ¹⁾	3,4 ¹⁾	3,4 ¹⁾	3,4 ¹⁾
250	400	630	800
250	400	630	800
250	400	630	800
4.2	6.8	10.7	13.6
2	4	6.3	8
25,000	4,000	2,500	2,500
10,000	1,000	500	500
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)
-	-	-	-
-	-	-	-
-	-	-	-
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
Terminal Screw, Terminal Bus Bar	Terminal Screw	Terminal Screw, Terminal Bus Bar	
Horizontal/Vertical	Horizontal/Vertical Cable	Horizontal/Vertical Cable	
Switchgear (Line & Load, Line Only)	Switchgear (Line & Load, Line Only)	Switchgear (Line & Load, Line Only)	
-	-	-	-
105/140	140/184	210/280	210/280
165	257	280	280
68	110	110	110
1.3/1.7	4.5/5.4	9.5/12.5	9.5/12.5
232 Page	232 Page	232 Page	232 Page
168 Page	169 Page	170 Page	170 Page

Model Selection Table

Motor Protection Circuit Breakers (HGM MO Type) : 50 ~ 250 AF

Common Ratings

Rated Insulation Voltage, U_i	1,000 V	Suitability for Isolation	Yes
Rated Operational Voltage, U_e	690 V	Utilization Category	A
Rated Impulse Withstand Voltage, U_{imp}	8 kV	Pollution Degree	3
Protection Function	Instantaneous, Short-Circuit Protection	Reference Standard	IEC 60947-2

Model Name		HGM50				HGM60			
Frame	(AF)		50				63		
Number of Poles	(P)		3				3		
Rated Current, at 40 °C	(A)		40, 50				40, 50, 63		
Rated Ultimate Short-Circuit Breaking Capacity [Icu] (kA rms)									
Short-Circuit Breaking Category Code		E	S	H	L	E	S	H	L
AC 660/690 V		2.5	5	8	10	2.5	5	7.5	8
AC 480/500 V		7.5	10	26	35	7.5	10	14	26
AC 415/440/460 V		16	20	38	55	16	20	26	30
AC 380 V		18	22	42	55	18	22	30	31
AC 220/240 V		35	50	85	100	35	50	50	50
DC 250 V (2P)		5	10	20	30	5	10	15	15
Service Breaking Capacity [$I_{cs} = \% I_{cu}$]		100	100	100	100	100	100	75	50
Rated Short-Circuit Making Capacity [Icm] (kA peak)									
AC 660/690 V		4	8	14	17	4	8	13	14
AC 480/500 V		13	17	55	74	13	17	28	55
AC 415/440/460 V		32	40	80	121	32	40	55	63
AC 380 V		36	47	89	121	36	47	63	66
AC 220/240 V		74	105	187	220	74	105	105	105
DC 250 V (2P)		8	17	40	63	8	17	30	30
Endurance [times] (Durability)									
Mechanical			30,000				30,000		
Electrical (at 460 V)			10,000				10,000		
Trip Device									
Magnetic	Instantaneous [INST]		10×In				10×In		
Accessory									
Internal	Auxiliary Switch	AUX		●			●		
	Alarm Switch	ALT		●			●		
	Shunt Trip	SHT		●			●		
	Under-Voltage Trip	UVT		●			●		
External	Rotary Handle	Front Contact TFG		●			●		
		Extension TFH		●			●		
	Mechanical Open/Close Device	MOT		●			●		
	Mechanical Interlock	MIF		●			●		
	Handle Locking Device	PLD		●			●		
	Plug-in	TDM (LINE/LOAD)	● (3P Only)	● (3P Only)			● (3P Only)		
		TDM (LINE Only)	● (3P Only)	● (3P Only)			● (3P Only)		
		TDF (LINE Only)	● (3P Only)	● (3P Only)			● (3P Only)		
		TDA (1 row)	● (3P Only)	● (3P Only)			● (3P Only)		
		TDA (2 rows)	● (2, 3P Only)	● (3P Only)			● (2, 3P Only)		
	Cage Terminal Block CTB		●				●		
	Terminal Cover TCF		●				●		
	Insulation Barrier TQQ		●				●		
	Terminal Bus Bar TBB		-				-		
Installation and Dimensions									
Connection/ Installation	Front Connection		Terminal Screw						
	Rear Connection		Horizontal/Vertical						
	Plug-in		Switchgear (Line & Load, Line Only), Distribution Panel						
	DIN Rail Installation		Possible if DIN Rail adaptor is be used		-		Possible if DIN Rail adaptor is be used		
Dimension (mm)	a		75		90		75		
	b		130		155		130		
	c		68		68		68		
Weight (kg)	3P		0.8		1.0		0.8		
Detailed Rating and Selection			232 Page		232 Page		232 Page		
Characteristic Curve and Appearance			149 / 166 Page		150 / 167 Page		149 / 166 Page		

HGM100				HGM125				HGM160				HGM250			
100				125				160				250			
3				3				3				3			
40, 50, 63, 75, 80, 100				40, 50, 63, 75, 80, 100, 125				100, 125, 150, 160				100, 125, 150, 160, 175, 200, 225, 250			
E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L
2.5	5	7.5	8	5	7.5	8	10	7.5	8	8	10	7.5	8	8	10
7.5	10	14	26	10	14	26	35	14	20	26	35	14	20	26	35
16	20	26	30	20	26	38	55	20	26	38	55	20	26	38	55
18	22	30	31	22	30	42	55	22	30	42	55	22	30	42	55
35	50	50	50	50	65	85	100	50	65	85	100	50	65	85	100
5	10	15	15	10	15	20	30	10	15	20	30	10	15	20	30
100	100	75	50	100	100	100	100	100	100	100	100	100	100	100	100
4	8	13	14	8	13	14	17	8	13	14	17	8	13	14	17
13	17	28	55	17	28	55	74	17	28	55	74	17	28	55	74
32	40	55	63	40	55	80	121	40	55	80	121	40	55	80	121
36	47	63	66	47	63	89	121	47	63	89	121	47	63	89	121
74	105	105	105	105	143	187	220	105	143	187	220	105	143	187	220
8	17	30	30	17	30	40	63	17	30	40	63	17	30	40	63
30,000				30,000				25,000				25,000			
10,000				10,000				10,000				10,000			
10×In				10×In				10×In				10×In			
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	-	-	-	-	-	-	-	-
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	-	-	-	-	-	-	-	-
● (2, 3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	-	-	-	-	-	-	-	-
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Terminal Screw								Terminal Screw, Terminal Bus Bar							
Horizontal/Vertical								Horizontal/Vertical							
Switchgear (Line & Load, Line Only), Distribution Panel								Switchgear (Line & Load, Line Only)							
Possible if DIN Rail adaptor is be used	-			-			-			-			-		
75	90			105			105			105			105		
130	155			165			165			165			165		
68	68			68			68			68			68		
0.8	1.0			1.3			1.3			1.3			1.3		
232 Page	232 Page			232 Page			232 Page			232 Page			232 Page		
149 / 166 Page	150 / 167 Page			151 / 168 Page			151 / 168 Page			151 / 168 Page			151 / 168 Page		


Model Selection Table

Motor Protection Circuit Breakers (HGM MO Type) : 400 ~ 800 AF

Common Ratings

Rated Insulation Voltage, U_i	1,000 V	Suitability for Isolation	Yes
Rated Operational Voltage, U_e	690 V	Utilization Category	A
Rated Impulse Withstand Voltage, U_{imp}	8 kV	Pollution Degree	3
Protection Function	Instantaneous, Short-Circuit Protection	Reference Standard	IEC 60947-2

Model Name		HGM400				HGM630				HGM800		
Frame	(AF)	400				630				800		
Number of Poles	(P)	3				3				3		
Rated Current, at 40 °C	(A)	250, 300, 350, 400				500, 630				700, 800		
Rated Ultimate Short-Circuit Breaking Capacity [Icu] (kA rms)												
Short-Circuit Breaking Category Code		E	S	H	L	E	S	H	L	S	H	L
AC 660/690 V		5	8	10	14	5	8	10	14	8	10	14
AC 480/500 V		18	35	50	65	25	45	50	65	45	50	65
AC 440/460 V		38	50	70	85	38	50	70	85	50	70	85
AC 380/415 V		45	65	85	100	45	65	85	100	65	85	100
AC 220/240 V		50	75	100	125	50	75	100	125	75	100	125
DC 250 V (2P)		20	25	40	40	20	25	40	40	25	40	40
Service Breaking Capacity [$I_{cs} = \% I_{cu}$]		100	100	100	100	100	100	100	100	100	100	100
Rated Short-Circuit Making Capacity [Icm] (kA peak)												
AC 660/690 V		8	14	17	28	8	14	17	28	14	17	28
AC 480/500 V		36	74	105	143	53	95	105	143	95	105	143
AC 440/460 V		80	105	154	187	80	105	154	187	105	154	187
AC 380/415 V		95	143	187	220	95	143	187	220	143	187	220
AC 220/240 V		105	165	220	275	105	165	220	275	165	220	275
DC 250 V (2P)		40	53	84	84	40	53	84	84	53	84	84
Endurance [times] (Durability)												
Mechanical		4,000				2,500				2,500		
Electrical (at 460 V)		1,000				500				500		
Trip Device												
Magnetic	Instantaneous [INST]	10×In				10×In				10×In		
Accessory												
Internal	Auxiliary Switch	AUX	●			●				●		
	Alarm Switch	ALT	●			●				●		
	Shunt Trip	SHT	●			●				●		
	Under-Voltage Trip	UVT	●			●				●		
External	Rotary Handle	Front Contact TFG	●			●				●		
		Extension TFH	●			●				●		
	Mechanical Open/Close Device	MOT	●			●				●		
	Mechanical Interlock	MIF	●			●				●		
	Handle Locking Device	PLD	●			●				●		
	Plug-in	TDM (LINE/LOAD)	● (3P Only)			● (3P Only)				● (3P Only)		
		TDM (LINE Only)	● (3P Only)			● (3P Only)				● (3P Only)		
		TDF (LINE Only)	-			-				-		
		TDA (1 row)	-			-				-		
		TDA (2 rows)	-			-				-		
	Cage Terminal Block	CTB	●			●				●		
	Terminal Cover	TCF	●			●				●		
	Insulation Barrier	TQQ	●			●				●		
	Terminal Bus Bar	TBB	●			●				●		
Installation and Dimensions												
Connection/ Installation	Front Connection		Terminal Screw				Terminal Screw, Terminal Bus Bar					
	Rear Connection		Horizontal/Vertical Cable				Horizontal/Vertical Cable					
	Plug-in		Switchgear (Line & Load, Line Only)				Switchgear (Line & Load, Line Only)					
Dimension (mm)	a (3P)		140				210				210	
	b		257				280				280	
	c		110				110				110	
Weight (kg)	3P		4.5				9.5				9.5	
Detailed Rating and Selection			232 Page				232 Page				232 Page	
Characteristic Curve and Appearance			151 / 169 Page				152 / 170 Page				152 / 170 Page	

Characteristics Curve
(I - t Curve)

Trip Unit Characteristics - Thermal Magnetic

Rated Current (A) In		40	50	63	75	80	100	125
MCCB	HGM50	●		●				
	HGM60	●		●	●			
	HGM100	●		●	●	●	●	
	HGM125	●		●	●	●	●	●
Instantaneous Characteristics li								
Setting Value (A)	10×In	400	500	630	750	800	1,000	1,250
	Max. Non-Tripping Current (A)	320	400	504	600	640	800	1,000
	Min. Tripping Current (A)	480	600	756	900	960	1,200	1,500

Rated Current (A) In		100	125	150	160	175	200	225	250	300	350	400	500	630	700	800
MCCB	HGM160	●	●	●	●											
	HGM250	●	●	●	●	●	●	●	●							
	HGM400								●	●	●	●				
	HGM630											●	●			
	HGM800												●	●		
Instantaneous Characteristics li																
Setting Value (A)	10×In	1,000	1,250	1,500	1,600	1,750	2,000	2,250	2,500	3,000	3,500	4,000	5,000	6,300	7,000	8,000
	Max. Non-Tripping Current (A)	800	1,000	1,200	1,280	1,400	1,600	1,800	2,000	2,400	2,800	3,200	4,000	5,040	5,600	6,400
	Min. Tripping Current (A)	1,200	1,500	1,800	1,920	2,100	2,400	2,700	3,000	3,600	4,200	4,800	6,000	7,560	8,400	9,600

Model Selection Table

ZCT Embedded Molded Case Circuit Breaker (HGM Type) : 32 ~ 250 AF

As a model with a built-in ZCT in MCCB, it is a device that detects grounding when connected to an external ELR (Earth Leakage Relay) that can enhance reliability.

Common Ratings

Rated Insulation Voltage, U_i	1,000 V	Suitability for Isolation	Yes
Rated Operational Voltage, U_e	690 V	Utilization Category	A
Rated Impulse Withstand Voltage, U_{imp}	8 kV	Pollution Degree	3
Protection Function	Overload, Instantaneous, Short-Circuit Protection	Reference Standard	IEC 60947-2

Model Name		HGM30			HGM50			HGM60			
Frame	(AF)	32			50			63			
Number of Poles	(P)	2 ²⁾ , 3, 4 ¹⁾			2 ²⁾ , 3, 4 ¹⁾			2 ²⁾ , 3, 4 ¹⁾			
Rated Current, at 40°C	(A)	16, 20, 25, 32			16, 20, 25, 32, 40, 50			16, 20, 25, 32, 40, 50, 63			
Rated Ultimate Short-Circuit Breaking Capacity [Icu] (kA rms)											
Short-Circuit Breaking Category Code		E	S	E	S	H	L	E	S	H	L
AC 660/690 V		2.5	5	2.5	5	8	10	2.5	5	7.5	8
AC 480/500 V		7.5	10	7.5	10	26	35	7.5	10	14	26
AC 415/440/460 V		16	20	16	20	38	55	16	20	26	30
AC 380 V		18	22	18	22	42	55	18	22	30	31
AC 220/240 V		35	50	35	50	85	100	35	50	50	50
Service Breaking Capacity [Ics = % Icu]		100	100	100	100	100	100	100	100	75	50
Rated Short-Circuit Making Capacity [Icm] (kA peak)											
AC 660/690 V		4	8	4	8	14	17	4	8	13	14
AC 480/500 V		13	17	13	17	55	74	13	17	28	55
AC 415/440/460 V		32	40	32	40	80	121	32	40	55	63
AC 380 V		36	47	36	47	89	121	36	47	63	66
AC 220/240 V		74	105	74	105	187	220	74	105	105	105
DC 250 V (2P)		8	17	8	17	40	63	8	17	30	30
Endurance [times] (Durability)											
Mechanical		30,000			30,000			30,000			
Electrical (at 460 V)		10,000			10,000			10,000			
ZCT Output Characteristics		200 mA/100 mV			200 mA/100 mV			200 mA/100 mV			
Trip Device											
Thermal	Long Time [LTD]	(1.0) × In			(1.0) × In			(1.0) × In			
Magnetic	Instantaneous [INST]	400 A			16 ~ 32 A : 400 A, 40 ~ 50 A : 10 × In			16 ~ 32 A : 400 A, 40 ~ 63 A : 10 × In			
Accessory											
Internal	Auxiliary Switch	AUX	●		●			●			
	Alarm Switch	ALT	●		●			●			
	Shunt Trip	SHT	●		●			●			
	Under-Voltage Trip	UVT	●		●			●			
External	Rotary Handle	Front Contact TFG	●		●			●			
	Extension	TFH	●		●			●			
	Mechanical Open/Close Device	MOT	●		●			●			
	Mechanical Interlock	MIF	●		●			●			
	Handle Locking Device	PLD	●		●			●			
	Plug-in	TDM (LINE/LOAD)	● (3P Only)		● (3P Only)			● (3P Only)			
		TDM (LINE Only)	● (3P Only)		● (3P Only)			● (3P Only)			
		TDF (LINE Only)	● (3P Only)		● (3P Only)			● (3P Only)			
		TDA (1 row)	● (3P Only)		● (3P Only)			● (3P Only)			
		TDA (2 rows)	● (2, 3P Only)		● (2, 3P Only)			● (2, 3P Only)			
	Cage Terminal Block	CTB	●		●			●			
	Terminal Cover	TCF	●		●			●			
	Insulation Barrier	TQQ	●		●			●			
	Terminal Bus Bar	TBB	-		-			-			
Installation and Dimensions											
Connection/ Installation	Front Connection		Terminal Screw								
	Rear Connection		Horizontal/Vertical								
	Plug-in		Switchgear (Line & Load, Line Only), Distribution Panel								
Dimension (mm)	DIN Rail Installation		Possible if DIN Rail adaptor is used		-		Possible if DIN Rail adaptor is used				
	a (2/3/4P)		75/75/100		75/75/100		90/90/120		75/75/100		
	b		130		130		155		130		
	c		68		68		68		68		
Weight (kg)		2/3/4P	0.7/0.8/1.0		0.7/0.8/1.0		0.9/1.0/1.3		0.7/0.8/1.0		
Detailed Rating and Selection			232 Page		232 Page		232 Page		232 Page		
Characteristic Curve and Appearance			149 / 166 Page		149 / 166 Page		150 / 167 Page		149 / 166 Page		

* 1) 4 Pole Arrangement : Basic specification of R-S-T-N

2) As for 2P products, only the neutral pole in the 3P product has been eliminated so the dimension is equivalent to the 3P product.

HGM100				HGM125				HGM160				HGM250			
100 2 2) 3, 4 1)		125 2 2) 3, 4 1)		160 2 2) 3, 4 1)		250 2 2) 3, 4 1)									
16, 20, 25, 32, 40, 50, 63, 75, 80, 100		16, 20, 25, 32, 40, 50, 63, 75, 80, 100, 125		100, 125, 150, 160		100, 125, 150, 160, 175, 200, 225, 250									
E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L
2.5	5	7.5	8	5	7.5	8	10	7.5	8	8	10	7.5	8	8	10
7.5	10	14	26	10	14	26	35	14	20	26	35	14	20	26	35
16	20	26	30	20	26	38	55	20	26	38	55	20	26	38	55
18	22	30	31	22	30	42	55	22	30	42	55	22	30	42	55
35	50	50	50	50	65	85	100	50	65	85	100	50	65	85	100
100	100	75	50	100	100	100	100	100	100	100	100	100	100	100	100
4	8	13	14	8	13	14	17	8	13	14	17	8	13	14	17
13	17	28	55	17	28	55	74	17	28	55	74	17	28	55	74
32	40	55	63	40	55	80	121	40	55	80	121	40	55	80	121
36	47	63	66	47	63	89	121	47	63	89	121	47	63	89	121
74	105	105	105	105	143	187	220	105	143	187	220	105	143	187	220
8	17	30	30	17	30	40	63	17	30	40	63	17	30	40	63
30,000				30,000				25,000				25,000			
10,000				10,000				10,000				10,000			
200 mA/100 mV				200 mA/100 mV				200 mA/100 mV				200 mA/100 mV			
(1.0) × In				(1.0) × In				(1.0) × In				(1.0) × In			
16 ~ 32 A : 400 A, 40 ~ 100 A : 10 × In				16 ~ 32 A : 400 A, 40 ~ 125 A : 10 × In				10 × In				10 × In			
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	-	-	-	-	-	-	-	-
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	-	-	-	-	-	-	-	-
● (2, 3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	-	-	-	-	-	-	-	-
●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Terminal Screw								Terminal Screw, Terminal Bus Bar							
Horizontal/Vertical								Horizontal/Vertical							
Switchgear (Line & Load, Line Only), Distribution Panel								Switchgear (Line & Load, Line Only)							
Possible if DIN Rail adaptor is used				-				-				-			
75/75/100				90/90/120				105/105/140				105/105/140			
130				155				165				165			
68				68				68				68			
0.7/0.8/1.0				0.9/1.0/1.3				1.1/1.3/1.7				1.1/1.3/1.7			
232 Page				232 Page				232 Page				232 Page			
149 / 166 Page				150 / 167 Page				151 / 168 Page				151 / 168 Page			

Model Selection Table

ZCT Embedded Molded Case Circuit Breaker (HGM Type) : 400 ~ 800 AF


Common Ratings

Rated Insulation Voltage, U_i	1,000 V	Suitability for Isolation	Yes
Rated Operational Voltage, U_e	690 V	Utilization Category	A
Rated Impulse Withstand Voltage, U_{imp}	8 kV	Pollution Degree	3
Protection Function	Overload, Instantaneous, Short-Circuit Protection	Reference Standard	IEC 60947-2

Model Name	HGM400				HGM630				HGM800					
Frame (AF)	400				630				800					
Number of Poles (P)	2 ²⁾ , 3, 4 ¹⁾				2 ²⁾ , 3				2 ²⁾ , 3					
Rated Current, at 40 °C (A)	250, 300, 350, 400				500, 630				700, 800					
Rated Ultimate Short-Circuit Breaking Capacity [Icu] (kA rms)														
Short-Circuit Breaking Category Code	E	S	H	L	E	S	H	L	S	H	L			
AC 660/690 V	5	8	10	14	5	8	10	14	8	10	14			
AC 480/500 V	18	35	50	65	25	45	50	65	45	50	65			
AC 440/460 V	38	50	70	85	38	50	70	85	50	70	85			
AC 380/415 V	45	65	85	100	45	65	85	100	65	85	100			
AC 220/240 V	50	75	100	125	50	75	100	125	75	100	125			
Service Breaking Capacity [Ics = % Icu]	100	100	100	100	100	100	100	100	100	100	100			
Rated Short-Circuit Making Capacity [Icm] (kA peak)														
AC 660/690 V	8	14	17	28	8	14	17	28	14	17	28			
AC 480/500 V	36	74	105	143	53	95	105	143	95	105	143			
AC 440/460 V	80	105	154	187	80	105	154	187	105	154	187			
AC 380/415 V	95	143	187	220	95	143	187	220	143	187	220			
AC 220/240 V	105	165	220	275	105	165	220	275	165	220	275			
DC 250 V (2P)	40	53	84	84	40	53	84	84	53	84	84			
Endurance [times] (Durability)														
Mechanical	4,000				2,500				2,500					
Electrical (at 460 V)	1,000				500				500					
ZCT Output Characteristics	200 mA/100 mV				200 mA/100 mV				200 mA/100 mV					
Trip Device														
Thermal	Long time [LTD]				(1.0) × In				(1.0) × In					
Magnetic	Instantaneous [INST]				10 × In				10 × In					
Accessory														
Internal	Auxiliary Switch	AUX	●		●		●		●		●			
	Alarm Switch	ALT	●		●		●		●		●			
	Shunt Trip	SHT	●		●		●		●		●			
	Under-Voltage Trip	UVT	●		●		●		●		●			
External	Rotary Handle	Front Contact TFG	●		●		●		●		●			
		Extension TFH	●		●		●		●		●			
	Mechanical Open/Close Device	MOT	●		●		●		●		●			
	Mechanical Interlock	MIF	●		●		●		●		●			
	Handle Locking Device	PLD	●		●		●		●		●			
	Plug-in	TDM (LINE/LOAD)	● (3P Only)		● (3P Only)		● (3P Only)		● (3P Only)		● (3P Only)			
		TDM (LINE Only)	● (3P Only)		● (3P Only)		● (3P Only)		● (3P Only)		● (3P Only)			
		TDF (LINE Only)	-		-		-		-		-			
	TDA (1 row)	-	-		-		-		-		-			
		TDA (2 rows)	-		-		-		-		-			
	Cage Terminal Block	CTB	●		●		●		●		●			
	Terminal Cover	TCF	●		●		●		●		●			
	Insulation Barrier	TQQ	●		●		●		●		●			
	Terminal Bus Bar	TBB	●		●		●		●		●			
Installation and Dimensions														
Connection/ Installation	Front Connection	Terminal Screw				Terminal Screw, Terminal Bus Bar								
	Rear Connection	Horizontal/Vertical Cable				Horizontal/Vertical Cable								
	Plug-in	Switchgear (Line & Load, Line Only)				Switchgear (Line & Load, Line Only)								
Dimension (mm)	a (2/3/4P)	140/140/184				210/210				210/210				
	b	257				280				280				
	c	110				110				110				
Weight (kg)	2/3/4P	4/4.5/5.4				8.7/9.5				8.7/9.5				
Detailed Rating and Selection			232 Page				232 Page				232 Page			
Characteristic Curve and Appearance			151 / 169 Page				152 / 170 Page				152 / 170 Page			

※ 1) 4 Pole Arrangement : Basic specification of R-S-T-N

2) As for 2P products, only the neutral pole in the 3P product has been eliminated so the dimension is equivalent to the 3P product.



Trip Unit Characteristics - Thermal Magnetic

Model Selection Table

Earth Leakage Circuit Breaker (HGE Type) : 32 ~ 250 AF

Common Ratings

Rated Operational Voltage, Ue	AC 220/460 V	Suitability for Isolation	Yes
Usable Voltage Range	AC 187 ~ 506 V	Utilization Category	A
Rated Impulse Withstand Voltage, Uimp	6 kV	Pollution Degree	3
Protection Function	Earth Leakage, Overload, Instantaneous, Short-Circuit Protection	Reference Standard	IEC 60947-2

Model Name		HGE30	HGE50			HGE60		
Frame	(AF)	32	50			63		
Number of Poles	(P)	2 ²⁾ , 3, 4 ¹⁾	2 ²⁾ , 3, 4 ¹⁾			2 ²⁾ , 3, 4 ¹⁾		
Rated Current, at 40 °C	(A)	16, 20, 25, 32	16, 20, 25, 32, 40, 50			16, 20, 25, 32, 40, 50, 63		
High Speed Type								
Adjustable Residual Current	(mA)	30	30			30		
Max. Operational Time	(s)	0.1	0.1			0.1		
Time Delay Type								
Adjustable Residual Current	(mA)	100 - 300 - 500 - 1,000 Adjustable	100 - 300 - 500 - 1,000 Adjustable			100 - 300 - 500 - 1,000 Adjustable		
Maximum Operational Time	(s)	0.1 - 0.4 - 1.0 - 2.0	0.1 - 0.4 - 1.0 - 2.0			0.1 - 0.4 - 1.0 - 2.0		
Inertial Delay Time	(ms)	0 - 200 - 500 - 1,000 Adjustable	0 - 200 - 500 - 1,000 Adjustable			0 - 200 - 500 - 1,000 Adjustable		
Rated Ultimate Short-Circuit Breaking Capacity [lcu] (kA rms)								
Short-Circuit Breaking Category Code	E	S	E	S	H	L	E	S
AC 415/440/460 V	16	20	16	20	38	55	16	20
AC 380 V	16	22	18	22	42	55	18	22
AC 220/240V	35	50	35	50	85	100	35	50
Service Breaking Capacity [Ics = % lcus]	100	100	100	100	100	100	100	75
Rated Short-Circuit Making Capacity [lcm] (kA peak)								
AC 415/440/460 V	32	40	32	40	80	121	32	40
AC 380 V	36	47	36	47	89	121	36	47
AC 220/240 V	74	105	74	105	187	220	74	105
Endurance [times] (Durability)								
Mechanical		30,000		30,000			30,000	
Electrical (at 460 V)		10,000		10,000			10,000	
Trip Device								
Thermal	Long Time [LTD]	(1.0) × In		(1.0) × In			(1.0) × In	
Magnetic	Instantaneous [INST]	400 A		16 ~ 32 A : 400 A, 40, 50 A : 10 × In			16 ~ 32 A : 400 A, 40 ~ 63 A : 10 × In	
Accessory								
Internal	Auxiliary Switch	AUX	●		●		●	
	Alarm Switch	ALT	●		●		●	
	Shunt Trip	SHT	-		-		-	
	Under-Voltage Trip	UVT	-		-		-	
External	Rotary Handle	Front Contact TFG	●		●		●	
		Extension TFH	●		●		●	
	Mechanical Open/Close Device	MOT	●		●		●	
	Mechanical Interlock	MIF	●		●		●	
	Handle Locking Device	PLD	●		●		●	
	Plug-in	TDM (LINE/LOAD)	● (3P Only)	● (3P Only)	● (3P Only)		● (3P Only)	
		TDM (LINE Only)	● (3P Only)	● (3P Only)	● (3P Only)		● (3P Only)	
		TDF (LINE Only)	● (3P Only)	● (3P Only)	● (3P Only)		● (3P Only)	
		TDA (1 row)	● (3P Only)	● (3P Only)	● (3P Only)		● (3P Only)	
		TDA (2 rows)	● (2, 3P Only)	● (2, 3P Only)	● (2, 3P Only)		● (2, 3P Only)	
	Cage Terminal Block CTB		●		●		●	
	Terminal Cover TCF		●		●		●	
	Insulation Barrier TQO		●		●		●	
	Terminal Bus Bar TBB		-		-		-	
Installation and Dimensions								
Connection/ Installation	Front Connection		Terminal Screw					
	Rear Connection		Horizontal/Vertical					
	Plug-in		Switchgear (Line & Load, Line Only), Distribution Panel					
Dimension (mm)	DIN Rail Installation	Possible if DIN Rail adaptor is used		-		Possible if DIN Rail adaptor is used		
	a (2/3/4P)	75/75/100	75/75/100		90/90/120		75/75/100	
	b	130	130		155		130	
	c	68	68		68		68	
Weight (kg)	2/3/4P	0.8/0.9/1.3	0.8/0.9/1.3	1.0/1.1/1.4		0.8/0.9/1.3		
Detailed Rating and Selection		232 Page	232 Page	232 Page		232 Page		
Characteristic Curve and Appearance		149 / 171 Page	149 / 171 Page	150 / 172 Page		149 / 171 Page		

※ 1) 4 Pole Arrangement : Basic specification of R-S-T-N

2) As for 2P products, only the neutral pole in the 3P product has been eliminated so the dimension is equivalent to the 3P product.

Model Selection Table

Earth Leakage Circuit Breaker (HGE Type) : 400 ~ 800 AF


Common Ratings

Rated Operational Voltage, Ue	AC 220/460 V	Suitability for Isolation	Yes
Usable Voltage Range	AC 187 ~ 506 V	Utilization Category	A
Rated Impulse Withstand Voltage, Uimp	6 kV	Pollution Degree	3
Protection Function	Earth Leakage, Overload, Instantaneous, Short-Circuit Protection	Reference Standard	IEC 60947-2



Model Name	HGE400	HGE630	HGE800		
Frame (AF)	400	630	800		
Number of Poles (P)	2 ²⁾ , 3, 4 ¹⁾	2 ²⁾ , 3	2 ²⁾ , 3		
Rated Current, at 40 °C (A)	250, 300, 350, 400	500, 630	700, 800		
High Speed Type					
Adjustable Residual Current (mA)	30	30	30		
Max. Operational Time (s)	0.1	0.1	0.1		
Time Delay Type					
Adjustable Residual Current (mA)	100 - 300 - 500 - 1,000 Adjustable	100 - 300 - 500 - 1,000 Adjustable	100 - 300 - 500 - 1,000 Adjustable		
Max. Operational Time (s)	0.1 - 0.4 - 1.0 - 2.0	0.1 - 0.4 - 1.0 - 2.0	0.1 - 0.4 - 1.0 - 2.0		
Inertial Delay Time (ms)	0 - 200 - 500 - 1,000 Adjustable	0 - 200 - 500 - 1,000 Adjustable	0 - 200 - 500 - 1,000 Adjustable		
Rated Ultimate Short-Circuit Breaking Capacity [Icu] (kA rms)	E S H L	E S H L	E S H L		
Short-Circuit Breaking Category Code	38 50 70 85	38 50 70 85	50 70 85		
AC 440/460 V	38	50	70		
AC 380/415 V	45	65	85		
AC 220/240 V	50	75	100		
Service Breaking Capacity [Ics = % Icu]	100	100	100		
Rated Short-Circuit Making Capacity [Icm] (kA peak)	80 105 154 187	80 105 154 187	105 154 187		
AC 440/460 V	80	105	154		
AC 380/415 V	95	143	187		
AC 220/240 V	105	165	220		
Endurance [times] (Durability)					
Mechanical	4,000	2,500	2,500		
Electrical (at 460 V)	1,000	500	500		
Trip Device					
Thermal	Long Time [LTD]	(1.0) × In	(1.0) × In		
Magnetic	Instantaneous [INST]	10 × In	10 × In		
Accessory					
Internal	Auxiliary Switch	AUX	●		
	Alarm Switch	ALT	●		
	Shunt Trip	SHT	●		
	Under-Voltage Trip	UVT	●		
External	Rotary Handle	Front Contact TFG	●		
	Extension	TFH	●		
	Mechanical Open/Close Device	MOT	●		
	Mechanical Interlock	MIF	●		
	Handle Locking Device	PLD	●		
	Plug-in	TDM (LINE/LOAD) TDM (LINE Only) TDF (LINE Only) TDA (1 row) TDA (2 rows)	● (3P Only) ● (3P Only) - - -	● (3P Only) ● (3P Only) - - -	● (3P Only) ● (3P Only)
	Cage Terminal Block	CTB	●	●	●
	Terminal Cover	TCF	●	●	●
	Insulation Barrier	TQQ	●	●	●
	Terminal Bus Bar	TBB	●	●	●
Installation and Dimensions					
Connection/ Installation	Front Connection	Terminal Screw	Terminal Screw, Terminal Bus Bar		
	Rear Connection	Horizontal/Vertical Cable	Horizontal/Vertical Cable		
	Plug-in	Switchgear (Line & Load, Line Only)	Switchgear (Line & Load, Line Only)		
Dimension (mm)	a (2/3/4P)	140/140/184	210/210	210/210	
	b	257	280	280	
	c	110	110	110	
Weight (kg)	3/4P	4/4.5/5.4	8.7/9.5	8.7/9.5	
Detailed Rating and Selection		232 Page	232 Page	232 Page	
Characteristic Curve and Appearance		151 / 174 Page	152 / 175 Page	152 / 175 Page	

* 1) 4 Pole Arrangement : Basic specification of R-S-T-N

2) As for 2P products, only the neutral pole in the 3P product has been eliminated so the dimension is equivalent to the 3P product.



Over-Current Protection Characteristics

Earth Leakage Protection Characteristics
(Time Delay Type)


Trip Unit Characteristics - Thermal Magnetic

Rated Current (A) In		16	20	25	32	40	50	63	75	80	100	125
ELCB	HGE30	●	●	●	●							
	HGE50	●	●	●	●	●	●					
	HGE60	●	●	●	●	●	●	●				
	HGE100	●	●	●	●	●	●	●	●	●	●	
	HGE125	●	●	●	●	●	●	●	●	●	●	●
Moment Characteristics I_r												
Setting Value (A)	$1.0 \times I_n$	16	20	25	32	40	50	63	75	80	100	125
Instantaneous Characteristics I_i												
Setting Value (A)	$10 \times I_n$ (Min. 400 A)				400		500	630	750	800	1,000	1,250
	Max. Non-Tripping Current (A)				320		400	504	600	640	800	1,000
	Min. Operational Current (A)				480		600	756	900	960	1,200	1,500
Rated Non-Operational Time $I_{\Delta n}$												
High-Speed Type												Fixed : 30 mA
Time Delay Type												Adjustable : 100 - 300 - 500 - 1,000 mA
Inertial Propagation Time Δt												
High-Speed Type												Fixed : 0 ms
Time Delay Type												Adjustable : 0 - 200 - 500 - 1,000 ms
Neutral Pole Protection												
4P3D												Unprotected
4P4D												-

Rated Current (A) In		100	125	150	160	175	200	225	250	300	350	400	500	630	700	800
ELCB	HGE160	●	●	●	●											
	HGE250	●	●	●	●	●	●	●	●	●	●	●				
	HGE400															
	HGE630												●	●		
	HGE800												●	●		
Moment Characteristics I_r																
Setting Value (A)	$1.0 \times I_n$	100	125	150	160	175	200	225	250	300	350	400	500	630	700	800
Instantaneous Characteristics I_i																
Setting Value (A)	$10 \times I_n$	1,000	1,250	1,500	1,600	1,750	2,000	2,250	2,500	3,000	3,500	4,000	5,000	6,300	7,000	8,000
	Max. Non-Tripping Current (A)	800	1,000	1,200	1,280	1,400	1,600	1,800	2,000	2,400	2,800	3,200	4,000	5,040	5,600	6,400
	Min. Operational Current (A)	1,200	1,500	1,800	1,920	2,100	2,400	2,700	3,000	3,600	4,200	4,800	6,000	7,560	8,400	9,600
Rated Non-Operational Time $I_{\Delta n}$																
High-Speed Type																Fixed : 30 mA
Time Delay Type																Adjustable : 100 - 300 - 500 - 1,000 mA
Inertial Propagation Time Δt																
High-Speed Type																Fixed : 0 ms
Time Delay Type																Adjustable : 100 - 200 - 500 - 1,000 ms
Neutral Pole Protection																
4P3D																Unprotected
4P4D																-



Model Selection Table

Trip Unit's Model Name and Function (Thermal Magnetic)



Overcurrent Protection	Instantaneous Current Protection	TRIP Unit Name								
		HGP50D	HGP125D	HGP160D	HGP100	HGP160	HGP250	HGP400	HGP630	HGP800
Fixed	Fixed			MTM - 16 - FF			MTM - 25 - FF		MTM - 63 - FF	MTM - 80 - FF
Adjustable	Fixed			MTM - 16 - JF			MTM - 25 - JF		MTM - 63 - JF	MTM - 80 - JF
Adjustable	Adjustable			-			MTM - 25 - JJ		MTM - 63 - JJ	MTM - 80 - JJ


Trip Unit Characteristics – Thermal Magnetic HGP50D, 125D, 160D



Rated Current (A) In	16	20	25	32	40	50	63	75	80	100	125	150	160	
MCCB	HGP50D	●	●	●	●	●	●							
	HGP125D	●	●	●	●	●	●	●	●	●	●	●		
	HGP160D													
	HGP100				●	●	●	●	●	●	●	●		
Moment Characteristics Ir	1.0×In	16	20	25	32	40	50	63	75	80	100	125	150	160
Fixed (FF)	1.0×In													
	0.7×In ¹⁾					28 ¹⁾	35 ¹⁾	44 ¹⁾	53 ¹⁾	56 ¹⁾	70 ¹⁾			
Adjustable (JF, JJ)	0.8×In	13	16	20	26	32	40	50	60	64	80	100	120	128
	0.9×In	14	18	23	29	36	45	57	68	72	90	113	135	144
	1.0×In	16	20	25	32	40	50	63	75	80	100	125	150	160
Instantaneous Characteristics li	10×In	160	200	250	320	400	500	630	750	800	1,000	1,250	1,500	1,600
Fixed (FF, JF)	Max. Non-Tripping Current (A)	128	160	200	256	320	400	504	600	640	800	1,000	1,200	1,280
	Min. Tripping Current (A)	192	240	300	384	480	600	756	900	960	1,200	1,500	1,800	1,920
Neutral Pole Protection	4P3D (Neutral Unprotected)	●	●	●	●	●	●	●	●	●	●	●	●	●
4P4D (Neutral Protected 100 % Ir)	●	●	●	●	●	●	●	●	●	●	●	●	●	●

¹⁾ Only applicable to HGP100

Trip Unit Characteristics – Thermal Magnetic HGP250, 400, 630, 800




Rated Current (A) In	100	125	150	160	175	200	225	250	300	350	400	500	630	700	800	
MCCB	HGP100	● 1)														
	HGP160	●	●	●	●											
	HGP250		●	●	●	●	●	●								
	HGP400								●	●	●					
	HGP630										●	●				
	HGP800											●	●			
Moment Characteristics Ir																
Fixed (FF)	1.0×In	100	125	150	160	175	200	225	250	300	350	400	500	630	700	800
Adjustable (JF, JJ)	0.7×In	70	88	105	112	123	140	158	175							
	0.8×In	80	100	120	128	140	160	180	200	240	280	320	400	504	560	640
	0.9×In	90	113	135	144	158	180	203	225	270	315	360	450	567	630	720
	1.0×In	100	125	150	160	175	200	225	250	300	350	400	500	630	700	800
Instantaneous Characteristics li																
Fixed (FF, JF)	10×In	1,000	1,250	1,500	1,600	1,750	2,000	2,250	2,500	3,000	3,500	4,000	5,000	6,300	7,000	8,000
Adjustable (JJ)	Max. Non-Tripping Current (A)	800	1,000	1,200	1,280	1,400	1,600	1,800	2,000	2,400	2,800	3,200	4,000	5,040	5,600	6,400
	Min. Tripping Current (A)	1,200	1,500	1,800	1,920	2,100	2,400	2,700	3,000	3,600	4,200	4,800	6,000	7,560	8,400	9,600
	5×In	500	625	750	800	875	1,000	1,125	1,250	1,500	1,750	2,000	2,500	3,150	3,500	4,000
	Max. Non-Tripping Current (A)	400	500	600	640	700	800	900	1,000	1,200	1,400	1,600	2,000	2,520	2,800	3,200
	Min. Tripping Current (A)	600	750	900	960	1,050	1,200	1,350	1,500	1,800	2,100	2,400	3,000	3,780	4,200	4,800
	6×In	600	750	900	960	1,050	1,200	1,350	1,500	1,800	2,100	2,400	3,000	3,780	4,200	4,800
	Max. Non-Tripping Current (A)	480	600	720	768	840	960	1,080	1,200	1,440	1,680	1,920	2,400	3,024	3,360	3,840
	Min. Tripping Current (A)	720	900	1,080	1,152	1,260	1,440	1,620	1,800	2,160	2,520	2,880	3,600	4,536	5,040	5,760
	7×In	700	875	1,050	1,120	1,225	1,400	1,575	1,750	2,100	2,450	2,800	3,500	4,410	4,900	5,600
	Max. Non-Tripping Current (A)	560	700	840	896	980	1,120	1,260	1,400	1,680	1,960	2,240	2,800	3,528	3,920	4,480
	Min. Tripping Current (A)	840	1,050	1,260	1,344	1,470	1,680	1,890	2,100	2,520	2,940	3,360	4,200	5,292	5,880	6,720
	8×In	800	1,000	1,200	1,280	1,400	1,600	1,800	2,000	2,400	2,800	3,200	4,000	5,040	5,600	6,400
	Max. Non-Tripping Current (A)	640	800	960	1,024	1,120	1,280	1,440	1,600	1,920	2,240	2,560	3,200	4,032	4,480	5,120
	Min. Tripping Current (A)	960	1,200	1,440	1,536	1,680	1,920	2,160	2,400	2,880	3,360	3,840	4,800	6,048	6,720	7,680
	9×In	900	1,125	1,350	1,440	1,575	1,800	2,025	2,250	2,700	3,150	3,600	4,500	5,670	6,300	7,200
	Max. Non-Tripping Current (A)	720	900	1,080	1,152	1,260	1,440	1,620	1,800	2,160	2,520	2,880	3,600	4,536	5,040	5,760
	Min. Tripping Current (A)	1,080	1,350	1,620	1,728	1,890	2,160	2,430	2,700	3,240	3,780	4,320	5,400	6,804	7,560	8,640
	10×In	1,000	1,250	1,500	1,600	1,750	2,000	2,250	2,500	3,000	3,500	4,000	5,000	6,300	7,000	8,000
	Max. Non-Tripping Current (A)	800	1,000	1,200	1,280	1,400	1,600	1,800	2,000	2,400	2,800	3,200	4,000	5,040	5,600	6,400
	Min. Tripping Current (A)	1,200	1,500	1,800	1,920	2,100	2,400	2,700	3,000	3,600	4,200	4,800	6,000	7,560	8,400	9,600
Neutral Pole Protection																
4P3D (Neutral Unprotected)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
4P4D (Neutral Protected 100 % Ir)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	

※ 1) HGP100 100 A product is only applicable to Instantaneous fixed type.


Model Selection Table

Trip Unit's Model Name and Function (ETU)

ETU Part Name



LCD Display / ICON (N Type is not applicable)



ETU Type / AF









Type	Model (AF)	Trip Unit				
		40	100	160	250	250
Normal Type					ETU-25-N	ETU-63-N
Display Type					ETU-25-D	ETU-63-D
Ammeter Type					ETU-25-A	ETU-63-A
Energy-meter Type					ETU-25-E	ETU-63-E
						ETU-80-N
						ETU-80-D
						ETU-80-A
						ETU-80-E

Trip Unit Characteristics – Electronic Type

	N	D	A	E	Remark
HMI	Dial 2 EA	• Dial 2 EA, Key Button 4 EA • Segment LCD	• Dial 2 EA, Key Button 4 EA • Segment LCD	• Dial 2 EA, Key Button 4 EA • Segment LCD	Dial Setting (Ir, Isd)
Protection	• L (Dial) • S (Dial) • I (Fixed) • IN (Dial)	• L (Dial, Key Button) • S (Dial) • I (Key Button) • G (Key Button) • IN (Dial)	• L (Dial, Key Button) • S (Dial) • I (Key Button) • G (Key Button) • IN (Dial)	• L (Dial, Key Button) • S (Dial) • I (Key Button) • G (Key Button) • IN (Dial)	L, S time to be changed by key button
Measurement		• IR, IS, IT, IN, IG	• IR, IS, IT, IN, IG • Iavg, Imax, Imin	• IR, IS, IT, IN, IG • Iavg, Imax, Imin • V, phase to neutral, phase to phase, P, total/per phase, power factor Q, total/per phase S, total/per phase Active(kW), Reactive(kVAr), Apparent(kVA) F, THD (I, V, per phase, VLN, VLL) Harmonic (15 th), Demand I, P	
History / Event	• 20 Trip information (damaged phase, type, time)	• 20 Trip information (damaged phase, type, time)	• 20 Trip information (damaged phase, type, time) • 32 System Event	• 20 Trip information (damaged phase, type, time) • 32 System Event	External power required DC 24 V
Power	• Self-Power	• Self-Power	• Self-Power External power input (24 V DC)	• Self-Power ¹⁾ External power input (24 V DC)	
Battery	●	●	●	●	External power required DC 24 V
Add-on function	• Test terminal	• Test terminal	• Test terminal • ZSI OUT : 250 AF • ZSI IN/OUT : 630 AF, 800 AF • Trip / Alarm Counter • Operating time 50 % In Over - 24 h	• Test terminal • ZSI OUT : 250 AF • ZSI IN/OUT : 630 AF, 800 AF • Trip / Alarm Counter • Operating time 50 % In Over - 24 h	
Communication			• RS-485 MODBUS-RTU	• RS-485 MODBUS-RTU	External power required DC 24 V
Indication	• LED 3 ea • Run LED / Trip LED Alarm LED (90 % off, 110 % on)	• LED 3 ea • Run LED / Trip LED Alarm LED (90 % off, 110 % on)	• LED 3 ea • Run LED / Trip LED Alarm LED (90 % off, 110 % on)	• LED 3 ea • Run LED / Trip LED Alarm LED (90 % off, 110 % on)	

※ 1) ETU self-power active current
Under 250A : over 30%In
Etc. : over 15%In

Trip Unit Overview

Type	ETU N	ETU D	ETU A	ETU E
Protection Elements	 <ul style="list-style-type: none"> For protecting the switchgear / general industry L, S, I 	 <ul style="list-style-type: none"> For protecting the switchgear / general industry L, S, I, G 	 <ul style="list-style-type: none"> For protecting the switchgear / general industry L, S, I, G 	 <ul style="list-style-type: none"> For protecting the switchgear / general industry L, S, I, G
Trip Unit	 250 AF  630 AF  800 AF	 250 AF  630 AF  800 AF	 250 AF  630 AF  800 AF	 250 AF  630 AF  800 AF
Setting and Display	<ul style="list-style-type: none"> Use the dial to set the pick-up for LT and ST. The setting of time delay has been fixed for operation.  LT pick-up setting  ST pick-up setting	<ul style="list-style-type: none"> A user can set LT and ST pick-up with a dial. A user can set the time delay for operation with a keypad. A user can set a pick-up and time delay of Instantaneous and grounding operation with a keypad. A user can move around information displayed on the LED window and set relaying with Menu, Up, Down, and Enter button.  LT pick-up setting  ST pick-up setting	<ul style="list-style-type: none"> It displays load and trip status, which are in use, on the LED window. 	<ul style="list-style-type: none"> It displays load and trip status, which are in use, on the LED window. 
	<ul style="list-style-type: none"> A user can check battery replacement time by pressing the keypad with the battery symbol. 	<ul style="list-style-type: none"> A user can check battery replacement time on the LED window. 		

※ A battery is consumable. 6 years of use is guaranteed under normal working conditions.

※ Even if the battery is discharged, the trip function of the ETU operates.

Model Selection Table

Trip Unit – Basic (N Type)

Protection

Overload : Long Time Protection Fixed Time Delay (I_{rd})

It protects the system from overload through fixed operation time and adjustable setting range.

Short Circuit : Short time Protection Fixed Time Delay (I_{sd})

It protects the system from short-circuit accidents through fixed operation time and adjustable setting range.

Short Circuit : Instantaneous Protection (I_i)

It protects the system from short-circuit accidents with a fixed setting range.

Neutral Wire : Neutral Protection (I_{in})


- A 3-phase circuit breaker does not protect a neutral wire.
 - In a 4-phase circuit breaker, a setting range is set with a regulating device (dial) to protect the neutral wire.
 - OFF : It does not protect a neutral wire.
 - 0.5 ①) : It protects a neutral wire at 0.5 I_r (x in).
 - 1 : It protects a neutral wire at 1 I_r (x in).
 - 1.6 : It protects a neutral wire at 1.6 I_r (x in).
- However, when it exceeds 0.63 A (rated current) in the setting range, a neutral wire is protected at 1 I_r (x in).

※ ①) It is set to 16 A or higher.

Display

Status LED

- RUN LED : It informs the operation status of a circuit breaker.
- Trip LED : It turns on when a circuit breaker operates.
- Alarm LED : It turns off at $I > 0.9 \times I_r$ and turns on at $I > 1.1 \times I_r$.
- Battery Check : It checks battery replacement time by pressing the N-Type Battery Check button.
 - Usable : 3 LED lamps turn on.
 - Replacement Time : One Alarm LED turns on.




Protection Setting Range

N Type

		L Long-Time Protection												
		Pick-up [A]	$I_r = I_n x$	Dial Setting	0.4	0.45	0.5	0.56	0.63	0.7	0.8	0.9	1	
t	I	Time Delay [s]	Accuracy $\pm 20\%$	tr =	1.5 $\times I_r$	378								
					6 $\times I_r$	16								
					7.2 $\times I_r$	11								
		Thermal Memory				20 minutes								
		S Short-Time Protection												
		Pick-up [A]	Accuracy $\pm 15\%$	$I_{sd} = I_r x$	dial setting	1.5	2	3	4	5	6	7	8	10
		Time Delay [s]		tsd =	Fixed									
					Non Tripping Time	0.08								
					Max Time	0.14								
		I Instantaneous Protection												
		Pick-up [A]	Accuracy $\pm 15\%$	$I_i =$	$I_n = 40 A$	600								
					$I_n = 100 A$	1,500								
					$I_n = 160 A$	2,400								
					$I_n = 250 A$	3,000								
					$I_n = 400 A$	4,800								
					$I_n = 630 A$	6,900								
					$I_n = 800 A$	8,800								
		Time Delay [s]			Maximum Time	≤ 0.05								
		IN Neutral Protection												
		Pick-up	$IN = I_r x$		OFF	0.5	1	1.6						

Technical Data (ETU)

Circuit Diagram



ETU A/E

Power
- (Black), + (Red) : 24V DC Power Supply

ZSI (Zone Selective Interlocking)

Z1 : ZSI OUT 0

Z2 : ZSI OUT 1

Z3 : ZSI IN 0

Z4 : ZSI IN 1


※ Z1-Z3 and Z2-Z4 are connected.

※ Z3 and Z4 are usable for HGP400, 630, and 800.

※ ZSI signal line to connect should not be longer than 3 meters.

E Voltage Measurement

ZSI Circuit Diagram



※ 1) 24V power cable spec.

- Min : 0.5mm², Max : 1.5mm²

2) Communication cable spec*

- Min : 0.5mm², Max : 1.5mm²

- Shield twisted pair

*Communication cable is not included.

※ Watch out cable direction(+) when customer connect 24V power cable.

- Please refer to □ marked point on left diagram.

- Damage can be occurred in case of reverse or wrong connection.

Internal Options Related to HGP Electronic Type

Type	Image	Features	Type	Image	Features
FAL 250 AF 630 AF 800 AF		Transmits a fault signal of ETU Indicator Fault Alarm LED	DC 24 V Terminal Block		ETU Trip Unit The options for the connection of "A" and "E" type to the external power source Easy to connect a power cable between the products ※ The same purpose as DC 24 V power cable
DC 24 V Power Cable		ETU Trip Unit The options for the connection of "A" and "E" type to the external power source (DC 24 V) - 1.5 m	DC 3.6 V Battery		A replaceable battery is necessary for the function of saving the ETU time and accidents. - 10 EA vinyl packing

External Options Related to HGP Electronic Type

Type	Image	Features
Test Kit		The external options used to test and set an electronic product.

Trip Unit – D/A/E Type


Display

It displays the setting info. of a trip unit and key measured values on the LCD window.

- D/A Type : Current
- E Type : Current, voltage, and energy

When it is connected with an external power source, it becomes possible to check a trip unit info. and set it even with the MCCB (molded case circuit breaker) open. The following functions activate when it is connected to an external power source.

- Connects with a communication system
- Displays trip info.




Test Terminal

For its maintenance, ETU has a test terminal at the front. When the test terminal is connected to the ETU test kit, it is possible to set the ETU and simulate a trip operation.

Test Kit Composition

- A dedicated adapter (AC 100 ~ 220 V 50/60 Hz)
- A dedicated cable to connect the ETU test terminal
- A user manual



Metering

Metering

The trip unit types (D, A, and E) display each phase and current to a neutral wire in RMS. A user can check information in each phase displayed with the Up and Down button.

The A type measures current and the E type provides information of voltage, power, and energy through a display device and communication.

Power Quality

The E type displays total harmonic distortion (THD) of load current and voltage, and 15th order harmonic waves. The relevant information is sent to a PC or a monitor through MODBUS communication.


Alarm Contact (FAL)

As an additional option, an alarm switch can be constructed only for ETU operations not connected with the MCCB trip alarm switch.


FAL Output Characteristics

Static Outputs : AC 100 ~ 220 V, 64 mA max

FAL Structure and Terminal



FAL Circuit Diagram




※ A lamp is not provided.

Technical Data (ETU)

Operation and Setting – ETU LCD

The ETU LCD provides a user with information of load status and relay settings.



It displays current metering on the default screen.

A user can move to the metering screen to display with the buttons.

In case there is information on phases in the metering screen, it turns sequentially (phase after phase) every 3 seconds.

With the button, a user can move around the screens (Current, Voltage, Power, and Energy).

Metering Display

Model	Mode	Order	Description
D/A/E	1	Instantaneous Current I1	R/A 250
	2	Instantaneous Current I2	S/B 250
	3	Instantaneous Current I3	T/C 250
	4	Instantaneous Neutral Current IN (4P or with ENCT)	N 0
	5	Instantaneous Ground Current Ig	A 20

Model	Mode	Order	Description
E	6	Phase to Phase Voltage U12	R/A S/B 380
	7	Phase to Phase Voltage U23	S/B T/C 380
	8	Phase to Phase Voltage U31	R/A T/C 380
	9	Phase to Phase Voltage V1N	R/A 220
	10	Phase to Phase Voltage V2N	S/B 220

Metering Display

Model	Mode	Order	Description		Model	Mode	Order	Description	
E		11	Phase to Phase Voltage V3N	V T/C	E		15	Active Energy Ep (readout and reset)	k Wh R/A S/B T/C
		12	Total Active Power Ptot	k W R/A S/B T/C			16	Reactive Energy Eq (readout and reset)	kVArh R/A S/B T/C
		13	Total Reactive Power Qtot	kVAR R/A S/B T/C			17	Apparent Energy Es (readout and reset)	kVA h R/A S/B T/C
		14	Total Apparent Power Stot	kVA R/A S/B T/C					

Setting Information Display

A user can check the relay settings on the default display screen with the button.

A user moves around the setting screens with the button.

Model	Mode	Order	Description		Model	Mode	Order	Description	
D/A/E		1	Ir Long Time Protection Pickup Value	A Ir= R/A S/B T/C	D/A/E		7	li Instantaneous Protection Pickup Value (N phase is display when it is 4P or with ENCT.)	A R/A S/B T/C
		2	Ir Long Time Protection Neutral Pickup Value (4P or with ENCT)	A Ir= N			8	Ig Ground Fault Protection Pickup Value	A Ig= N R/A S/B T/C
		3	tr Long Time Protection Time Delay @ 6 Ir	s Tr=			9	tg Ground Fault Protection Time Delay Value - ON : I ² t Active - OFF : I ² t Reactive	s Tg=
		4	Isd Short Time Protection Pickup Value	A Isd= R/A S/B T/C			10	Communication Address : 1~250	A
		5	Isd Short Time Protection Neutral Pickup Value (4P or with ENCT)	A Isd= N			11	Communication Baud Rate b 9.6 : 9600 bps b 19.2 : 19200 bps b 38.4 : 38400 bps	A
		6	tsd Short Time Protection Time Delay - ON : I ² t Active - OFF : I ² t Reactive	s Tsd=					

Technical Data (ETU)

Operation and Setting – ETU LCD

Setting Information Display

Model	Mode	Order	Description
D/A/E		12	<p>Thermal ON/OFF ON/OFF Check</p>

Setting Change Screen

To change the ETU settings, keep pressing the two buttons + for more than 3 seconds and the Lock symbol disappears. Then a user can change the settings. When no entry has been made for 10 seconds or the button is pressed, the Lock symbol is displayed automatically. A user moves around the setting screens with the buttons. (Mode :

1. Relay Setting

1	Ir Setting Screen 	+ > 3 Seconds Hold The Lock Symbol Disappears.	
1.1	The Lock Symbol Not Seen 	 Flashing + The State of Changing The Settings	
1.2	Ir Setting 	 Setting The Current Value a User Wants Step 1 A Fine Adjustment and Dial Adjustment (~ Max Dial Settings)	
1.3	Saving Ir Settings 	 Saving The Settings	
2	tr Setting Screen 	 Move Flashing + The State of Changing The Settings	
2.1	tr Setting and Saving 	 Setting the desired trip time. : 0.5 ~ 16 Saving The Settings	
3	Isd Setting Screen Move 	 Move	

Setting Change Screen

1. Relay Setting

3.1	Isd Setting Screen 	 Pickup Range Dial Setting : 1.5 ~ 10	 Isd= R/A S/B T/C
4	tsd Setting Screen 	 Move Flashing + The State of Changing The Settings	 Tsd= OFF
4.1	tsd Setting and Saving 	 Time Delay Setting - OFF.1 : I^2t OFF 0.1 s - On.4 : I^2t ON 0.4 s Saving The Settings	 Tsd= 0.4 s
5	lg Setting 	 Move Flashing + The State of Changing The Settings	 lg= 0.2
5.1	lg Setting and Saving 	 Pickup Range : 0.2 ~ $1 \times In$ Saving The Settings	 lg= 0.2
6	tg Setting 	 Move Flashing + The State of Changing The Settings	 tg= OFF
6.1	tg Setting and Saving 	 Time Delay Setting : 0.1 ~ 0.4 - OFF.1 : I^2t OFF 0.1 s - On.4 : I^2t ON 0.4 s Saving The Settings	 tg= 0.4 s
7	li Setting 	 Move Flashing + The State of Changing The Settings	 li= R/A S/B T/C
7.1	li Setting and Saving 	 Pickup Range : 1.5 ~ $11 \times In$ N is displayed when it is 4P or with ENCT. Saving The Settings	 li= R/A S/B T/C
8	IN Setting 	 Move Setting with The Pickup Range Dial. OFF - 0.5 - 1 - 1.6	 IN= OFF

Technical Data (ETU)

Operation and Setting – ETU LCD

Setting Change Screen

2. Communication Settings Address (A/E)			
9	Communication Address Setting Screen  	 +  > 3 Seconds Hold The Lock Symbol Disappears.	
9.1	The Lock Symbol Disappears. 	 Flashing + The State of Changing The Settings	
9.2	Setting 	 Address Setting : 1 ~ 250	
9.3	Saving Settings 	 Save	
10	Communication Baud Rate Setting Screen  	 +  > 3 Seconds Hold The Lock Symbol Disappears.	
10.1	The Lock Symbol Disappears. 	 Flashing + The State of Changing The Settings	
10.2	Setting 	 Setting The Desired Communication Speed. b 9.6 : 9600 bps b 19.2 : 19200 bps b 38.4 : 38400 bps	
10.3	Saving Settings 	 Save	

Setting Change Screen

Basically, the MCCB has thermal characteristics. The thermal functions are aimed to prevent a fire caused by heat and a device from it by simulating the thermal energy of a bus-bar, which runs at a regular phase.

When a user wants to deactivate the functions in a certain situation, he or she can do so by setting on the setting screen as follows.

3. Thermal On/Off (A/E)

11	Thermal On/Off Screen 	Move Setting Display	
11.1	Thermal On/Off Setting 	Flashing + The State of Changing The Settings Setting Change - ON : Thermal ON - OFF : Thermal OFF I^2t Applying	
11.2	Thermal On/Off Saving 	Save	
11.3	Thermal On/Off Screen 	Move The Screen	

Reset

Energy Reset (Active, Reactive, Apparent) E Type

1	Energy Metering Screen 	+ >3 Seconds Hold The Lock Symbol Disappears.	
2	The Lock Symbol Disappears. 	A Measured Value Flashes.	
3	Energy Reset 	Energy Values Reset.	
6	Return to The Energy Metering Screen 		

Model Selection Table

Motor Protection Type of Molded Case Circuit Breaker (HGP Type) : 100 ~ 800 AF

The circuit breaker for motor protection is a circuit breaker for instantaneous trip (magnetic only) equipped with instantaneous and short circuit protection functions only, it is suitable for protecting the motor by assembling it together with the overcurrent relay/ electronic connector.

Common Ratings

Rated Insulation Voltage, U_i	1,000 V	Suitability for Isolation	Yes
Rated Operational Voltage, U_e	690 V	Utilization Category	A
Rated Impulse Withstand Voltage, U_{imp}	8 kV	Pollution Degree	3
Protection Function	Instantaneous, Short-Circuit Protection	Reference Standard	IEC 60947-2

Model Name	HGP100				HGP250			
Frame (AF)	100				250			
Number of Poles (P)	3				3			
Rated Current, at 40 °C (A)	2.5, 3.2, 6.3, 12.5, 20, 32, 50, 63, 80, 100				125, 150, 175, 200, 225, 250			
Rated Short-Circuit Breaking Capacity [Icu] (kA rms)								
Short-Circuit Breaking Category Code	F* ¹⁾	S	H	X	F* ¹⁾	S	H	X
AC 660/690 V	6	8	8	10	6	8	8	10
AC 480/500 V	25	50	65	100	25	50	65	100
AC 440/460 V	36	65	85	150	36	65	85	150
AC 380/415 V	50	85	100	150	50	85	100	150
AC 220/240 V	65	100	130	200	65	100	130	200
Service Breaking Capacity [Ics = % Icu]	100	100	100	100	100	100	100	100
Rated Short-Circuit Making Capacity [Icm] (kA peak)								
AC 660/690 V	9	14	14	17	9	14	14	17
AC 480/500 V	53	105	143	220	53	105	143	220
AC 440/460 V	76	143	187	330	76	143	187	330
AC 380/415 V	105	187	220	330	105	187	220	330
AC 220/240 V	143	220	286	440	143	220	286	440
Endurance [times] (Durability)								
Mechanical	25,000				25,000			
In @ 440 V	10,000				10,000			
Trip Device								
Thermal Magnetic	Long Time [LTD] Instantaneous [INST]	-	●		(6 - 7 - 8 - 9 - 10 - 11 - 12 - 13 - 14) × In		●	-
Electronic	Long Time [LTD] Short Time [STD] Instantaneous [INST]	-	-	-	-	-	-	-
Accessory								
Internal	Auxiliary Switch AUX Alarm Switch ALT Shunt Trip SHT Under-Voltage Trip UVT	●	●	●	●	●	●	●
External	Rotary Handle Front Contact TFG Extension TFH Mechanical Open/Close Device MOT Mechanical Interlock MIF Handle Locking Device PLD Plug-in TDM (LINE/LOAD) TDM (LINE Only) Cage Terminal Block CTB Terminal Cover TCF Insulation Barrier TQQ Terminal Bus Bar TBB	●	●	●	● (3P Only) ● (3P Only)	● (3P Only) ● (3P Only)	●	●

Installation and Dimensions		
Connection/ Installation	Front Connection Rear Connection Plug-in	Terminal Screw, Terminal Bus Bar Horizontal/Vertical Cable Switchgear (Line & Load, Line Only)
Dimension (mm)	a b c	105 165 86.5
Weight (kg)	3/4P	2/2.6
Detailed Rating and Selection	234 Page	234 Page
Characteristic Curve and Appearance	157 / 177 Page	157 / 177 Page

* 1) F type is for overseas sales.

HGP400				HGP630				HGP800			
F ¹⁾	S	H	X	F ¹⁾	S	H	X	F ¹⁾	S	H	X
400				630				800			
3				3				3			
350, 400				500, 630				700, 800			
10	10	20	35	10	10	20	35	10	10	20	35
25	50	70	100	25	50	70	100	25	50	70	100
36	70	85	150	36	70	85	150	36	70	85	150
50	85	100	150	50	85	100	150	50	85	100	150
65	100	130	200	65	100	130	200	65	100	130	200
100	100	100	100	100	100	100	100	100	100	100	100
17	17	40	74	17	17	40	74	17	17	40	74
53	105	154	220	53	105	154	220	53	105	154	220
76	154	187	330	76	154	187	330	76	154	187	330
105	187	220	330	105	187	220	330	105	187	220	330
143	220	286	440	143	220	286	440	143	220	286	440
20,000				20,000				10,000			
6,000				4,000				3,000			
●	-	-	-	●	-	-	-	●	-	-	-
(5 - 6 - 7 - 8 - 9 - 10) × In				(5 - 6 - 7 - 8 - 9 - 10) × In				(5 - 6 - 7 - 8 - 9 - 10) × In			
-				-				-			
-				-				-			
-				-				-			
-				-				-			
●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	●	●
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)
140				140				210			
260				260				320			
110				110				135			
5.4/7.2				5.4/7.2				15.1/19.6			
234 Page				234 Page				234 Page			
158 / 178 Page				158 / 178 Page				158 / 179 Page			

Model Selection Table

Trip Unit Characteristics



Model Selection Table

Switch Disconnectors (HGP NA Type) : 50 ~ 800 AF

Switch disconnector is a short circuit switch without protection function and as the appearance is equivalent to the circuit breaker, all accessories can be shared with the circuit breaker.

Common Ratings

Rated Insulation Voltage, U_i	1,000 V	Suitability for Isolation	Yes
Rated Operational Voltage, U_e	690 V	Utilization Category	AC 22 A/AC 23 A - DC 22 A/DC 23 A
Rated Impulse Withstand Voltage, U_{imp}	8 kV	Pollution Degree	3

Model Name	HGP50DNA	HGP125DNA	HGP160DNA
Frame (AF)	50	125	160
Number of Poles (P)	3, 4 ¹⁾	3, 4 ¹⁾	3, 4 ¹⁾
Conventional Thermal Current, I_{th} at 60 °C (A)	50	125	160
Rated Operational Current [Ie]			
AC 690V (50/60 Hz)	50	125	160
DC 250 V (1 Pole)	50	125	160
DC 250 V (2 Pole in Series)	50	125	160
Rated Short-Circuit Making Capacity [Icm] (kA Peak)	2.1	2.8	3.6
Rated Short-Time Withstand Current [Icw]			
1s (Arms)	1,800	2,200	2,200
3s (Arms)	1,800	2,200	2,200
20 s (Arms)	690	960	960
Endurance [times] (Durability)			
Mechanical	25,000	25,000	25,000
In @ 440 V	10,000	10,000	10,000
Accessory			
Internal	Auxiliary Switch	AUX	●
	Alarm Switch	ALT	●
	Shunt Trip	SHT	●
	Under-Voltage Trip	UVT	●
External	Rotary Handle	Front Contact TFG	●
	Extension	TFH	●
	Mechanical Open/Close Device	MOT	●
	Mechanical Interlock	MIF	●
	Handle Locking Device	PLD	●
	Plug-in	TDM (LINE/LOAD)	● (3P Only)
		TDM (LINE Only)	● (3P Only)
	Cage Terminal Block	CTB	●
	Terminal Cover	TCF	●
	Insulation Barrier	TQQ	●
Installation and Dimensions			
Connection/Installation	Front Connection	Terminal Screw	
	Rear Connection	Horizontal/Vertical Cable	
	Plug-in	Switchgear (Line & Load, Line Only)	
Dimension (mm)	a (3/4P)	90/120	90/120
	b	140	140
	c	86	86
Weight (kg)	3/4P	1.5/1.8	1.5/1.8
Detailed Rating and Selection		234 Page	234 Page
Characteristic Curve and Appearance		176 Page	176 Page

* 1) 4 Pole Arrangement : Basic specification of R-S-T-N

Applicable Field of Switch – Disconnectors

- Bus bar connection and disconnection
- Disconnection of switchgear and control panel
- Switch for emergency power switchover (ATS)

HGP250NA	HGP400NA	HGP630NA	HGP800NA
250	400	630	800
3,4 ¹⁾	3,4 ¹⁾	3,4 ¹⁾	3,4 ¹⁾
250	400	630	800
250	400	630	800
250	400	630	800
250	400	630	800
4.9	7.1	8.5	12
3,500	5,000	6,300	8,000
3,500	5,000	6,300	8,000
1,350	1,920	2,320	2,560
25,000	20,000	20,000	10,000
10,000	6,000	4,000	3,000
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)
● (3P Only)	● (3P Only)	● (3P Only)	● (3P Only)
●	●	●	●
●	●	●	●
●	●	●	●
●	●	●	●
Terminal Screw	Terminal Screw	Terminal Screw	Terminal Screw
Horizontal/Vertical Cable	Horizontal/Vertical Cable	Horizontal/Vertical Cable	Horizontal/Vertical Cable
Switchgear (Line & Load, Line Only)			
105/140	140/186.5	140/186.5	210/280
165	260	260	320
86.5	110	110	135
2/2.6	5.4/7.2	5.4/7.2	15.1/19.6
234 Page	234 Page	234 Page	234 Page
177 Page	178 Page	178 Page	179 Page

Model Selection Table

Molded Case Circuit Breaker (HGP DC Type)

Common Ratings

Rated Insulation Voltage, U_i	1,000 V	Suitability for Isolation	Yes
Rated Impulse Withstand Voltage, U_{imp}	8 kV	Utilization Category	A
Protection Function	Overload, Instantaneous, Short-Circuit Protection	Pollution Degree	3

Model Name		HGP100				HGP160								
Frame	(AF)	100				160								
Number of Poles	(P)	3, 4 ¹⁾				3, 4 ¹⁾								
Rated Current, at 40 °C	(A)	40, 50, 63, 80, 100				100, 125, 150, 160								
Rated Ultimate Short-Circuit Breaking Capacity [Icu] (kA rms)														
Short-Circuit Breaking Category Code		F	S	H	X	F	S	H	X					
DC 750 V for 3P		10	55	85	100	10	55	85	100					
DC 1,000 V for 4P		10	55	85	100	10	55	85	100					
Service Breaking Capacity [$I_{cs} = \% I_{cu}$]		100	100	100	100	100	100	100	100					
Trip Device														
Thermal Magnetic	Long Time [LTD]	$(0.7 - 0.8 - 0.9 - 1.0) \times I_n$				$(0.7 - 0.8 - 0.9 - 1.0) \times I_n$								
	Instantaneous [INST]	$10 \times I_n$				$(5 - 6 - 7 - 8 - 9 - 10) \times I_n$								
Accessory														
Internal	Auxiliary Switch	AUX	●		●									
	Alarm Switch	ALT	●		●									
	Shunt Trip	SHT	●		●									
	Under-Voltage Trip	UVT	●		●									
External	Rotary Handle	Front Contact	TFG	●		●								
		Extension	TFH	●		●								
	Mechanical Open/Close Device	MOT	●		●									
	Mechanical Interlock	MIF	●		●									
	Handle Locking Device	PLD	●		●									
	Cage Terminal Block	CTB	●		●									
	Insulation Barrier	TQQ	●		●									
	Terminal Bus Bar	TBB	●		●									
	Series Busbar	SBB	●		●									
Installation and Dimensions														
Connection/Installation	Front Connection	Terminal Screw, Terminal Bus Bar				Terminal Screw, Terminal Bus Bar								
Dimension (mm)	a (3/4P)	105/140				105/140								
	b	165				165								
	c	86.5				86.5								
Weight (kg)	3/4P	2/2.6				2/2.6								
Detailed rating and Selection		234				234								
Characteristic Curve and Appearance		157 / 229				157 / 229								
Certification	CB-DEKRA	●				●								

* 1) 4 Pole Arrangement : Basic specification of R-S-T-N

Technical Data (HGP DC Type)

Installation


Precautions for Use

Please keep in mind the following installation conditions when applying the product to a solar power system. Otherwise, it could lead to damage to the product and the system.

Circuit Diagram

Referring to the contact circuit diagram below, connect the adjacent poles in series.

In the case where a 3P product is used for a 2P product, connect it skipping the phase(s) in the middle.



Connection

In wiring the circuit, a wire must be at least as long as 60 cm.

If it is shorter than that, it can produce excessive heat.

When using the busbar, operate it referring to the Rated Current Derating Table on the right.

When using a self-produced busbar, please keep it to the dimension on page 229 ~ 230. And it is recommended to plate it (busbar) with silver or tin. (A busbar and a heat sink are optional. You need to make an additional order if you want it.) (SBB 25/63/80 GP)

Insulation

Please insert a barrier between the phases after connecting a busbar or a cable if they do not use the same phase.

External Environment

In the case that the internal temperature of the panel is above 40 °C, derate the temperature, referring to the Rated Current Derating Table on the right.

Technical Data

Environmental Operating Conditions

Temperature Derating


The overcurrent characteristic of MCCB has been set to the ambient temperature of 40 °C. If the ambient temperature is less or more than 40 °C, the overcurrent characteristics may differ.

If the Ambient Temperature is less than 40 °C

In order to ensure that the circuit breaker's overcurrent meet the derating curve at the given ambient temperature, the real current (I_r) has to be adjusted. The temperature correction ratio or each MCCB is shown in the circuit breaker's characteristics curve.

If the Ambient Temperature is more than 40 °C

As the internal temperature of MCCB is a sum of increased temperature due to current flow and the ambient temperature, if the ambient temperature exceeds 40 °C, thermal damage of internal insulation material of MCCB may occur causing the circuit breaker to trip at an early stage. When applying ambient temperature higher than 40 °C, the rated current must be adjusted as shown in the following rated current correction table.



I_n (Rated Current) :

Circuit breaker's rating at ambient temperature of 40 °C

I_r (Real Current) :

Circuit breaker's rating at the given temperature


$$I_r = \text{Correction Ratio (\%)} \times I_n$$

Rated Current Derating Table : HGP DC Type/Standard Mounting (Fixed Type)


Model	Rated Current (A _c)	Ambient Temperature (°C)									Connection	
		10	20	30	40	45	50	55	60	65		
HGP100 HGP160 HGP250	40	46	44	42	40	39	38	37	36	35	34	HGP250 Busbar
	50	58	55	53	50	49	48	46	45	44	43	
	63	72	69	66	63	61	60	58	57	55	54	
	80	92	88	84	80	78	76	74	72	70	68	
	100	115	110	105	100	98	95	93	90	88	85	
	125	144	138	131	125	122	119	116	113	109	106	
	150	173	165	158	150	146	143	139	135	131	128	
	160	184	176	168	160	156	152	148	144	140	136	
	175	201	193	184	175	171	166	162	158	153	149	
	200	230	220	210	200	195	190	185	180	175	170	
HGP400 HGP630	225	259	248	236	225	219	214	208	203	197	191	HGP250 Busbar + Heat Sink
	250	288	275	263	250	244	238	231	225	219	213	
	300	323	315	308	300	291	282	273	264	255	246	
	350	376	368	359	350	340	330	320	310	300	290	
	400	430	420	410	400	388	376	364	352	340	328	
HGP800	500	538	525	513	500	485	470	455	440	425	410	HGP630 Busbar + Heat Sink
	630	677	662	646	630	611	592	573	554	535	516	
	700	753	735	718	700	679	658	637	616	595	574	
	800	860	840	820	800	776	752	728	704	680	656	

Accessory

HGM General-Type



※ 1) DIN Rail Adaptor (DRA) : For HGM/HGE100





HGM Type MCCB

- | | | |
|--------------------------------------|---------------------------------------|---|
| ① Plug-in Device (TDA, TDM, TDF) | ⑧ Terminal Cover (General-Type) (TCF) | ⑯ Motor Operator (MOT) |
| ② Terminal Cover (For Plug-in) (TCP) | ⑨ Padlock (PLD) | ⑰ Front Contact Rotary Handle (TFG) |
| ③ Bus Bar (TBB) | ⑩ Rear Connection Terminal (RCT) | ⑱ Extension Rotary Handle (TFH) |
| ④ Insulation Barrier (TQQ) | ⑪ Shunt Trip Switch (SHT) | ⑲ Plug-in Terminal Block (CBM) |
| ⑤ DIN Rail Adaptor (DRA) | ⑫ Under-Voltage Trip Switch (UVT) | ⑳ Plug-in Terminal Block (CBB BLOCK UNIT) |
| ⑥ Mechanical Interlock (MIF) | ⑬ Auxiliary Switch (AUX) | ㉑ Plug-in Terminal Block (CBB PLATE) |
| ⑦ Lug Terminal (CTB) | ⑭ Trip Alarm Switch (ALT) | ㉒ Plug-in Terminal (PC MALE) |

Accessory

HGP High Breaking Capacity







HGP Type MCCB

- | | | |
|---|-----------------------------------|---|
| ① Plug-In Device (TDM) | ⑧ Padlock (PLD) | ⑮ Front Contact Rotary Handle (TFG) |
| ② Terminal Cover (For Plug-in) (TCF Short Type) | ⑨ Rear Connection Terminal (RCT) | ⑯ Extension Rotary Handle (TFH) |
| ③ Bus Bar (TBB) | ⑩ Auxiliary Switch (AUX) | ⑰ Auxiliary Handle (THA) |
| ④ Insulation Barrier (TQQ) | ⑪ Trip alarm Switch (ALT) | ⑱ Plug-in Terminal Block (CBM) |
| ⑤ Mechanical Interlock MIF | ⑫ Shunt trip Switch (SHT) | ⑲ Plug-in Terminal Block (CBB BLOCK UNIT) |
| ⑥ Lug Terminal (CTB) | ⑬ Under-Voltage Trip Switch (UVT) | ⑳ Plug-in Terminal Block (CBB PLATE) |
| ⑦ Terminal Cover (General-Type) (TCF Long Type) | ⑭ Motor Operator (MOT) | ㉑ Plug-in Terminal (PC MALE) |


Internal Accessories (HGM)




HGM30, 50E/S, 60, 100



HGM50H/L, 125



HGM160, 250



Possible Installation Combinations (Below 250 AF)

Type	Pole	AUX		ALT		SHT		UVT		AXT		AUX		AUX		SHT		UVT		SHT		UVT		
													ALT	ALT	AUX	AUX	ALT	ALT	AXT	AXT				
HGM30 ~ HGM125	2																							
HGM30 ~ HGM250	3/4																							
HGE30 ~ HGE250	2/3/4																							



* AUX : Auxiliary Switch □ / ALT : Alarm Switch ■ / SHT : Shunt Trip □ / UVT : Under-Voltage Trip □ / AXT : Auxiliary Alarm Switch □■ (AUX/ALT Integrated Type)

HGM Type's Internal Accessories and Possible Location for Installation

- Auxiliary Switch (AUX)
- Alarm Switch (ALT)
- Auxiliary + Trip Alarm Switch (AXT)
- Shunt Trip Coil (SHT)
- Under-Voltage Trip Coil (UVT)

HGM630, 800

HGM400



Possible Installation Combinations (400 ~ 800 AF)

Left Side of Handle Right Side of Handle
Breaker Handle

Type	Pole	AUX	ALT	SHT	UVT	AUX	SHT	UVT	SHT	UVT	SHT	UVT
						ALT	AUX	AUX	ALT	ALT	AUX	AUX
HGM400	2/3/4											
HGM630 HGM800	2/3 4RSTN											
HGM630 HGM800	4NRST											
HGE400	2/3/4											
HGE630 HGE800	2/3											

※ AUX : Auxiliary Switch □ / ALT : Alarm Switch ■ / SHT : Shunt Trip □ / UVT : Under-Voltage Trip □
HGM Type's ZCT embedded type of product can be combined equally as HGE Type.

Internal Accessories (HGM)

Auxiliary Switch (AUX) / Trip Alarm Switch (ALT)

It is a contact for indicating the status of the circuit breaker in a remote position.

This contact can be used to realize not only the indication function but also electrical functions such as electrical lock and relay.

Auxiliary Switch (AUX)

- Indicates the ON/OFF status of the circuit breaker contact.
- Status is OFF during TRIP.
- It is comprised of C contact.

Auxiliary + Trip Alarm Switch (AXT)

- This switch is an integrated combination of auxiliary switch and trip alarm switch.

Contact Circuit Diagram

	Auxiliary Switch (AUX)	Trip Alarm Switch (ALT)
MCCB ON		
MCCB OFF		
MCCB TRIP		

Rating of Contact

Rated Conventional Thermal Current	5 A	
Minimum Load	160 mA, 5 VDC	
Rated Operation Current	Resistive Load	Inductive Load
AC 125 V	5 A	3 A
AC 250 V	3 A	2 A
DC 30 V	4 A	3 A
DC 125 V	0.4 A	0.4 A
DC 250 V	0.2 A	0.2 A

Trip Alarm Switch (ALT)

- It is only activated when the circuit breaker has tripped due to an overload, short circuit or operation of shunt trip switch and does not operate during general ON/OFF.
- Returns to original state when circuit breaker has been reset.
- It is comprised of C contact.

Possible Location for Installation

Type	Pole	AUX	ALT	AXT
HGM30 ~ HGM125	2			
HGM30 ~ HGM250	3/4			
HGE30 ~ HGE250	2/3/4			
HGM400	2/3/4			
HGE400	2/3/4			
HGM630 ~ HGM800	2/3/4			
HGE630 ~ HGE800	2/3			

※ AUX : Auxiliary Switch □

ALT : Alarm Switch ■

AXT : Auxiliary Alarm Switch □■ (AUX/ALT Integrated Type)



AUX



ALT

Shunt Trip Device (SHT)

Shunt trip device (SHT) is a device that remotely trips the circuit breaker by applying voltage to both terminals of the coil.

Operating Condition


- $U \geq 0.7 \times U_n$ (More than 70 % of rated voltage applied)
- As for impulse type voltage, more than 20 ms applied

Rated Voltage and Characteristics (100 ~ 250 AF)

Rated voltage (Un)	Power Consumption	
	VA (W)	A (A)
DC	24 V	50.2
	48 V	94.6
	60 V	91.2
	100 ~ 120 V	11.8
	125 V	58.1
	100 ~ 120 V	75.2
AC (50/60 Hz)	200 ~ 250 V	64.8
	380 ~ 480 V	131
Rated Operational Voltage		0.7 ~ 1.1 × Un
Operating Time		50 ms


※ Controller output voltage : DC 45 V

SHT Wiring



※ Not applicable to
HGM400, 630, 800 AF DC 24 V

2. HGM400, 630, 800 AF DC 24 V
(SHT + Controller)



Possible Location for Installation

Type	Pole	SHT	UVT
HGM30 ~ HGM125	2		
HGM30 ~ HGM250	3/4		
HGE30 ~ HGE250	2/3/4		
HGM400	2/3/4		
HGE400	2/3/4		
HGM630 HGM800	2/3/4		
HGE630 HGE800	2/3		

※ SHT : Shunt Trip
UVT : Under-Voltage Trip



Internal Accessories (HGM)

Under-Voltage Trip Device (UVT)

In case the circuit voltage drops to less than 35 % of the rated voltage (U_n), UVT automatically initiates a trip in the circuit breaker to prevent damage to the load.

Opening Conditions


- Operating characteristics are guaranteed to conform to the IEC 60947-2 standard criteria.
- Trip Condition of Circuit Breaker : $U \leq 0.35 \times U_n$
- Fixed Type : 50 ms (400 ~ 800 AF)
- Time Delay Type : 500 ~ 1,000 ms (Below 250 AF)
- No Trip Condition of Circuit Breaker : $U \geq 0.7 \times U_n$
- In the $U = 0.35 \sim 0.7 \times U_n$ interval, the circuit breaker can be tripped but the operation is not guaranteed.

Time Delay Function

Malfunction is prevented during a short momentary voltage drop of below 500 ms. (Below 250 AF)

UVT Wiring

1. HGM30 ~ 250 AF (UVT + Controller)



※ DC 24 V among HGM400 and above products require a controller.

2. HGM400, 630, 800 AF (UVT Only)



Closing Conditions

- In case of circuit breakers assembled with UVT, the circuit breaker cannot be ON (Closing) when voltage is not applied to the UVT.
- The reset operation after the circuit breaker's trip caused by UVT operation may differ depending on the circuit breaker's type and UVT structure.
- In order to close the circuit breaker, Voltage must be applied to UVT.
- Closing Condition : $U \geq 0.85 \times U_n$

Rated Voltage and Characteristics (Below 250 AF)

Rated Voltage (U_n)	Power Consumption	
	VA (W)	A (mA)
DC	24 V	0.96
	48 V	1.1
	100 ~ 110 V	2.2
	100 ~ 120 V	5.1
AC (50/60 Hz)	200 ~ 230 V	6
	380 ~ 415 V	9.6
	440 ~ 480 V	12.5
	Starting Voltage	0.35 ~ 0.7 × U_n
Opening		0.85 × U_n
Closing		0.85 × U_n
Rated Operational Voltage	0.85 ~ 1.1 × U_n	
Operating Time	500 ~ 1,000 ms	

※ Do not use UVT for electrical interlocking system.

※ Controller output voltage : DC 45 V



UVT




UVT Controller

Internal Accessories (HGP)

HGP Type's Internal Accessories and Possible Location for Installation

- Auxiliary Switch (AUX)
- Alarm Switch (ALT)
- Shunt Trip Coil (SHT)
- Under-Voltage Trip Coil (UVT)
- Fault Alarm Contact (FAL), Only for Electronic



Possible Location for Installation

Type	Pole	AUX	ALT	SHT	UVT	SHT AUX	SHT ALT	UVT AUX	UVT ALT	SHT AUX	UVT AUX
HGP50D HGP125D HGP160D	3/4										
HGP250	3/4										
HGP400 HGP630	3/4										
HGP800	3/4										

※ AUX : Auxiliary Switch □ / ALT : Alarm Switch ■ / SHT : Shunt Trip □ / UVT : Under-Voltage Trip □ / AXT : Auxiliary Alarm Switch □■ (AUX/ALT Integrated Type)

Internal Accessories (HGP)

Auxiliary Switch (AUX)/ Trip Alarm Switch (ALT)

It is a contact for indication to inform the status of the circuit breaker in a remote position.

This contact can be used to realize not only the indication function but also electrical functions such as electrical lock and relay.

Auxiliary Switch (AUX)

- Indicates the ON/OFF status of the circuit breaker contact.
- Status is OFF during TRIP.
- It is comprised of C contact.

Trip Alarm Switch (ALT)

- It is only activated when the circuit breaker has tripped due to an overload, short circuit or operation of shunt trip switch and does not operate during general ON/OFF.
- Returns to original state when circuit breaker has been reset.
- It is comprised of C contact.

Contact Circuit Diagram

	Auxiliary Switch (AUX)	Trip Alarm Switch (ALT)
MCCB ON		
MCCB OFF		
MCCB TRIP		

Possible Location for Installation

Type	AUX	ALT
HGP50D HGP125D HGP160D		
HGP250		
HGP400 HGP630		
HGP800		

Rating of Contact

Rated Conventional Thermal Current	5 A	
Minimum Load	160 mA, 5 VDC	
Rated Operation Current	Resistive Load	Inductive Load
AC	125 V	5 A
	250 V	3 A
DC	30 V	4 A
	125 V	0.4 A
	250 V	0.2 A
		0.2 A



HGP160D ALT



HGP250 ~ 800 ALT
HGP160D ~ 800 AUX

Shunt Trip Device (SHT) / Under-Voltage Device (UVT)

SHT/UVT is installed inside the circuit breaker and it offers the function of remote tripping the circuit breaker by controlling the voltage applied to both terminals of the coil.

Shunt Trip Device (SHT)

It is able to remotely trip the circuit breaker by applying voltage to the shunt trip device installed in the circuit breaker.

Operating Condition

- $U \geq 0.7 \times Un$ (More than 70 % of rated voltage applied)
- As for impulse type voltage, more than 20 ms applied

Rated Voltage and Characteristics


Rated Voltage (Un)	Power Consumption	
	W or VA	A (mA)
DC	24 V	1.2
	100 ~ 110 V	2.8
	100 ~ 120 V	3.3
AC (50/60 Hz)	200 ~ 230 V	5.2
	380 ~ 415 V	13.9
	440 ~ 480 V	10.9
		22.8
Rated Operational Voltage	0.7 ~ 1.1 × Un	
Operating Time	50 ms	

※ Controller output voltage : DC 45 V


Possible Location for Installation

Type	SHT	UVT
HGP50D		
HGP125D		
HGP160D		
HGP250		
HGP400		
HGP630		
HGP800		

SHT Wiring



UVT Wiring



Under-Voltage Device (UVT)

If the under-voltage trip device is installed in the circuit breaker, the circuit breaker is tripped or is not closed in case the circuit voltage is below the reference value.

In case the circuit voltage drops to less than 35 % of the rated voltage (Un), UVT automatically initiates a trip in the circuit breaker to prevent damage to the load.

Opening Conditions

- Operating characteristics are guaranteed to conform to the IEC 60947-2 standard criteria.
- Trip Condition of Circuit Breaker : $U \leq 0.35 \times Un$
- No Trip Condition of Circuit Breaker : $U \geq 0.7 \times Un$
- In the $U = 0.35 \sim 0.7 \times Un$ interval, the circuit breaker can be tripped but the operation is not guaranteed.

Closing Conditions

- In case of circuit breakers assembled with UVT, the circuit breaker can be OFF/RESET when voltage is not applied but the circuit breaker cannot be ON (Closing).
- In order to close the circuit breaker, Voltage must be applied to UVT.
- Closing Condition : $U \geq 0.85 \times Un$

Rated Voltage and Characteristics

Rated Voltage (Un)	Power Consumption	
	Pick Up	
	W or VA	A (mA)
DC	24 V	2.6
	100 ~ 110 V	5
	100 ~ 120 V	4.5
AC (50/60 Hz)	200 ~ 230 V	5.6
	380 ~ 415 V	10.8
	440 ~ 480 V	12.5
	Opening	0.35 ~ 0.7 × Un
Starting Voltage	Closing	0.85 × Un
Rated Operational Voltage	0.85 ~ 1.1 × Un	
Operating Time	50 ms	

※ Do not use UVT for electrical interlocking system.

※ Controller output voltage : DC 45 V



HGP50D ~ 160D SHT/
UVT



HGP250
SHT/UVT



HGP400 ~ 800 SHT/
UVT



UVT Controller

External Accessories (HGM)

Locking Device

Handle Locking Device Using Padlock (PLD)

This device is used for locking the handle of circuit breaker to the OFF position by using a padlock. Padlock is not provided separately and up to 3 can be used. The applicable specifications of padlocks are as below.

Type	Application	Padlock Diameter ¹⁾
PLD 10GM	HGM30 ~ HGM250	5 mm
	HGE30 ~ HGE250	
PLD 40GM	HGM400 ~ HGM800	6 mm
	HGE400 ~ HGE800	

Mechanical Interlock

This device interlocks two circuit breakers by using a mechanical interlock.




Key Features

- It prevents two breakers from closing at the same time.
- All circuit breakers are turned OFF. The applicable specifications of padlocks are as below.



Type	2P	3P	4P (RSTN)	4P (NRST)	Application	Padlock Diameter ¹⁾
MIF 10GM 2	MIF 10GM 3	MIF 10GM R4	MIF 10GM N4		HGM/HGE30, 50E/S, 60, 100	
MIF 12GM 2	MIF 12GM 3	MIF 12GM R4	MIF 12GM N4		HGM/HGE50H/L, 125	5 mm
-	MIF 25GM 3	MIF 25GM R4	MIF 25GM N4		HGM/HGE160, 250	
-	MIF 40GM 3	MIF 40GM R4	MIF 40GM N4		HGM/HGE400	
-	MIF 80GM 3	MIF 80GM R4	MIF 80GM N4		HGM/HGE630, 800	6 mm




PLD

Padlock Diameter
(Refer to Table)


MIF

Padlock Diameter
(Refer to Table)

Right Off Lock



Left Off Lock



Double Off Lock

※ 1) Padlock not included

Terminal Cover

As a part that insulates the circuit breaker's live and load side of terminal area from the outside, it prevents electric shock and short-circuit accidents that may occur due to direct contact of people's hand or tools such as drivers with the live current part. When the terminal cover is used, the protection grade of IP40 is applied to the power part. Based on the connection method of the circuit breaker, it can be classified into long or short type for use and various handles and interlock devices can be combined for use.

Short Type

It is suitable for plug-in or rear connection.

Long Type

It is suitable for front connection by using wires, bus bar or lug terminals.

Type						Application	Pitch (mm)
2P		3P		4P			
Short	Long	Short	Long	Short	Long		
TCF 10GM S2	TCF 10GM L2	TCF 10GM S3	TCF 10GM L3	TCF 10GM S4	TCF 10GM L4	HGM30, 50E/S, 60, 100 HGE30, 50E/S, 60, 100	25
TCF 12GM S2	TCF 12GM L2	TCF 12GM S3	TCF 12GM L3	TCF 12GM S4	TCF 12GM L4	HGM50H/L, 125 HGE50H/L, 125	30
TCF 25GM S3	TCF 25GM L3	TCF 25GM S3	TCF 25GM L3	TCF 25GM S4	TCF 25GM L4	HGM160, 250 HGE160, 250	35
TCF 40GM S3	TCF 40GM L3	TCF 40GM S3	TCF 40GM L3	TCF 40GM S4	TCF 40GM L4	HGM400 HGE400	44
TCF 80GM S3	TCF 80GM L3	TCF 80GM S3	TCF 80GM L3	TCF 80GM S4	TCF 80GM L4	HGM630, 800 HGE630, 800	70
TCF 10HD S2	-	TCF 10HD S3	-	-	-	HDB30, 50, 100 HDG30, 50, 100	25


※ In case of using as front connection,
please use it after removing the
indicated part.




Short Type




Long Type



Assembly Diagram



Short Type
(Plug-in Connection)



Long Type
(Front Connection)

External Accessories (HGM)


Insulation Barrier

As a part used to prevent accidents with regards to insulation and conductive foreign substance between the circuit breaker terminals, it improves the performance of phase-to-phase insulation by installing it in the groove between the circuit breaker's terminals. It can easily be assembled even if the circuit breaker has already been installed and in case the two circuit breakers have been installed side by side, it can also be assembled in the gap between the two circuit breakers. In addition, it is used in the terminal cover and plug-in base.

※ In case insulation barrier is not mounted between the circuit breaker's terminal, it may cause secondary short-circuit accidents so it must be used.

Insulation barrier must be installed towards the direction of the circuit breaker's line indication part.

Type				Application	No. of Parts (EA/Set)		
	2P	3P	4P		2P	3P	4P
TQQ 10GM 2	TQQ 10GM 3	TQQ 10GM 4		HGM30, 50E/S, 60, 100 HGE30, 50E/S, 60, 100	1	2	3
TQQ 10GM 2	TQQ 10GM 3	TQQ 10GM 4		HGM50H/L, 125 HGE50H/L, 125	1	2	3
TQQ 25GM 2	TQQ 25GM 3	TQQ 25GM 4		HGM160, 250 HGE160, 250	1	2	3
TQQ 40GM 2	TQQ 40GM 3	TQQ 40GM 4		HGM400 HGE400	1	2	3
TQQ 40GM 2	TQQ 40GM 3	TQQ 40GM 4		HGM630, 800 HGE630, 800	1	2	3
TQQ 10HD 2	TQQ 10HD 3	-		HDB30, 50, 100 HDG30, 50, 100	2	4	-



Rotary Handle

Rotary handle is a product that can check and operate MCCB's ON/OFF/TRIP even when the panel door is closed by installing the circuit breaker in enclosed switchgear or on MCCB panel and others. There are two types of rotary handle, front contact type and extension type and all the rotary handles offer panel door locking function and handle locking function. The rotary handle can be rotated clockwise to turn the circuit breaker "ON" and according to the mounting direction of MCCB, it is categorized into the upper line, the right line and the left line. The IP rating of the handle is IP40/IP54.

Front Contact Rotary Handle

- 32 ~ 250 AF : The handle is attached directly to the circuit breaker.
- 400 ~ 800 AF : The handle attached to the door of the panel.

Extension Rotary Handle


It is suitable in case the distance between the circuit breaker and the panel door is long. The handle is attached to the door of the panel and there is no trip-button function.

Type			Application
Upper Line	Right Line	Left Line	
TFG 10GM U	TFG 10GM R	TFG 10GM L	HGM/HGE30, 50E/S, 60, 100
TFG 12GM U	TFG 12GM R	TFG 12GM L	HGM/HGE50H/L, 125
TFG 25GM U	TFG 25GM R	TFG 25GM L	HGM/HGE160, 250
TFG 40GM U	TFG 40GM R	TFG 40GM L	HGM/HGE400
TFG 80GM U	TFG 80GM R	TFG 80GM L	HGM/HGE630, 800


Type	Application
TFH 10GM	HGM/HGE30, 50E/S, 60, 100
TFH 12GM	HGM/HGE50H/L, 125
TFH 25GM	HGM/HGE160, 250
TFH 40GM	HGM/HGE400
TFH 80GM	HGM/HGE630, 800



Front Contact Rotary Handle
(TFG-HGM)




HGM30 ~ HGM250




HGM400 ~ HGM800



Extension Rotary Handle
(TFH-HGM)



HGM30 ~ HGM250



HGM400 ~ HGM800


※ When installing an extension rotary handle, the eccentric tolerance of the handle drive shaft is 1.5 degrees.

External Accessories (HGM)

Rotary Handle

Types of Handle Depending on the Circuit Breaker's Installation Type


Rotary handle is divided into the following three types depending on the circuit breaker's direction of power supply.



How to Operate the Handle


Operating Direction : Turn the handle clockwise to turn the breaker ON.

- Circuit Breaker ON : Rotate the handle to ON position. (Figure 1)
- Circuit Breaker OFF : Rotate the handle to OFF position. (Figure 2)
- Circuit Breaker TRIP : If the circuit breaker is tripped, the handle will automatically return to TRIP position. (Figure 3)
- After the circuit breaker is tripped, rotate the handle to the RESET position first (Figure 4) then rotate to the ON position and the circuit breaker will turn ON (Figure 1).
- If you need to open the door when the handle is in the ON state, rotate the RELEASE screw to the direction of the arrow then open the door (Figure 5).



Handle Locking Device

Lock Function	OFF State Door Lock	ON State Door Lock	Reverse Interlock	Handle Padlock
Details	<ul style="list-style-type: none"> • Impossible to open the panel door when the circuit breaker is in the OFF state. • Possible at RESET position • Possible to open the panel door after rotating the handle to RESET 	<ul style="list-style-type: none"> • Impossible to open the panel door when the circuit breaker is in the ON state • Possible to open the panel door after rotating the RELEASE screw 	<ul style="list-style-type: none"> • Impossible to close the circuit breaker (ON) in case the panel door is open 	<ul style="list-style-type: none"> • Padlocking function which locks using a padlock to prevent handle operation. • Padlock is not provided separately and the number of padlocks depends on the padlock diameter. (Refer to the table below) • As for the specifications of the applicable padlocks, refer to the table below.
Front Contact Type (TFG)	●	●	● (100/125/250 AF Only)	●
Extension Type (TFH)	●	●	-	●



Application	Padlock Diameter ¹⁾	No. of Padlocks that can be Used
HGM/HGE30 ~ 250	6 ~ 8 mm	Ø6, Ø7 : 2 EA Ø8 : 1 EA
HGM/HGE400 ~ 800	5 ~ 7 mm	3 EA

※ 1) Padlock not included

Front Connection of Fixed Devices

Straight/spreader bus bar or lug terminal can be selected for use depending on the size specification of the cable or bus bar to be connected to the circuit breaker.

Insulated Bar Connection


In case the bus bar pitch of the switchgear is equal to the circuit breaker, it can be connected directly to the circuit breaker by using an insulation tube. Refer to the following connection bus bar specification for connection. Interphase barrier and terminal cover must be used.

Application	Connection Bus Bar Dimensions (mm)				Applicable Bolt and Tightening Torque	
	A	B	C	D	Bolt Spec.	Max. Tightening Torque (kgf×cm)
HGM/HGE 30, 50E/S, 60, 100	< 7.5	< 17	$\emptyset \geq 5.5$ (≤ 50 A)	A + 7.5	M5 Screw (≤ 50 A)	28.5
	< 7.5	< 17	$\emptyset \geq 9$ (> 50 A)	A + 7.5	M8 Screw <td>110</td>	110
HGM/HGE50H/L, 125	< 7.5	< 20	$\emptyset \geq 9$	A + 7.5	M8 Screw	110
HGM/HGE160, 250	< 10	< 27	$\emptyset \geq 9$	A + 10	M8 Hex Socket	110
HGM/HGE400	< 12.5	< 30	$\emptyset \geq 11$	A + 12.5	M10 Hex Socket	270
HGM/HGE630, 800	< 12.5	< 45	$\emptyset \geq 13$	A + 12.5	M12 Hex Socket	470



Crimp Terminal

The terminal that conforms to the specification (crimped/copper tubing terminal) must be used and the interphase barrier and the terminal cover must be used. Select the terminal that meets the material and specification of the cable according to the circuit breaker's rating. The terminal is not provided separately. Refer to the table below for the wire specifications for the main ratings.

Application	Type	Rated Current	Cu Cable Size (mm ²)	Applicable Terminal Dimensions (mm)	
				A	B
HGM/HGE 30, 50E/S, 60, 100	32	6	$\emptyset \geq 5.5$	$\emptyset \geq 5.5$	< 18
	50	10	$\emptyset \geq 5.5$		
	63	16	$\emptyset \geq 9$		
	100	35	$\emptyset \geq 9$		
HGM/HGE50H/L, 125	50	10	$\emptyset \geq 9$	< 21	< 21
	125	50			
HGM/HGE160, 250	160	70	$\emptyset \geq 9$	< 28	< 28
	250	120	$\emptyset \geq 9$		
HGM/HGE400	400	240	$\emptyset \geq 11$	< 30	< 30
HGM/HGE630, 800	800	240×2	$\emptyset \geq 13$		



Connection Bus Bar



Crimped Terminal

External Accessories (HGM)

Front Connection of Fixed Devices

Busbar

Straight Busbar

It is used to meet the cable and standards of the switchgear.
(Pitch between the poles maintained)

Spreader Busbar

It is used to extend the internal insulation distance of the switchgear. (Pitch between the poles extended)

Application		Straight		Spreader		Thickness
Type	Pole	Type	Pitch	Type	Pitch	
HGM/HGE 160, 250	2	TBB 25GP 2S	35 mm	-	45 mm	4 mm
	3	TBB 25GP 3S		TBB 25GP 3E45		
	4	TBB 25GP 4S		TBB 25GP 4E45		
HGM/HGE 400	2	TBB 40GM 2S	44 mm	-	59 mm	8 mm
	3	TBB 40GM 3S		TBB 40GM 3E59		
	4	TBB 40GM 4S		TBB 40GM 4E59		
HGM/HGE 630	2	TBB 63GM 2S	70 mm	-	-	8 mm
	3	TBB 63GM 3S		-		
	4	TBB 63GM 4S		-		
HGM/HGE 800	2	TBB 80GM 2S	70 mm	-	-	10 mm
	3	TBB 80GM 3S		-		
	4	TBB 80GM 4S		-		

LUG Terminal

As a part that connects the cable to the circuit breaker so that the cable can be used without crimp terminal, it must be selected according to the product's rating and size of cable.

Application		LUG Terminal		Applicable Cable			Tightening Torque (kgf×cm)	
Type	Pole	Type	Material	EA	Material	S (mm ²)	L (mm)	
HGM/HGE 30, 50E/S, 60, 100 (≤ 50 A)	2	CTB 10GM 2S50	Al	1	Cu/Al	2.5 ~ 16	14	60
	3	CTB 10GM 3S50						
	4	CTB 10GM 4S50						
HGM/HGE 60, 100 (> 50 A)	2	CTB 10GM 2S100	Al	1	Cu/Al	16 ~ 50	14	60
	3	CTB 10GM 3S100						
	4	CTB 10GM 4S100						
HGM/HGE 50H/L, 125	2	CTB 12GM 2S	Al	1	Cu/Al	2.5 ~ 70	14	60
	3	CTB 12GM 3S						
	4	CTB 12GM 4S						
HGM/HGE 160, 250	2	CTB 25GM 2S	Al	1	Cu/Al	50 ~ 180	19	140
	3	CTB 25GM 3S						
	4	CTB 25GM 4S						
HGM/HGE 400	3	CTB 40GM 3S1H	Al	1	Cu/Al	60 ~ 240	30 ~ 60	353
	4	CTB 40GM 4S1H				60 ~ 125		
HGM/HGE 400	3	CTB 40GM 3S	Al	2	Cu/Al	60 ~ 240	30 ~ 60	353
	4	CTB 40GM 4S						
HGM/HGE 630, 800	3	CTB 80GM 3S	Al	3	Cu/Al	60 ~ 185	30 ~ 60	353
	4	CTB 80GM 4S						

※ Quantity per Set : 2P - 2 EA, 3P - 3 EA, 4P - 4 EA

This type is inch type. For HGM100~250, ISO type (mm) is also available.



Straight
Busbar



Spreader
Busbar

LUG Terminal




HGM/HGE30 ~ 250



HGM400




HGM/HGE630, 800



Plug-in Connection Devices

If the plug-in connection method is used, the circuit breaker can be replaced quickly and accurately without separating the power cable during a malfunction of a circuit breaker. Therefore, if plug-in type circuit breaker is installed in important electrical facilities such as shipping, broadcast station and others, the circuit breaker can be replaced and maintained quickly and conveniently without disconnecting the bus bar.

- Applicable to 32 ~ 800 AF.
- Offers convenient maintenance of switchgear.
- Convenient and relaxed installation after manufacture of the switchgear.
- Circuit breaker can be removed or replaced quickly without touching the terminal connection area.
- Connection block can be made by connecting the internal accessory to the circuit breaker.
- Type : For switchgear (TDM/TDF), for distribution board (TDA)
- Composition : Plug-in devices, plug-in MCCB, terminal cover or insulation barrier (Option).



※ 1) Plug-in MCCB must be used to apply plug-in connection method.

2) In case of not using the terminal cover, be sure to install a interphase barrier.



External Accessories (HGM)

HG-MCCB Plug-in CBM Wiring Position (TDM Front Side)

Option	HGM30, 50E/S, 60, 100 / 2P	HGM30, 50E/S, 60, 100	HGM50H/L, 125, 160, 250	HGM400, 630, 800	HGP50D, 125D, 160D	HGP250	HGP630	HGP800
AUX	[12]1110	[12]1110	[12]1110		[12]1110	[12]1110	[10 11 12]	[10 11 12]
AUX2		[12]1110[22]2120	[12]1110[22]2120		[12]1110[22]2120	[12]1110[22]2120	[10 11 12 20 21 22]	[10 11 12 20 21 22]
AUX3			[12]1110 [22]2120[23]130	[30 31 32 20 21 22] [10 11 12]			[10 11 12 20 21 22]	[10 11 12 20 21 22]
ALT	[9:8:7]	[9:8:7]	[9:8:7]	[7 8 9 10 11 12]	[9:8:7]	[9:8:7]	[7 8 9 10 11 12]	[9:8:7]
SHT/UVT		[b5 - 1/3]	[b5 - 1/3]	[1/3 - b5]	[2/5 - 1/3]	[2/5 - 1/3]	[1/3 - 2/5]	[1/3 - 2/5]
AUX+ALT		[9:8:7][12]1110	[9:8:7][12]1110	[7 8 9 10 11 12]	[9:8:7][12]1110	[9:8:7][12]1110	[10 11 12 20 21 22]	[10 11 12]
AUX2+ALT			[9:8:7][22]2120	[7 8 9 10 11 12]	[9:8:7][22]2120	[9:8:7][22]2120	[10 11 12 20 21 22]	[10 9:8:7]
AUX3+ALT			[9:8:7][23]130 [12]1110[22]2120	[7 8 9 10 11 12]			[10 11 12 20 21 22]	[10 9:8:7]
AUX+ SHT/UVT		[12]1110[25 - 1/3]	[12]1110[25 - 1/3]	[1/3 - 10 11 12]	[12]1110 [2/5 - 1/3]	[2/5 - 1/3][12]1110	[1/3 - 10 11 12]	[1/3 - 10 11 12]
AUX2+ SHT/UVT			[12]1110[25 - 1/3] [22]2120	[20 21 22 1/3 - 10 11 12]	[12]1110 [2/5 - 1/3][22]2120	[2/5 - 1/3][12]1110 [22]2120	[1/3 - 10 11 12 20 21 22]	[1/3 - 10 11 12]
AUX3+ SHT/UVT				[30 31 32 20 21 22 1/3 - 10 11 12]			[1/3 - 10 11 12 20 21 22]	[1/3 - 10 11 12]
ALT+ SHT/UVT		[9:8:7][25 - 1/3]	[9:8:7][25 - 1/3]	[7 8 9 1/3 - 2/5]	[9:8:7] [2/5 - 1/3]	[9:8:7] [2/5 - 1/3]	[1/3 - 7 8 9]	[1/3 - 9:8:7]
AUX+ALT+ SHT/UVT			[9:8:7][25 - 1/3] [12]1110	[7 8 9 1/3 - 10 11 12]	[9:8:7][12]1110 [2/5 - 1/3]	[9:8:7][12]1110 [2/5 - 1/3]	[1/3 - 10 11 12 9]	[1/3 - 10 9:8:7]
AUX+ALT+ SHT/UVT Max. Mounting Combination				[7 8 9 10 11 12]	[9:8:7][12]1110 [2/5 - 1/3][22]2120	[9:8:7][12]1110 [2/5 - 1/3][22]2120	[1/3 - 10 11 12 9]	[1/3 - 10 9:8:7]

Plug-in Connection Block

It is a connection block enables plug-in connection method, and it can be connected to the internal and external accessory of the circuit breaker.

Application			
HGM100 ($\leq 50\text{ A}$)			
HGM100 ($> 50\text{ A}$)			
HGM125	CBM 10GM 2PUNIT (2P)	CBB BLOCK UNIT	CBBPLATE 10GM
HGM250	CBM 10GM UNIT (3P)	CBB BLOCK UNIT2C	
HGM400			CBBPLATE 40GM
HGM800			CBBPLATE 80GM
Quantity per Set	1	1	1

※ Please refer to the bolt tightening torque of CBM/CBB.


CBM : 5~10kgf·cm

CBB : 15~20kgf·cm

Specifications for the wires : AWG20 to AWG22

Plug-in Terminal

It is a part that can implement the plug-in MCCB.

Application	
HGM100 ($\leq 50\text{ A}$)	PCMALE 10GM 50 A
HGM100 ($> 50\text{ A}$)	PCMALE 10GM 100 A
HGM125	PCMALE 12GM
HGM250	PCMALE 25GM
HGM400	PCMALE 40GM
HGM800	PCMALE 80GM
Quantity per Set	6

External Accessories (HGM)

Plug-in Devices

It is a connection block for plug-in MCCB installation and it is available according to the applicable panel and usage.

TDM Type

- TDM-P : It is comprised of plug-in terminal for both line/load for convenient use of connection block depending on the structure of the switchgear.
- TDM-F : Only plug-in parts of the line terminal are provided in TDM-P products.

TDF Type

- Only the line terminal is comprised of plug-in terminal but the plug-in device can be fixed to the switchgear using the same method as TDM-P.


Applied Panel Type	Switchgear		Distribution Board	
	TDM-P	TDM-F	TDF	TDA (2 row) TDA (1 row)
Composition				
Purpose	Line/Load Side	Line Side	Line Side	Duble Base
HGM/HGE Type	32 ~ 800 AF	32 ~ 800 AF	32 ~ 125 AF	32 ~ 125 AF
Pole	3P	3P	3P	2P (100 AF Only), 3P
				Single Base
				3P

Specification of Connection Busbar



The bus bar of the switchgear can directly be connected to the plug-in device. The specifications of the applicable bus bar are as below and the insulation barrier or terminal cover must be used.

Product	A	B	C	D	Remark
HGM/HGE30, 50E/S, 60, 100	< 10	< 21	$\varnothing \geq 6.5$	< 17.5	
HGM/HGE50H/L, 125	< 10	< 21	$\varnothing \geq 6.5$	< 19.5	
HGM/HGE160, 250	< 17.5	< 25	$\varnothing \geq 8.5$	< 27.5	
HGM/HGE400	< 22	< 32	$\varnothing \geq 10.5$	< 38	
HGM/HGE630, 800	< 30	< 40	$\varnothing \geq 17$	< 48.5	

Unit : mm



Product	A	B	C	D	Remark
HGM/HGE30, 50E/S, 60, 100	< 7.5	< 15	$\varnothing \geq 7$	< 13	
HGM/HGE50H/L, 125	< 7.5	< 15	$\varnothing \geq 7$	< 13	
HGM/HGE160, 250	-	-	-	-	
HGM/HGE400	-	-	-	-	
HGM/HGE630, 800	-	-	-	-	




Rear Connection Terminal

It is a part for rear connection instead of front connection requirement it applies the fixed type of circuit breaker to the switchgear. The bus bar of the switchgear can be wired vertically or horizontally depending on the assembly direction of the connection.

Flat Type

Application		Rear Terminal		Quantity per Set	
Type	Pole	Line Side	Load Side	Short Terminal	Long Terminal
HGM/HGE 30, 50E/S, 60, 100 (≤ 50 A)	2		RCT 05GM F2	1	1
	3		RCT 05GM F3	2	1
	4		RCT 05GM F4	2	2
HGM/HGE 60, 100 (> 50 A)	2		RCT 10GM F2	1	1
	3		RCT 10GM F3	2	1
	4		RCT 10GM F4	2	2
HGM/HGE 50H/L, 125	2		RCT 12GM F2	1	1
	3		RCT 12GM F3	2	1
	4		RCT 12GM F4	2	2
HGM/HGE 160, 250	2		RCT 25GM F2	2	0
	3		RCT 25GM F3	2	1
	4		RCT 25GM F4	2	2
HGM/HGE 400	3	RCT 40GM F3 LINE	RCT 40GM F3 LOAD	2	1
	4	RCT 40GM F4 LINE	RCT 40GM F4 LOAD	2	2
HGM/HGE 630, 800	3	RCT 80GM F3 LINE	RCT 80GM F3 LOAD	2	1
	4	RCT 80GM F4 LINE	RCT 80GM F4 LOAD	2	2




※When assembling the RCT, remove the back barrier in advance.

DIN Rail Adaptor

This is a part that enables a separate adaptor to be assembled and mounted for rear connection with the circuit breaker when the circuit breaker is mounted on the DIN Rail.
(HGM/HGE100 Only)

Application		Din Rail Adapter	Quantity
Type	Pole		
HGM/HGE 30, 50E/S, 60, 100	2	DRA 10GM	1
	3	DRA 10GM	1
	4	DRA 10GM	2



※ When assembling the DRA, remove the back barrier in advance.

External Accessories (HGM)

Motor Operator

This device is used for turning the circuit breaker ON/OFF in remote position.


It is convenient for establishing automation system for low-voltage system and for selecting load when operating under emergency power.

Application		Pole	MOT	Voltage
Type				
HGM30, 50E/S, 60, 100	3, 4		MOT 10GM	
HGM50H/L, 125	3, 4		MOT 12GM	
HGM160, 250	3, 4		MOT 25GM	
HGM400	3, 4		MOT 40GM	
HGM630, 800	3, 4		MOT 80GM	

Rating and Characteristics

Format	Mechanical Lifespan	Operational Voltage	Operational Current (A)	Operating Time (ms)		Power Consumption (W)
				Closing	Opening	
MOT 10GM	10,000	DC 24 V	≤ 2.5	1,000	1,000	14
		AC/DC 110 V	≤ 0.5			
		AC/DC 240 V	≤ 0.5			
MOT 12GM	10,000	DC 24 V	≤ 2.5	1,000	1,000	14
		AC/DC 110 V	≤ 0.5			
		AC/DC 240 V	≤ 0.5			
MOT 25GM	8,000	DC 24 V	≤ 2.5	1,000	1,000	14
		AC/DC 110 V	≤ 0.5			
		AC/DC 240 V	≤ 0.5			
MOT 40GM	5,000	DC 24 V	≤ 6.0	1,200	1,200	14
		AC/DC 110 V	≤ 3.0			
		AC/DC 240 V	≤ 2.0			
MOT 80GM	5,000	DC 24 V	≤ 6.0	1,200	1,200	35
		AC/DC 110 V	≤ 3.0			
		AC/DC 240 V	≤ 2.0			

※ Operating Voltage Range : 85 ~ 110 % (DC 24 V : 95 ~ 110 %)



※ Precaution for mounting



When mounting the motor operator on MCCB, it must be mounted when the MCCB's handle position is in OFF position.

Mounting the motor operator in other positions (ON, TRIP) may cause damage to the motor.

※ Operation caution

When device tripped in off position, it is tripped and handle position is located in trip position even if indicator turn off to green color.
In this case, device should be reset manually.

Circuit and Wiring Drawing



(M) : Motor
(K1, K2) : ON Relay
(K3, K4) : OFF Relay
S1 : ON Limit Switch
S2 : OFF Limit Switch
S3 : Auto/Manual Limit Switch

External Accessories (HGP)

Locking Device

Padlock Device (PLD)

This device is used for locking the handle of circuit breaker to the OFF position by using a padlock. Padlock is not provided separately and up to 3 can be used. The applicable specifications of padlocks are as below.

Type	Application	Padlock Diameter ¹⁾
PLD 16GP	HGP50D, HGP125D, HGP160D	
PLD 25GP	HGP250 (HGP100/MCP)	
PLD 63GP	HGP400, HGP630	5 ~ 6 mm
PLD 80GP	HGP800	

※ 1) Padlock not included







Mechanical Interlock

This device interlocks two circuit breakers by using a mechanical interlock.


Key Features

- It prevents two breakers from closing at the same time.
- All circuit breakers are open. The applicable specifications of padlocks are as below.


Type	3P	4P	Application	Padlock Diameter ¹⁾
MIF 16GP 3	MIF 16GP R4		HGP50D, HGP125D, HGP160D	
MIF 25GP 3	MIF 25GP R4		HGP250 (HGP100/MCP)	
MIF 63GP 3	MIF 63GP R4		HGP400, HGP630	5 ~ 7 mm
MIF 80GP 3	MIF 80GP R4		HGP800	



Right Off Lock



Left Off Lock



Double Off Lock

External Accessories (HGP)

Terminal Cover / Insulation Barrier

Terminal Cover

It is our insulation part of circuit breaker for live and load side of terminal area from the outside and it prevents electric shock and short-circuit accidents that may occur due to direct contact of people's hand or tools with the live current part. When the terminal cover is used, the protection degree of IP40 is applied to the conductor part. Based on the connection method of the circuit breaker, it can be classified into long or short type for use and various handles and interlock devices can be combined for use.

Short Type

It is suitable for plug-in or rear connection.

Long Type

It is suitable for front connection using wires, bus bar or lug terminals.

Type	3P Short (Plug-in)	3P Long (3P)	4P Long (4P)	Application	Pitch (mm)	No. of Parts (EA/ Set)
TCF 16GP S3	TCF 16GP L3	TCF 16GP L4		HGP50D, HGP125D, HGP160D	30	1
TCF 25GP-G S3	TCF 25GP-G L3	TCF 25GP-G L4		HGP250 (HGP100/MCP)	35	1
TCF 63GP S3	TCF 63GP L3	TCF 63GF L4		HGP400, HGP630	46.5	1
TCF 80GP S3	TCF 80GP L3	TCF 80GF L4		HGP800	70	1




Terminal Cover
Short Type



Terminal Cover
Long Type

※ In case of using as front connection,
please use it after removing the
indicated part.



Insulation Barrier


As a part used to prevent accidents with regards to insulation and conductive foreign substance between the circuit breaker terminals, it improves the performance of phase-to-phase insulation by installing it in the groove between the circuit breaker's terminals. It can easily be assembled even if the circuit breaker has already been installed and in case the two circuit breakers have been installed side by side, it can also be assembled in the gap between the two circuit breakers. In addition, it is used in the terminal cover and plug-in base. In case insulation barrier is not mounted between the circuit breaker's terminal, it may cause secondary short-circuit accidents so it must be used.

Type	3P	4P	Application	3P	4P	No. of Parts (EA/Set)
TQQ 16GP 3	TQQ 16GP 4		HGP50D, HGP125D, HGP160D	4	6	
TQQ 25GP-G 3	TQQ 25GP-G 4		HGP250 (HGP100/MCP)	4	6	
TQQ 63GP 3	TQQ 63GP 4		HGP400, HGP630	4	6	
TQQ 80GP 3	TQQ 80GP 4		HGP800	4	6	



Insulation Barrier

※ Additional barrier required for close
mounting is provided as additional options.
(It may cause secondary accidents,
so it must be installed.)



Rotary Handle

Rotary handle is a product that can check and operate MCCB's ON/OFF/TRIP even when the panel door is closed by installing the circuit breaker in enclosed switchgear or on MCCB panel and others. There are two types of rotary handle, front contact type and extension type and all the rotary handles offer panel door locking function and handle locking function. The rotary handle can be rotated clockwise to turn the circuit breaker "ON" and according to the mounting direction of MCCB, it is categorized into the upper line, the right line and the left line. The IP grade of the handle is IP40/IP54.

Front Contact Rotary Handle


- 160 ~ 250 AF : The handle is installed directly to the circuit breaker.
- 630 ~ 800 AF : The handle is installed to the door of the panel.

Extension Rotary Handle


It is suitable if the distance between the circuit breaker and the panel door is long. The handle is installed to the door of the panel and there is no trip-button function.

Type	Application		
Upper Line	Right Line	Left Line	
TFG 16GP U	TFG 16GP R	TFG 16GP L	HGP50D, HGP125D, HGP160D
TFG 25GP U	TFG 25GP R	TFG 25GP L	HGP250 (HGP100/MCP)
TFG 63GP U	TFG 63GP R	TFG 63GP L	HGP400, HGP630
TFG 80GP U	TFG 80GP R	TFG 80GP L	HGP800


Type	Application
TFH 16GP	HGP50D, HGP125D, HGP160D
TFH 25GP	HGP250 (HGP100/MCP)
TFH 63GP	HGP400, HGP630
TFH 80GP	HGP800



HGP50D, HGP125D
HGP160D, HGP250



HGP400, HGP630
HGP800



HGP50D, HGP125D
HGP160D, HGP250

HGP400, HGP630
HGP800


※ When installing an extension rotary handle, the eccentric tolerance of the handle drive shaft is 1.5 degrees.

External Accessories (HGP)

Rotary Handle

Types of Handle by the Circuit Breaker's Installation Type


Rotary handle is divided into the following three types by the circuit breaker's direction of power supply.



How to Operate the Handle

Operating Direction : Turn the handle clockwise to turn the breaker ON.


- Circuit Breaker ON : Rotate the handle to ON position. (Figure 1)
- Circuit Breaker OFF : Rotate the handle to OFF position. (Figure 2)
- Circuit Breaker TRIP : If the circuit breaker is tripped, the handle will automatically return to TRIP position. (Figure 3)
- After the circuit breaker is tripped, rotate the handle to the RESET position first (Figure 4) then rotate to the ON position and the circuit breaker will turn ON (Figure 1).
- If you need to open the door when the handle is in the ON state, rotate the RELEASE screw to the direction of the arrow then open the door (Figure 5).



Handle Locking Device

Lock Function	OFF State Door Lock	ON State Door Lock	Reverse Interlock	Handle Padlock ¹⁾
Details	<ul style="list-style-type: none"> Impossible to open the panel door when the circuit breaker is in the OFF state. Possible at RESET position Possible to open the panel door after rotating the handle to RESET 	<ul style="list-style-type: none"> Impossible to open the panel door when the circuit breaker is in the ON state Possible to open the panel door after rotating the RELEASE screw 	<ul style="list-style-type: none"> Impossible to close the circuit breaker (ON) in case the panel door is open 	<ul style="list-style-type: none"> Padlocking function which locks using a padlock to prevent handle operation. Padlock is not provided separately and the number of padlocks depends on the padlock diameter. (Refer to the table below) As for the specifications of the applicable padlocks, refer to the table below.
Front Contact Type (TGF)	●	●	● (160/250 AF Only)	●
Extension Type (TFH)	●	●	-	●

※ 1) For TFG 250 AF or less, The handle remains ON when the circuit breaker is tripped after padlocking in ON position.



Application	Padlock Diameter ¹⁾
HGP50D, HGP125D, HGP160D, HGP250	6 ~ 8 mm
HGP400, HGP630, HGP800	5 ~ 7 mm

※ 1) Padlock not included

Front Connection of Fixed Devices

Straight/spreader bus bar or lug terminal can be selected according to the size and specification of the cable or bus bar to be connected to the circuit breaker.

Insulated Bar Connection


In case the bus bar pitch of the switchgear is equal to the circuit breaker, it can be connected directly to the circuit breaker by using an insulation tube. Refer to the following connection bus bar specification for connection and the insulation barrier between phases and terminal cover must be used.

Crimped Terminal

Standard terminals (crimped/copper tubing terminal) must be used and the insulation barrier between phases and the terminal cover must be used. Standard terminals must be selected for use according to the rating of the circuit breaker and the terminal is not provided separately. As for the cable specifications with regards to important ratings, refer to the table below.

Application	Connection Bus Bar Dimensions (mm)				Applicable Bolt and Tightening Torque	
	A	B	C	D	Bolt Spec.	Max. Tightening Torque (kgf×cm)
50~160 AF	< 9	< 22	Ø9	A+9	M8 Screw	136
250 AF	< 9	< 25	Ø9	A+10	M8 Hex Socket	136
400~630 AF	< 15	< 32	Ø10.5	A+15	M10 Hex Socket	270
800 AF	< 15.5	< 50	Ø13	A+16.5	M12 Hex Socket	470

Application	Cu Cable Size (mm ²)		Applicable Terminal Dimensions (mm)		
	AF	Rated Current	A	B	C
50~160 AF	100 A	35	Ø9	< 22	< 9
250 AF	160 A	70	Ø9	< 25	< 9
400~630 AF	160 A	70	Ø10.5	< 32	< 15
800 AF	250 A	120	Ø10.5	< 50	< 15.5
	400 A	240	Ø13	< 50	< 15.5
	630 A	185×2			
	800 A	240×2			



Busbar

Straight Busbar


It is used to meet the cable and standards of the switchgear.
(Pitch between the poles maintained)

Spreader Busbar

It is used to extend the internal insulation distance of the switchgear.
(Pitch between the poles extended)

Series Busbar

Used for serial connection of adjacent phases. (DC only)



Straight Busbar



Spreader Busbar



Series Busbar

Application	Straight			Spreader		Series	
	Type	Pole	Type	Pitch	Type	Pitch	Type
HPG250	3		TBB 25GP 3S	35 mm	TBB 25GP 3E45	45 mm	SBB 25GP
	4		TBB 25GP 4S		TBB 25GP 4E45		
HPG630	3		TBB 63GP 3S	46.5 mm	TBB 63GP 3E61.5	61.5 mm	SBB 63GP
	4		TBB 63GP 4S		TBB 63GP 4E61.5		
HPG800	3		TBB 80GP 3S	70 mm	-	-	SBB 80GP
	4		TBB 80GP 4S		-		

* Quantity per Set : 3P - 3 EA, 4P - 4 EA, SBB - 1 EA

External Accessories (HGP)

LUG Terminals

As a cable connection to the circuit breaker the cable can be used without crimped terminal, it must be selected according to the product's rating and size of cable.

Application		LUG Terminal		Application				Tightening Torque (kgf×cm)
Type	Pole	Type	Material	EA	Material	S (mm ²)	L (mm)	
HGP50D	3	CTB 16GP 3	Steel	1	Cu/Al	1.5 ~ 95	19	140
HGP125D								
HGP160D	4	CTB 16GP 4						
HGP250	3	CTB 25GP 3	Al	1	Cu/Al	14 ~ 185	19	140
(HGP100/MCP)	4	CTB 25GP 4						
HGP400	3	CTB 63GP 3	Al	2	Cu/Al	60 ~ 240	30 ~ 60	353
HGP630	4	CTB 63GP 4						
HGP800	3	CTB 80GP 3	Al	3	Cu/Al	60 ~ 185	30 ~ 60	353
	4	CTB 80GP 4						

※ Packaging Quantity per Set : Provided in the composition quantity of line or load side (3P - 3 EA, 4P - 4 EA)



HGP50D
HGP125D
HGP160D




HGP250







HGP400
HGP630



HGP800




Wire



Plug-in Connection Devices


When the plug-in connection method is used, the circuit breaker can be replaced quickly and accurately without power off during a malfunction of a circuit breaker. Therefore, in case the plug-in method of circuit breaker is installed in important electrical facilities such as shipping, broadcast station and others, the circuit breaker can be replaced and maintained quickly and conveniently without disconnecting the bus bar.

- Applicable to 50 ~ 800 AF, up to 3P.
- Offers convenient maintenance of switchgear.
- Convenient and relaxed installation after manufacture of the switchgear.
- Circuit breaker can be removed or replaced quickly without touching the terminal connection area.
- Type : For switchboard (TDM/TDF)
- Composition : Plug-in devices, plug-in MCCB, terminal cover or insulation barrier (Option)



Plug-in MCCB (For HGP)

In order to apply the plug-in connection method, the plug-in MCCB must be used instead of the general type, even for the MCCB. The product covers various breaking capacity up to the rated current of 800 A so this product conforms to the switchgear standard. Connection board (Connector) can be added to connect internal accessories to the circuit breaker.



External Accessories (HGP)



Plug-in Connection Devices

Plug-in Devices

As a connection block in which plug-in MCCB can be installed, it is available according to the applied panel and the purpose.

TDM Type

- TDM-P : It is comprised of plug-in terminal for both line/load for convenient use of connection block depending on the structure of the switchgear.
- TDM-F : Only plug-in parts of the line terminal are provided in TDM-P products.

Applied Panel	For Switchgear	
Type	TDM-P	TDM-F
Composition		
Purpose	Line/Load Side	Line Side
Applicable MCCB	HGP50 ~ 800 AF 3P	


Specification of Connection Busbar


The bus bar of the switchgear can directly be connected to the plug-in device.


The specifications of the applicable bus bar are as below and the insulation barrier or terminal cover must be used.

There is no separate bus bar for connection.

Unit : mm

Product	A	B	C	D	Remark
50 ~ 160 AF	< 12	< 21	$\varnothing \geq 8.5$	A + 18	
250 AF	< 18	< 25	$\varnothing \geq 8.5$	A + 17	
400 ~ 630 AF	< 34	< 35	$\varnothing \geq 10.5$	A + 26	
800 AF	< 30	< 40	$\varnothing \geq 16.5$	A + 30	

Product	A	B	C	D	Remark
50 ~ 160 AF	< 12	< 21	$\varnothing \geq 8.5$	< 12	
250 AF	< 18	< 25	$\varnothing \geq 8.5$	< 18	
400 ~ 630 AF	< 25	< 35	$\varnothing \geq 10.5$	< 25	
800 AF	< 30	< 40	$\varnothing \geq 16.5$	< 30	





HG-MCCB Plug-in CBM Wiring Position (TDM Front Side)

Option	HGP50D, HGP125D, HGP160D	HGP250 (HGP100/MCP)	HGP400, HGP630	HGP800
AUX				
AUX2				
AUX3				
ALT				
SHT/UVT				
AUX+ALT				
AUX2+ALT				
AUX3+ALT				
AUX+SHT/UVT				
AUX2+SHT/UVT				
AUX3+SHT/UVT				
ALT+SHT/UVT				
AUX+ALT+SHT/UVT				
AUX+ALT+SHT/UVT Max. Mounting Combination				

External Accessories (HGP)

Plug-in Connection Block

In order for the plug-in connection method, it can be connected to the internal and external accessory of the circuit breaker.

Application			
HGP160D			CBBPLATE 16GP
HGP250			CBBPLATE 25GP
HGP630			CBBPLATE 63GP
HGP800			CBBPLATE 80GP
Quantity per Set	1	1	1

※ Please refer to the bolt tightening torque of CBM/CBB.


CBM : 5~10kgf·cm

CBB : 15~20kgf·cm

Specifications for the wires : AWG20 to AWG22

Plug-in Terminal

It is a part that can realize the plug-in MCCB.


Application	
HGP160D	PCMALE 16GP
HGP250	PCMALE 25GP-G
HGP630	PCMALE 63GP
HGP800	PCMALE 80GP
Quantity per Set	6

Rear Connection Terminal

It is a part that is used in case there is a need for rear connection instead of front connection by applying the fixed type of circuit breaker to the switchgear. The bus bar of the switchgear can be wired vertically or horizontally depending on the assembly direction of the connection.


Flat Type

Application	Type	Rear Terminal		Quantity per Set		
		Pole	Line Side	Load Side	Short Terminal	Long Terminal
HGP50D, HGP125D, HGP160D	3		RCT 16GP F3		2	1
	4		RCT 16GP F4		2	2
HGP250 (HGP100/MCP)	3		RCT 25GP-G F3		2	1
	4		RCT 25GP-G F4		2	2
HGP400 HGP630	3		RCT 63GP F3 LINE	RCT 63GP F3 LOAD	2	1
	4		RCT 63GP F4 LINE	RCT 63GP F4 LOAD	2	2
HGP800	3		RCT 80GP F3 LINE	RCT 80GP F3 LOAD	2	1
	4		RCT 80GP F4 LINE	RCT 80GP F4 LOAD	2	2



Auxiliary Handle (THA)

As an auxiliary handle used to reduce the operating force of ON, OFF, RESET in large capacity circuit breaker (400 ~ 800 AF), it is a standard product provided. It comes together with a holder for storing auxiliary handle that can be fixed to the switchboard panel.



External Accessories (HGP)

Motor Operator


This device is used for turning the circuit breaker ON/OFF from remote position. It is convenient for establishing automation system for low-voltage load system and for selecting load when operating under emergency power.

Application		Pole	MOT	Voltage
Type				
HGP50D, HGP125D, HGP160D		3, 4	MOT 16GP	
HGP250 (HGP100/MCP)		3, 4	MOT 25GP	DC 24 V AC/DC 110 V AC/DC 240 V
HGP400, HGP630		3, 4	MOT 63GP	
HPG800		3, 4	MOT 80GP	



Rating and Characteristics

Format	Operational voltage	Operational Current (A)	Operating Time (ms)		Power Consumption (W)	Endurance
			Closing	Opening		
MOT 16GP	DC 24 V	≤ 2.5	1,000	1,000	14	10,000
	AC/DC 110 V	≤ 0.5				
	AC/DC 240 V	≤ 0.5				
MOT 25GP	DC 24 V	≤ 2.5	1,000	1,000	14	10,000
	AC/DC 110 V	≤ 0.5				
	AC/DC 240 V	≤ 0.5				
MOT 63GP	DC 24 V	≤ 6.0	1,200	1,200	35	5,000
	AC/DC 110 V	≤ 3.0				
	AC/DC 240 V	≤ 2.0				
MOT 80GP	DC 24 V	≤ 6.0	1,200	1,200	35	5,000
	AC/DC 110 V	≤ 3.0				
	AC/DC 240 V	≤ 2.0				

※ Range of Operational Voltage : 85 ~ 110 % (DC 24 V : 95 ~ 110 %)



Circuit and Wiring Drawing



(M) : Motor **(K₁)** : ON Relay **(K₃)** : Relay for Motor
(K₂) : OFF Relay **(K₄)** : OFF Limit Switch **S₁** : ON Limit Switch
S₂ : OFF Limit Switch **S₃** : Auto/Manual Limit Switch

Precaution for mounting

When mounting the motor operator on MCCB, it must be mounted when the MCCB's handle position is at in position.

Mounting the motor operator in other positions (ON, TRIP) may cause damage to the motor.

Operation caution

When device tripped in off position, it is tripped and handle position is located in trip position even if indicator turn off to green color.

In this case, device should be reset manually.

Technical Data (HGM/HGE)

Environmental Operating Conditions

Temperature Derating


The overcurrent characteristic of MCCB has been set to the ambient temperature of 40 °C. If the ambient temperature is less or more than 40 °C, the overcurrent characteristics may differ.

If the Ambient Temperature is lower than 40 °C

In order to ensure that the circuit breaker's overcurrent meet the derating curve at the given ambient temperature, the real current (I_r) has to be adjusted. The temperature correction ratio or each MCCB is shown in the circuit breaker's characteristics curve.

If the Ambient Temperature is higher than 40 °C

As the internal temperature of MCCB is a sum of increased temperature due to current flow and the ambient temperature, if the ambient temperature exceeds 40 °C, thermal damage of internal insulation material of MCCB may occur causing the circuit breaker to trip at an early stage. When applying ambient temperature higher than 40 °C, the rated current must be adjusted as shown in the following rated current derating table.



I_n (Rated Current) :

Circuit breaker's rating at ambient temperature of 40 °C

I_r (Real Current) :

Circuit breaker's rating at the given temperature

$$I_r = \text{Correction Ratio (\%)} \times I_n$$

Rated Current Derating Table : HG Type/Standard Mounting

Model	Rated Current (A)	Ambient Temperature (°C)									
		10	20	30	40	45	50	55	60	65	70
HGM/HGE 30, 50E/S, 60, 100	16	18.9	18.6	17.8	16	15.2	14.6	14.1	13.6	13.2	12.8
	20	23.58	23.3	22.2	20	19.1	18.3	17.6	17.0	16.5	16.0
	25	26.8	26.2	25.6	25	24.7	24.4	24.1	23.8	23.5	23.2
	32	34.3	33.5	32.8	32	31.6	31.3	30.9	30.5	30.1	29.7
	40	42.9	41.9	41.0	40	39.5	39.0	38.6	38.1	37.6	37.1
	50	53.6	52.4	51.2	50	49.4	48.8	48.2	47.6	47.0	46.4
	63	67.5	66.0	64.5	63	62.2	61.5	60.7	60.0	59.2	58.5
	75	80.4	78.6	76.8	75	74.1	73.2	72.3	71.4	70.5	69.6
	80	85.8	83.8	81.9	80	79.0	78.1	77.1	76.2	75.2	74.2
	100	107.2	104.8	102.4	100	98.8	97.6	96.4	95.2	94.0	92.8
HGM/HGE 50H/L, 125	16	18.9	18.6	17.8	16	15.2	14.6	14.1	13.6	13.2	12.8
	20	23.6	23.3	22.2	20	19.1	18.3	17.6	17.0	16.5	16.0
	25	27.3	26.6	25.8	25	24.6	24.2	23.8	23.4	23.0	22.6
	32	35.0	34.0	33.0	32	31.5	31.0	30.5	30.0	29.5	29.0
	40	43.8	42.5	41.3	40	39.4	38.8	38.1	37.5	36.8	36.2
	50	54.7	53.1	51.6	50	49.2	48.4	47.7	46.9	46.1	45.3
	63	68.9	66.9	65.0	63	62.0	61.0	60.1	59.1	58.0	57.0
	75	82.0	79.7	77.3	75	73.8	72.7	71.5	70.3	69.1	67.9
	80	87.5	85.0	82.5	80	78.8	77.5	76.3	75.0	73.7	72.4
	100	109.4	106.3	103.1	100	98.4	96.9	95.3	93.8	92.1	90.5
HGM/HGE 160, 250	125	136.7	132.8	128.9	125	123.1	121.1	119.1	117.2	115.1	113.1
	100	107.8	105.2	102.6	100	96.0	94.0	92.0	88.0	85.5	83.0
	125	134.8	131.5	128.3	125	120.0	117.5	115.0	110.0	106.9	103.8
	150	161.7	157.8	153.9	150	144.0	141.0	138.0	132.0	128.3	124.5
	160	172.5	168.3	164.2	160	153.6	150.4	147.2	140.8	136.8	132.8
	175	188.7	184.1	179.6	175	168.0	164.5	161.0	154.0	149.6	145.3
	200	215.6	210.4	205.2	200	192.0	188.0	184.0	176.0	171.0	166.0
	225	242.6	236.7	230.9	225	216.0	211.5	207.0	198.0	192.4	186.8
	250	269.5	263.0	256.5	250	240.0	235.0	230.0	220.0	213.8	207.5

Rated Current Derating Table : HG Type/Standard Mounting

Model	Rated Current (A)	Ambient Temperature (°C)									
		10	20	30	40	45	50	55	60	65	70
HGM/HGE 400	250	269.5	263.0	256.5	250	246.8	243.5	240.2	237.0	233.6	230.3
	300	324	316.5	309	300	291	282	273	264	255	246
	350	378	369.25	360.5	350	340	330	320	310	300	290
	400	432	422	412	400	388	376	364	352	340	328
HGM/HGE 630, 800	500	540	527.5	515	500	485	470	455	440	425	410
	630	680.4	664.65	648.9	630	611	592	573	554	535	516
	700	756	738.5	721	700	679	658	637	616	595	574
	800	864	844	824	800	776	752	728	704	680	656

Rated Current Derating Table : HG Type/Plug-in Method

Model	Rated Current (A)	Ambient Temperature (°C)									
		10	20	30	40	45	50	55	60	65	70
HGM/HGE 30, 50E/S, 60, 100	16	18.5	18.3	17.4	16	14.9	14.3	13.8	13.3	12.9	12.5
	20	23.1	22.8	21.8	20	18.7	17.9	17.2	16.7	16.1	15.7
	25	26.3	25.7	25.1	25	24.2	23.9	23.6	23.3	23.0	22.7
	32	33.6	32.9	32.1	31	31.0	30.6	30.2	29.9	29.5	29.1
	40	42.0	41.1	40.1	39	38.7	38.3	37.8	37.3	36.8	36.4
	50	52.5	51.4	50.2	49	48.4	47.8	47.2	46.6	46.1	45.5
	63	66.2	64.7	63.2	62	61.0	60.3	59.5	58.8	58.0	57.3
	75	78.8	77.0	75.3	74	72.6	71.7	70.9	70.0	69.1	68.2
	80	84.0	82.2	80.3	78	77.5	76.5	75.6	74.6	73.7	72.8
	100	105.1	102.7	100.4	98	96.8	95.6	94.5	93.3	92.1	90.9
	16	18.5	18.2	17.4	16	14.9	14.3	13.8	13.3	12.9	12.5
HGM/HGE 50H/L, 125	20	23.1	22.8	21.8	20	18.7	17.9	17.2	16.7	16.1	15.7
	25	26.8	26.0	25.3	25	24.1	23.7	23.4	23.0	22.6	22.2
	32	34.3	33.3	32.3	31	30.9	30.4	29.9	29.4	28.9	28.4
	40	42.9	41.7	40.4	39	38.6	38.0	37.4	36.8	36.1	35.5
	50	53.6	52.0	50.5	49	48.2	47.5	46.7	45.9	45.1	44.4
	63	67.5	65.6	63.7	62	60.8	59.8	58.8	57.9	56.9	55.9
	75	80.4	78.1	75.8	74	72.4	71.2	70.1	68.9	67.7	66.5
	80	85.8	83.3	80.9	78	77.2	76.0	74.7	73.5	72.2	71.0
	100	107.2	104.1	101.1	98	96.5	94.9	93.4	91.9	90.2	88.7
	125	134.0	130.2	126.3	123	120.6	118.7	116.8	114.8	112.8	110.9
	100	103.5	101.0	98.5	96	92.2	90.2	88.3	84.5	82.1	79.7
HGM/HGE 160, 250	125	129.4	126.2	123.1	120	115.2	112.8	110.4	105.6	102.6	99.6
	150	155.3	151.5	147.8	144	138.2	135.4	132.5	126.7	123.1	119.5
	160	165.6	161.6	157.6	154	147.5	144.4	141.3	135.2	131.3	127.5
	175	181.1	176.7	172.4	168	161.3	157.9	154.6	147.8	143.6	139.4
	200	207.0	202.0	197.0	192	184.3	180.5	176.6	169.0	164.2	159.4
	225	232.9	227.3	221.6	216	207.4	203.0	198.7	190.1	184.7	179.3
	250	258.7	252.5	246.2	240	230.4	225.6	220.8	211.2	205.2	199.2
	250	261.4	255.1	248.8	242.5	239.3	236.2	233.0	229.9	226.6	223.4
HGM/HGE 400	300	314.3	307.0	299.7	291.0	282.3	273.5	264.8	256.1	247.4	238.6
	350	366.7	358.2	349.7	339.5	329.8	320.1	310.4	300.7	291.0	281.3
	400	405.2	395.8	387.6	378	373.7	367.9	363.2	357.9	352.6	347.3
	500	523.8	511.7	499.6	485.0	470.5	455.9	441.4	426.8	412.3	397.7
HGM/HGE 630, 800	630	660.0	644.7	629.4	611.1	592.7	574.2	555.8	537.4	519.0	500.5
	700	725.8	709.0	692.2	672.0	651.8	631.7	611.5	591.4	571.2	551.0
	800	777.8	759.7	744.1	726	717.4	706.3	697.3	687	676.9	666.7

Technical Data (HGM/HGE)

Environmental Operating Conditions

Altitude Derating

The characteristics of the circuit breaker is not affected at an altitude of less than 2,000 m. Characteristics of insulation and air cooling of the circuit breaker are reduced at an altitude of more than 2,000 m and the rated current and rated voltage must be adjusted as shown in the table below. However, there is no change in the characteristics of breaking capacity.

Circuit Breaker	Altitude	2,000 m	3,000 m	4,000 m	5,000 m
HGM Type MCCB 32 ~ 800 AF	Withstand Voltage (V)	3,000	2,500	2,100	1,800
	Insulation Voltage (V) U_i	1,000	850	750	600
	Maximum Operational Voltage (V) U_e	690	590	520	460
	Average Through-Current (A), at 40 °C $I_{n,x}$	1	0.96	0.93	0.9
HGE Type ELCB 32 ~ 800 AF	Withstand Voltage (V)	3,000	2,500	2,100	1,800
	Maximum Operational Voltage (V) U_e	460	390	345	275
	Average Through-Current (A), at 40 °C $I_{n,x}$	1	0.96	0.93	0.9

Vibrations

The excessive vibration may cause problems such as decrease of breaking capacity, lower dynamic strength, reduction of electric current conductivity or compromising safety of operating characteristics. Therefore, proper consideration is required with regards to these environmental stresses when it comes to designating the circuit breakers. These stresses are generated by the vibration during transportation, magnetic impact during opening and closing operation and influence of adjacent devices. Our circuit breaker has been verified in accordance with the standards with regards to vibration resistance.

Vibration test

Vibration test is verified with the standard requested by the shipping certification institute in compliance with IEC 60068-2-6. Out of the vibration test items, resonance test and vibration Endurance test were verified based on the following standard.

Resonance test

It confirms whether vibration is generated in the characteristics part of MCCB by slowly changing the frequency in the frequency sector of the following sinusoidal wave.

- 5 ~ 13.2 Hz : 1 mm Displacement
- 13.2 ~ 100 Hz : 0.7 g Acceleration

Vibration Endurance test

A sinusoidal wave with frequency of 30 Hz is applied for 90 minutes to check for abnormalities.





- 30 Hz : 0.7 g Acceleration

Seismic Performance and Shock Tolerance Table

Item	Seismic
Test Condition	<p>Mounting Posture Direction of Vibration, Shock</p> <ul style="list-style-type: none"> • Vertical mounting • Up-down, left-right, front-back
Status of MCCB	<ul style="list-style-type: none"> • Non-conduction (ON or OFF status) • Status where rated current has been conducted on until the temperature of MCCB becomes constant and continuous
Test Result	<ul style="list-style-type: none"> • If it is ON, it should not turn OFF • If it is OFF, it should not turn ON • No abnormal status such as damage, deformation or loosened screw part • The characteristics of switch and trip after the test must be normal

Degree of Protection

The MCCB's IP rating is defined based on IEC 60529. The IP rating also depends on product conditions.

Condition	Circuit Breaker	Circuit Breaker + Terminal Cover	Circuit Breaker + Terminal Cover + Rotary Handle (Front Contact Type)	Circuit Breaker + Terminal Cover + Rotary Handle (Extension Type)
Appearance				
Protection Degree	IP20	IP40	IP40	IP40/IP54

※ 1) When applying IP54, please contact us separately.

Technical Data (HGM/HGE)

Power Loss / Resistance

HGM Type MCCB

Type	Rated Current (A)	HGM30, 50E/S, 60, 100		HGM50H/L, 125		HGM160, 250		HGM400		HGM630, 800	
		R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)
Fixed / Adj	16	16.0	4.10	17.0	4.35						
	20	16.0	6.40	17.0	6.80						
	25	4.0	2.50	4.3	2.69						
	32	4.0	4.10	3.0	3.07						
	40	2.9	4.64	1.9	3.06						
	50	2.3	5.75	1.6	3.90						
	63	1.2	4.88	0.9	3.37						
	75	0.7	4.11	0.6	3.38						
	80	0.9	5.76	0.6	3.84						
	100	0.7	7.30	0.6	5.60	0.6	5.60				
	125			0.5	7.97	0.4	6.72				
	150					0.4	8.55				
	160					0.3	8.70				
	175					0.3	9.80				
	200					0.3	10.80				
	225					0.3	13.67				
	250					0.2	13.75	0.2	14.38		
	300							0.2	18.90		
	350							0.2	23.28		
	400							0.2	27.20		
	500									0.1	30.00
	630									0.1	39.60
	700									0.1	53.90
	800									0.1	64.00
Plug-in	16	16.1	4.12	17.1	4.37						
	20	16.1	6.43	17.1	6.83						
	25	4.1	2.55	4.4	2.74						
	32	4.1	4.18	3.1	3.15						
	40	3.0	4.77	2.0	3.18						
	50	2.4	5.95	1.6	4.10						
	63	1.3	5.20	0.9	3.69						
	75	0.8	4.56	0.7	3.83						
	80	1.0	6.27	0.7	4.35						
	100	0.8	8.10	0.6	6.40	0.6	6.40				
	125			0.6	9.22	0.5	7.97				
	150					0.5	10.35				
	160					0.4	10.75				
	175					0.4	12.25				
	200					0.4	14.00				
	225					0.4	17.72				
	250					0.3	18.75	0.3	19.38		
	300							0.3	26.10		
	350							0.3	33.08		
	400							0.3	40.00		
	500									0.2	50.00
	630									0.2	68.40
	700									0.2	93.10
	800									0.2	115.20

HGE Type ELCB

Type	Rated Current (A)	HGE30, 50E/S, 60, 100		HGE50H/L, 125		HGE160, 250		HGE400		HGE630, 800	
		R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)
Fixed	16	14.3	3.66	12.9	3.30						
	20	14.3	5.72	12.9	5.16						
	25	4.9	3.04	4.2	2.63						
	32	4.9	4.98	3.9	4.00						
	40	2.9	4.64	2.3	3.75						
	50	2.4	6.03	1.7	4.14						
	63	1.7	6.62	1.2	4.80						
	75	0.8	4.49	0.7	4.15						
	80	1.0	6.65	0.7	4.72						
	100	0.8	8.07	0.8	7.52	0.5	5.44				
	125			0.7	10.16	0.5	7.32				
	150					0.4	8.10				
	160					0.3	8.67				
	175					0.3	10.06				
	200					0.3	11.37				
	225					0.3	14.65				
	250					0.2	15.13	0.3	16.25		
	300							0.2	21.60		
	350							0.2	26.95		
	400							0.2	32.00		
	500									0.2	40.00
	630									0.2	54.00
	700									0.1	68.60
	800									0.1	83.20
Plug-in	16	14.3	3.66	12.9	3.30						
	20	14.3	5.72	12.9	5.16						
	25	4.9	3.04	4.4	2.75						
	32	4.9	4.98	3.9	4.00						
	40	2.9	4.64	3.0	4.85						
	50	2.4	6.03	1.8	4.49						
	63	2.1	8.49	1.7	6.59						
	75	1.3	7.14	1.1	6.40						
	80	1.0	6.65	1.1	7.28						
	100	1.0	9.77	0.8	8.42	0.5	5.44				
	125			0.7	11.56	0.5	7.32				
	150					0.4	8.10				
	160					0.3	8.67				
	175					0.3	10.06				
	200					0.3	11.37				
	225					0.3	14.65				
	250					0.2	15.13	0.3	21.25		
	300							0.3	28.80		
	350							0.3	36.75		
	400							0.3	44.80		
	500									0.2	60.00
	630									0.2	82.80
	700									0.2	107.80
	800									0.2	134.40



Technical Data (HGM/HGE)

Cascading Table

AC 220/240 V

Upstream Circuit Breaker : HGM30, HGM50, HGM60, HGM100, HGM125, HGM160, HGM250, HGM400

Downstream Circuit Breaker : HGD32, HGD63, HGD125, HGM30, HGM50, HGM60, HGM100

Upstream Circuit Breaker	HGM30				HGM50				HGM60				HGM100					
	E	S	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L
Breaking Capacity [Icu] (kA r.m.s.)	35	50	35	50	85	100	35	50	50	50	35	50	50	50	35	50	50	50
Downstream Breaking Capacity [Icu] (kA r.m.s.) Enhanced Breaking Capacity																		
HGD63E	10	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	
HGD63S	15	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	
HGD32NS, HGD63N/M	20		35	40	40	40	40	35	40	40	40	40	35	40	40	40	40	
HGD63H/P	25		35	50	50	50	35	40	40	40	40	35	40	40	40	40	40	
Upstream Circuit Breaker	HGM125				HGM160				HGM250				HGM400					
	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L		
Breaking Capacity [Icu] (kA r.m.s.)	50	65	85	100	50	65	85	100	50	65	85	100	50	65	85	100		
Downstream Breaking Capacity [Icu] (kA r.m.s.) Enhanced Breaking Capacity																		
HGD63E	10	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	
HGD63S	15	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	
HGD32NS, HGD63N/M	20	40	40	40	40	40	40	40	40	40	40	40	40	40	40	40	40	
HGD63H/P	25	40	50	50	50	40	50	50	50	50	50	40	50	50	50	50	50	
HGD100S/125	25	40	40	40	40	40	40	40	40	40	40	40	40	40	40	40	40	
Upstream Circuit Breaker	HGM30				HGM50				HGM60				HGM100					
	E	S	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L
Breaking Capacity [Icu] (kA r.m.s.)	35	50	35	50	85	100	35	50	50	50	50	35	50	50	50	35	50	50
Downstream Breaking Capacity [Icu] (kA r.m.s.) Enhanced Breaking Capacity																		
HGM30E	35		50		50	65	65		50	50	50		50		50	50	50	50
HGM50E	35			50	65	70		50	50	50	50		50		50	50	50	50
HGM50S	50				70	85												
HGM50H	85					100												
HGM60E	35								50	50	50		50		50	50	50	50
HGM100E	35												50		50		50	
Upstream Circuit Breaker	HGM125				HGM160				HGM250				HGM400					
	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L		
Breaking Capacity [Icu] (kA r.m.s.)	50	65	85	100	50	65	85	100	50	65	85	100	50	75	100	125		
Downstream Breaking Capacity [Icu] (kA r.m.s.) Enhanced Breaking Capacity																		
HGM30E	35	50	65	65	65	70	65	65	50	65	65	65	50	65	65	65	65	
HGM30S	50		65	65	65		65	65	65	65	65	65	65	65	65	65	65	
HGM50E	35	50	65	70	50	65	65	70	50	65	65	65	70	50	65	65	70	
HGM50S	50		65	70	85		65	70	85		65	70	85		65	70	85	
HGM50H	85			100				100					100				100	
HGM60E	35	50	65	70	70	50	65	70	70	50	65	70	70	50	65	70	70	
HGM60S	50		65	70	70		65	70	70		65	70	70		65	70	70	
HGM60H	50		65	70	70		65	70	70		65	70	70		65	70	70	
HGM60L	50		65	70	70		65	70	70		65	70	70		65	70	70	
HGM100E	35	50	65	70	70	50	65	70	70	50	65	70	70	50	65	70	70	

Upstream Circuit Breaker : HGM125, HGM160, HGM250, HGM400, HGM630, HGM800

Downstream Circuit Breaker : HGM100, HGM160, HGM250, HGM400, HGM630, HGM800

Upstream Circuit Breaker	HGM125				HGM160				HGM250				HGM400				
	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L	
Breaking Capacity [Icu] (kA r.m.s.)	50	65	85	100	50	65	85	100	50	65	85	100	50	75	100	125	
Downstream Breaking Capacity [Icu] (kA r.m.s.)																	
HGM100S	50		65	70	70		65	70	70		65	70	70		65	70	70
HGM100H	50		65	70	70		65	70	70		65	70	70		65	70	70
HGM100L	50		65	70	70		65	70	70		65	70	70		65	70	70
HGM125E	50		65	85	100		65	85	100		65	85	100		65	85	100
HGM125S	65			85	100			85	100			85	100			85	100
HGM125H	85				100			100			100			100			100

Upstream Circuit Breaker	HGM160				HGM250				HGM400				
	E	S	H	L	E	S	H	L	E	S	H	L	
Breaking Capacity [Icu] (kA r.m.s.)	50	65	85	100	50	65	85	100	50	75	100	125	
Downstream Breaking Capacity [Icu] (kA r.m.s.)													
HGM160E	50		65	85	100		65	85	100		75	85	100
HGM160S	65			85	100			85	100			85	100
HGM160H	85				100				100			100	125
HGM160L	100												125
HGM250E	50					65	85	100		75	85	100	
HGM250S	65						85	100			85	100	
HGM250H	85							100			100	125	
HGM250L	100											125	

Upstream Circuit Breaker	HGM630				HGM800			
	E	S	H	L	E	S	H	L
Breaking Capacity [Icu] (kA r.m.s.)	50	75	100	125		75	100	125
Downstream Breaking Capacity [Icu] (kA r.m.s.)								
Enhanced Breaking Capacity								
HGM250E	50		75	85	100	75	85	100
HGM250S	65			85	100		85	100
HGM250H	85			100	125		100	125
HGM250L	100				125			125
HGM400E	50		75	85	100	75	85	100
HGM400S	75			85	100		85	100
HGM400H	100				125			125
HGM630E	50		75	85	100	75	85	100
HGM630S	75			85	100		85	100
HGM630H	100				125			125
HGM800S	75						70	85
HGM800H	100							85

Technical Data (HGM/HGE)

Cascading Table

AC 440/460 V

Upstream Circuit Breaker : HGM30, HGM50, HGM60, HGM100, HGM125, HGM160, HGM250, HGM400

Downstream Circuit Breaker : HGD32, HGD63, HGD125, HGM30, HGM50, HGM60, HGM100

Upstream Circuit Breaker	HGM30				HGM50				HGM60				HGM100					
	E	S	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L
Breaking Capacity [Icu] (kA r.m.s.)	16	20	16	20	38	55	16	20	26	30	16	20	26	30	16	20	26	30
Downstream Breaking Capacity [Icu] (kA r.m.s.) Enhanced Breaking Capacity																		
HGD63E	3	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	
HGD63S	4.5	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	
HGD32NS, HGD63N/M	6		16	20	20	20	16	20	20	20	16	20	20	20	20	20	20	
HGD63H/P	10		16	20	26	26	16	20	20	20	16	20	20	20	20	20	20	
Upstream Circuit Breaker	HGM125				HGM160				HGM250				HGM400					
	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L		
Breaking Capacity [Icu] (kA r.m.s.)	20	26	38	55	20	26	38	55	20	26	38	55	20	26	38	55		
Downstream Breaking Capacity [Icu] (kA r.m.s.) Enhanced Breaking Capacity																		
HGD63E	3	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	
HGD63S	4.5	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	
HGD32NS, HGD63N/M	6	16	20	20	20	16	20	20	20	16	20	20	16	20	20	20	20	
HGD63H/P	10	16	20	26	26	16	20	26	16	20	26	26	16	20	26	26	26	
HGD100S/125	10	16	20	26	26	16	20	26	16	20	26	26	16	20	26	26	26	
Upstream Circuit Breaker	HGM30				HGM50				HGM60				HGM100					
	E	S	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L
Breaking Capacity [Icu] (kA r.m.s.)	16	20	16	20	38	55	16	20	26	30	16	20	26	30	16	20	26	30
Downstream Breaking Capacity [Icu] (kA r.m.s.) Enhanced Breaking Capacity																		
HGM30E	16		20		20	26	30		20	20	20		20	20	20	20	20	20
HGM30S	20				30	30			26	26			20	20	20	26	26	26
HGM50E	16				20	26	30		20	20	20		20	20	20	20	20	20
HGM50S	20				30	38			26	26			26	26	26	26	26	26
HGM50H	38					55												
HGM60E	16								20	20	20		20	20	20	20	20	20
HGM60S	20								26	26			26	26	26	26	26	26
HGM60H	26									30			30			30	30	30
HGM100E	16												20	20	20	20	20	20
HGM100S	20												26		26	26	26	26
HGM100H	26														30	30	30	30
Upstream Circuit Breaker	HGM125				HGM160				HGM250				HGM400					
	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L		
Breaking Capacity [Icu] (kA r.m.s.)	20	26	38	55	20	26	38	55	20	26	38	55	38	50	70	85		
Downstream Breaking Capacity [Icu] (kA r.m.s.) Enhanced Breaking Capacity																		
HGM30E	16	20	26	30	20	26	26	30	20	26	26	30	26	30	30	30	30	
HGM30S	20		26	30	30		26	30		26	30	30		30	30	30	30	30
HGM50E	16	20	26	30	20	26	30	30	20	26	30	30	20	26	30	30	30	30
HGM50S	20		26	30	38		26	30	38		26	30	38	20	30	38	38	38
HGM50H	38			55				55				55		50	70	70	70	70
HGM50L	55																	
HGM60E	16	20	26	30	20	26	26	30	20	26	26	30	26	26	30	30	30	30
HGM60S	20		26	30	30		26	30		26	30	30		26	30	30	30	30
HGM60H	26			38				38				38		30	38	38	38	38
HGM60L	30				38			38				38		38	38	38	38	38
HGM100E	16	20	26	30	20	26	26	30	20	26	26	30	26	26	30	30	30	30
HGM100S	20		26	30	30		26	30		26	30	30		30	30	30	30	30
HGM100H	26			38				38				38		38	38	38	38	38
HGM100L	26				38			38				38		38	38	38	38	38

Upstream Circuit Breaker : HGM125, HGM160, HGM250, HGM400, HGM630, HGM800

Downstream Circuit Breaker : HGM100, HGM160, HGM250, HGM400, HGM630, HGM800

Upstream Circuit Breaker	HGM125				HGM160				HGM250				HGM400				
	E	S	H	L	E	S	H	L	E	S	H	L	E	S	H	L	
Breaking Capacity [Icu] (kA r.m.s.)	20	26	38	55	20	26	38	55	20	26	38	55	38	50	70	85	
Downstream Breaking Capacity [Icu] (kA r.m.s.)																	
HGM125E	20		26	30	38		26	30	38		26	30	38	26	30	38	38
HGM125S	26			38	38		38	38		38	38		38	50	50	50	
HGM125H	38				55			55				55		50	70	70	
HGM125L	55													70	70	70	
HGM160E	20					26	30	38		26	30	38	26	30	38	38	
HGM160S	26						38	50		38	50	50	30	38	50	50	
HGM160H	38							55				55		50	70	70	
HGM160L	55													70	70	70	

Upstream Circuit Breaker	HGM250				HGM400				HGM630				HGM800			
	E	S	H	L	E	S	H	L	E	S	H	L	S	H	L	
Breaking Capacity [Icu] (kA r.m.s.)	20	26	38	55	38	50	70	85	38	50	70	85	50	70	85	
Downstream Breaking Capacity [Icu] (kA r.m.s.)																
HGM250E	20		26	30	38	26	30	38	38	26	30	38	38	30	38	38
HGM250S	26			38	50	30	38	50	50	30	38	50	50	38	50	50
HGM250H	38				55		50	70	70		50	70	70	50	70	70
HGM250L	55						70	70			70	70		70	70	70
HGM400E	38					50	70	70		50	70	70	50	70	70	70
HGM400S	50						70	85			70	85		70	85	85
HGM400H	70							85					85			85
HGM630E	38									50	70	70	50	70	70	70
HGM630S	50										70	85		70	85	85
HGM630H	70											85				85
HGM800S	50													70		85
HGM800H	70															85

Technical Data (HGM/HGE)

Installation


Insulation Distance (Safety Clearance)

For safety, insulation distance must be secured at installation. In case of installing a circuit breaker, safety clearances must be secured between breakers or between the circuit breaker and panel, bus bar and other adjacent devices. When the circuit breaker interrupts a short circuit, high temperature ionized gas is generated and the gas is discharged through the discharge outlet from the circuit breaker. As this gas can cause short-circuit accidents and grounding accidents, sufficient insulation distance is required between the circuit breaker and the panel.


※ In case insulation barrier is not installed between the circuit breaker terminals, secondary short-circuit accident may occur so it must be used.

The insulation barrier must be installed towards the direction of the circuit breaker's line indication part.


Separation distance in case the circuit breaker is installed side by side




Up/down/left/right distance in case of metallic panel



Front/back distance in case of metallic panel



Distance with circuit breaker in case the live part is exposed



※ In case of using the minimum separation distance ($A1 = 0$), terminal cover and phase to phase barrier must be assembled between the product. And pay attention to the tolerances of the enclosure dimensions.


※ If the distance between the live parts is less than 60 mm, the exposed part must be insulated.

HGM/HGE Type's Minimum Insulation Distance

Type	Minimum Clearance (mm)											
	460 V			240 V								
	A1	B1	B2	B3	C1	D1	A1	B1	B2	B3	C1	D1
HGM30 E/S	0	25	50	25	0	85	0	15	50	25	0	70
HGM50 E/S	0	25	50	25	0	85	0	15	50	25	0	70
HGM100 E/S/H/L	0	25	50	25	0	85	0	15	50	25	0	70
HGM50 H/L	0	25	50	25	0	85	0	15	50	25	0	70
HGM125 E/S/H/L	0	25	50	25	0	85	0	15	50	25	0	70
HGM160 E/S	0	25	80	40	0	140	0	15	80	40	0	110
HGM160 H/L	0	40	80	40	0	140	0	20	80	40	0	110
HGM250 E/S	0	25	80	40	0	140	0	15	80	40	0	110
HGM250 H/L	0	40	80	40	0	140	0	20	80	40	0	110
HGE30 E/S	0	25	50	25	0	85	0	15	50	25	0	70
HGE50 E/S	0	25	50	25	0	85	0	15	50	25	0	70
HGE100 E/S/H/L	0	25	50	25	0	85	0	15	50	25	0	70
HGE50 H/L	0	25	50	25	0	85	0	15	50	25	0	70
HGE125 E/S/H/L	0	25	50	25	0	85	0	15	50	25	0	70
HGE160 E/S	0	25	80	40	0	140	0	15	80	40	0	110
HGE160 H/L	0	40	80	40	0	140	0	20	80	40	0	110
HGE250 E/S	0	25	80	40	0	140	0	15	80	40	0	110
HGE250 H/L	0	40	80	40	0	140	0	20	80	40	0	110
HGM400 E/S	0	60	120	60	0	200	0	30	120	60	0	160
HGM400 H/L	0	80	120	60	0	200	0	40	120	60	0	160
HGM630,800 E/S	0	60	120	60	0	200	0	30	120	60	0	160
HGM630,800 H/L	0	80	120	60	0	200	0	40	120	60	0	160
HGE400 E/S	0	60	120	60	0	200	0	30	120	60	0	160
HGE400 H/L	0	80	120	60	0	200	0	40	120	60	0	160
HGE630,800 E/S	0	60	120	60	0	200	0	30	120	60	0	160
HGE630,800 H/L	0	80	120	60	0	200	0	40	120	60	0	160

Installation Angle


It can be installed vertically or horizontally without changing any characteristics of the HGM/HGE Type of circuit breakers and as for the detailed installation direction, please refer to the figure below.



Direction of Power Supply

HGM/HGE Type

When wiring the terminal between breakers, the LINE, LOAD mark in front of the product's cover must be checked.




Technical Data (HGM/HGE)

Standard Configuration


HGM/HGE Type

HGM/HGE30 ~ 250



Type	Part				
HGM/HGE 30, 50E/S, 60, 100	2P	2 EA (M4×L70)	4 EA	(M5×L15) (15 ~ 50 A)	1 EA
	3P	2 EA (M4×L70)	6 EA		2 EA
	4P	4 EA (M4×L70)	8 EA		3 EA
HGM/HGE 50H/L, 125	2P	2 EA (M4×L70)		4 EA (M8×L15)	1 EA
	3P	2 EA (M4×L70)		6 EA (M8×L15)	2 EA
	4P	4 EA (M4×L70)		8 EA (M8×L15)	3 EA
HGM/HGE 160, 250	2P	2 EA (M4×L70)		4 EA (Hex Socket M8×L18)	1 EA
	3P	2 EA (M4×L70)		6 EA (Hex Socket M8×L18)	2 EA
	4P	4 EA (M4×L70)		8 EA (Hex Socket M8×L18)	3 EA


HGM/HGE400 ~ 800



Type	Part				
HGM/HGE 400	2P	4 EA (M6×L103)	4 EA (M10×L30)	1 EA	1 EA
	3P	4 EA (M6×L103)	6 EA (M10×L30)	2 EA	1 EA
	4P	6 EA (M6×L103)	8 EA (M10×L30)	3 EA	1 EA
HGM/HGE 630, 800	2P	4 EA (M6×L103)	4 EA (M12×L30)	1 EA	1 EA
	3P	4 EA (M6×L103)	6 EA (M12×L30)	2 EA	1 EA
	4P	6 EA (M6×L103)	8 EA (M12×L30)	3 EA	1 EA

MCCB/ELCB Assembly and Terminal Mounting Specification

HGM/HGE Type



No	Type	Panel Mounting		Connection Terminal	
		Screw Specification	Terminal Connection Method and Dimensions (mm)	Conductor Processing	Tightening Torque
1	HGM/HGE 30, 50E/S, 60, 100	M4 : 13 kgf.cm			 M5 : 28.5 kgf.cm M8 : 110 kgf.cm
2	HGM/HGE 50H/L, 125	M4 : 13 kgf.cm			 M8 : 110 kgf.cm
3	HGM/HGE 160, 250	M4 : 13 kgf.cm			 Hex M8 : 110 kgf.cm
4	HGM/HGE 400	M6 : 45 kgf.cm			 Hex M10 : 270 kgf.cm
5	HGM/HGE 630, 800	M6 : 45 kgf.cm			 Hex M12 : 470 kgf.cm

Technical Data (HGP)

Environmental Operating Conditions

Temperature Derating


The overcurrent characteristic of MCCB has been set to the ambient temperature of 40°C. If the ambient temperature is less or more than 40°C, the overcurrent characteristics may differ.

If the Ambient Temperature is less than 40 °C

In order to ensure that the circuit breaker's overcurrent meet the derating curve at the given ambient temperature, the real current (I_r) has to be adjusted. The temperature correction ratio or each MCCB is shown in the circuit breaker's characteristics curve.

If the Ambient Temperature is more than 40 °C

As the internal temperature of MCCB is a sum of increased temperature due to current flow and the ambient temperature, if the ambient temperature exceeds 40 °C, thermal damage of internal insulation material of MCCB may occur causing the circuit breaker to trip at an early stage. When applying ambient temperature higher than 40 °C, the rated current must be adjusted as shown in the following rated current derating table.



In (Rated Current) :

Circuit breaker's rating at ambient temperature of 40 °C

I_r (Real Current) :

Circuit breaker's rating at the given temperature

$$I_r = \text{Correction Ratio (\%)} \times I_n$$

Rated Current Derating Table : HGP Type/Standard Mounting (Fixed Type)

Model	Rated Current (A)	Ambient Temperature (°C)									
		10	20	30	40	45	50	55	60	65	70
HGP160D	16	18	17	17	16	16	15	15	14	14	13
	20	22	22	21	20	19	19	18	18	17	16
	25	28	27	26	25	24	24	23	22	22	21
	32	36	35	33	32	31	30	29	28	27	26
	40	45	43	42	40	39	38	36	35	34	33
	50	56	54	52	50	49	47	46	44	43	41
	63	71	68	66	63	61	59	57	55	53	51
	80	90	87	83	80	78	75	73	70	68	65
	100	112	108	104	100	97	94	91	88	85	82
	125	141	135	130	125	121	117	113	109	105	101
	150	169	162	156	150	145	140	135	130	125	120
	160	180	173	166	160	155	150	145	140	135	130
	40	46	44	42	40	39	38	37	36	35	34
	50	58	55	53	50	49	48	46	45	44	43
HGP250	63	72	69	66	63	61	60	58	57	55	54
	80	92	88	84	80	78	76	74	72	70	68
	100	115	110	105	100	98	95	93	90	88	85
	125	144	138	131	125	122	119	116	113	109	106
	150	173	165	158	150	146	143	139	135	131	128
	160	184	176	168	160	156	152	148	144	140	136
	175	201	193	184	175	171	166	162	158	153	149
	200	230	220	210	200	195	190	185	180	175	170
	225	259	248	236	225	219	214	208	203	197	191
	250	288	275	263	250	244	238	231	225	219	213
HGP400 HGP630	300	323	315	308	300	291	282	273	264	255	246
	350	376	368	359	350	340	330	320	310	300	290
	400	430	420	410	400	388	376	364	352	340	328
	500	538	525	513	500	485	470	455	440	425	410
	630	677	662	646	630	611	592	573	554	535	516
HPG800	700	753	735	718	700	679	658	637	616	595	574
	800	860	840	820	800	776	752	728	704	680	656

Rated Current Derating Table : HGP Type/Plug-in Method

Model	Rated Current(A)	Ambient Temperature (°C)									
		10	20	30	40	45	50	55	60	65	70
HGP 160D	16	16	16	15	14	14	14	13	13	12	12
	20	20	19	19	18	17	17	16	16	15	15
	25	25	24	23	23	22	21	21	20	19	19
	32	32	31	30	29	28	27	26	25	24	23
	40	40	39	37	36	35	34	33	32	31	30
	50	51	49	47	45	44	42	41	40	38	37
	63	64	61	59	57	55	53	51	50	48	46
	80	81	78	75	72	70	68	65	63	61	59
	100	101	97	94	90	87	85	82	79	77	74
	125	126	122	117	113	109	105	102	98	95	91
	150	152	146	140	135	131	126	122	117	113	108
	160	162	156	150	144	140	135	131	126	122	117
	40	40	38	36	34	33	32	31	30	29	28
	50	50	48	45	43	41	40	39	38	36	35
HGP250	63	63	60	57	54	52	50	49	47	46	44
	80	80	76	72	68	66	64	62	60	58	56
	100	105	100	95	90	88	85	83	80	78	75
	125	131	125	119	113	109	106	103	100	97	94
	150	158	150	143	135	131	128	124	120	116	113
	160	168	160	152	144	140	136	132	128	124	120
	175	184	175	166	158	153	149	144	140	136	131
	200	210	200	190	180	175	170	165	160	155	150
	225	236	225	214	203	197	191	186	180	174	169
	250	263	250	238	225	219	213	206	200	194	188
HGP400 HGP630	300	284	277	271	264	256	248	240	232	224	216
	350	331	323	316	308	299	290	282	273	264	255
	400	378	370	361	352	341	331	320	310	299	289
	500	473	462	451	440	427	414	400	387	374	361
	630	596	582	568	554	538	521	504	488	471	454
HGP800	700	696	680	664	648	628	609	589	570	550	531
	800	796	777	759	740	718	696	673	651	629	607

Technical Data (HGP)

Environmental Operating Conditions

Altitude Derating

The characteristics of the circuit breaker is not affected at an altitude of less than 2,000 m. Characteristics of insulation and air cooling of the circuit breaker are reduced at an altitude of more than 2,000 m and the rated current and rated voltage must be adjusted as shown in the table below. However, there is no change in the characteristics of breaking capacity.

Circuit breaker	Altitude	2,000 m	3,000 m	4,000 m	5,000 m
HGP Type MCCB	Withstand Voltage (V)	3,000	2,500	2,100	1,800
HGP160D	Insulation Voltage (V) U_i	1,000	850	750	650
HGP250 ~ 800	Maximum Operational Voltage (V) U_e	690	590	520	460
	Average Through-Current (A), at 40 °C $I_{n,x}$	1	0.96	0.93	0.9

Vibrations

The excessive vibration may cause problems such as decrease of breaking capacity, lower dynamic strength, reduction of electric current conductivity or compromising safety of operating characteristics. Therefore, proper consideration is required with regards to these environmental stresses when it comes to designating the circuit breakers. These stresses are generated by the vibration during transportation, magnetic impact during opening and closing operation and influence of adjacent devices. Our circuit breaker has been verified in accordance with the standards with regards to vibration resistance.

Vibration Test

Vibration test is verified with the standard requested by the shipping certification institute in compliance with IEC 60068-2-6. Out of the vibration test items, resonance test and vibration Endurance test were verified based on the following standard.

Vibration Endurance Test

A sinusoidal wave with frequency of 30 Hz is applied for 90 minutes to check for abnormalities.


- 30 Hz : 0.7 g Acceleration

Resonance Test

It confirms whether vibration is generated in the characteristics part of MCCB by slowly changing the frequency in the frequency sector of the following sinusoidal wave.





- 5 ~ 13.2 Hz : 1 mm Displacement
- 13.2 ~ 100 Hz : 0.7 g Acceleration

Seismic Performance and Shock Tolerance Table

Item	Seismic
Test Condition	<p>Mounting Posture Direction of Vibration, Shock</p> <ul style="list-style-type: none"> • Vertical mounting • Up-down, left-right, front-back 
Status of MCCB	<ul style="list-style-type: none"> • Non-conduction (ON or OFF status) • Status where rated current has been conducted on until the temperature of MCCB becomes constant and continuous
Test Result	<p>Judgment Condition</p> <ul style="list-style-type: none"> • If it is ON, it should not turn OFF • If it is OFF, it should not turn ON • No abnormal status such as damage, deformation or loosened screw part • The characteristics of switch and trip after the test must be normal

Degree of Protection

The MCCB's IP rating is defined based on IEC 60529. The IP rating also depends on product conditions.

Condition	Circuit Breaker	Circuit Breaker + Terminal Cover	Circuit Breaker + Terminal Cover + Rotary Handle (Front Contact Type)	Circuit Breaker + Terminal Cover + Rotary Handle (Extension Type)
Appearance				
Protection Degree	IP20	IP40	IP40	IP40/IP54

※ 1) When applying IP54, please contact us separately.

Technical Data (HGP)

Power Loss / Resistance

HGP Type MCCB

Type	Rated Current (A)	HGP50D		HGP125D		HGP160D		HGP100		HGP160		HGP250	
		R/Pole (mΩ)	P/Pole (W)										
 Fixed	16	14.4	3.69	14.4	3.69	14.4	3.69						
	20	14.4	5.76	14.4	5.76	14.4	5.76						
	25	6.372	3.98	6.372	3.98	6.372	3.98						
	32	4.056	4.15	4.056	4.15	4.056	4.15						
	40	2.544	4.07	2.544	4.07	2.544	4.07	2.40	3.84				
	50	2.544	6.36	2.544	6.36	2.544	6.36	1.80	4.50				
	63			1.488	5.91	1.488	5.91	1.30	5.16				
	80			1.188	7.60	1.188	7.60	0.84	5.37				
	100			1.044	10.44	1.044	10.44	0.88	8.80	0.88	8.80		
	125			0.924	14.44	0.924	14.44			0.61	9.53	0.61	9.53
	150					0.792	17.82			0.46	10.35	0.46	10.35
	160					0.792	20.28			0.46	11.78	0.46	11.78
	175											0.39	11.94
	200											0.39	15.60
	225											0.3	15.19
	250											0.3	18.75

Type	Rated Current (A)	HGP400		HGP630		HGP800	
		R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)
 Fixed	300	0.215	19.35				
	350	0.215	26.34				
	400	0.185	29.60				
	500		0.155	38.75			
	630		0.125	49.61			
	700				0.11	53.90	
	800				0.08	51.20	

Type	Rated Current (A)	HGP100 MP	
		R/Pole (mΩ)	P/Pole (W)
 Fixed	2.5	160.7	1
	3.2	67.20	0.69
	6.3	14.85	0.59
	12.5	4.29	0.67
	20	2.53	1.01
	32	0.96	0.98
	50	0.59	1.49
	63	0.59	2.35
	80	0.52	3.34
	100	0.48	4.78

Type	Rated Current (A)	HGP100 ETU		HGP160 ETU		HGP250 ETU		HGP400 ETU		HGP630 ETU		HGP800 ETU	
		R/Pole (mΩ)	P/Pole (W)										
 Fixed	40	0.6	0.96										
	100	0.3	3.00	0.3	3.00								
	160			0.3	7.68	0.3	7.68						
	250					0.3	18.75	0.125	7.81				
	400							0.125	20.00				
	630									0.125	49.61		
	800										0.08	51.20	

Type	Rated Current (A)	HGP50D		HGP125D		HGP160D		HGP100		HGP160		HGP250	
		R/Pole (mΩ)	P/Pole (W)										
Plug-in	16	14.48	3.71	14.48	3.71	14.48	3.71						
	20	14.48	5.79	14.48	5.79	14.48	5.79						
	25	6.452	4.03	6.452	4.03	6.452	4.03						
	32	4.136	4.24	4.136	4.24	4.136	4.24						
	40	2.624	4.20	2.624	4.20	2.624	4.20	2.46	3.94				
	50	2.624	6.56	2.624	6.56	2.624	6.56	1.86	4.65				
	63			1.568	6.22	1.568	6.22	1.36	5.40				
	80			1.268	8.12	1.268	8.12	0.899	5.75				
	100			1.124	11.24	1.124	11.24	0.94	9.40	0.94	9.40		
	125			1.004	15.69	1.004	15.69			0.67	10.47	0.67	10.47
	150					0.872	19.62			0.52	11.70	0.52	11.70
	160					0.872	22.32			0.52	13.31	0.52	13.31
	175										0.45	13.78	
	200										0.45	18.00	
	225										0.36	18.23	
	250										0.36	22.50	

Type	Rated Current (A)	HGP400		HGP630		HGP800	
		R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)	R/Pole (mΩ)	P/Pole (W)
Plug-in	300	0.255	22.95				
	350	0.255	31.24				
	400	0.225	36.00				
	500			0.195	48.75		
	630			0.165	65.49		
	700					0.13	63.70
	800					0.1	64.00

Type	Rated Current (A)	HGP100 MP	
		R/Pole (mΩ)	P/Pole (W)
Plug-in	2.5	160.76	1
	3.2	67.26	0.69
	6.3	14.91	0.59
	12.5	4.35	0.68
	20	2.59	1.04
	32	1.015	1.04
	50	0.654	1.64
	63	0.651	2.58
	80	0.582	3.72
	100	0.538	5.38

Type	Rated Current (A)	HGP100 ETU		HGP160 ETU		HGP250 ETU		HGP400 ETU		HGP630 ETU		HGP800 ETU	
		R/Pole (mΩ)	P/Pole (W)										
Plug-in	40	0.66	1.06										
	100	0.36	3.60	0.36	3.60								
	160			0.36	9.22	0.36	9.22						
	250					0.36	22.50	0.165	10.31				
	400							0.165	26.40				
	630									0.165	65.49		
	800											0.1	64.00

Technical Data (HGP)

Cascading Table

AC 220/240 V

Upstream : HGP50D, HGP125D, HGP160D, HGP250, HGP400, HGP630

Downstream : HGD32 *, HGD63 *, HGD125 *, HGM30, HGM50

Upstream Circuit Breaker	HGP50D				HGP125D				HGP160D			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200
Enhanced Breaking Capacity												
HGD63E *	10	20	20	20	20	20	20	20	20	20	20	20
HGD63S *	15	30	30	30	30	30	30	30	30	30	30	30
HGD32NS *, HGD63N/M *	20	40	60	60	40	60	60	60	40	60	60	60
HGD63H/P *	25	40	60	60	40	60	60	60	40	60	60	60
HGD100S/125 *	25	40	60	60	40	60	60	60	40	60	60	60
Upstream Circuit Breaker	HGP100				HGP160				HGP250			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200
Enhanced Breaking Capacity												
HGD63E *	10	20	20	20	20	20	20	20	20	20	20	20
HGD63S *	15	30	30	30	30	30	30	30	30	30	30	30
HGD32NS *, HGD63N/M *	20	40	60	60	40	60	60	60	40	60	60	60
HGD63H/P *	25	40	60	60	40	60	60	60	40	60	60	60
HGD100S/125 *	25				40	60	60	60	40	60	60	60
Upstream Circuit Breaker	HGP50D				HGP125D				HGP160D			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200
Enhanced Breaking Capacity												
HGM30E	35	65	70	70	70	65	70	70	65	70	70	70
HGM30S	50	65	70	70	70	65	70	70	65	70	70	70
HGM50E	35	65	85	100	100	65	85	100	65	85	100	100
HGM50S	50	65	100	130	130	65	100	130	65	100	130	130
HGM50H	85		100	130	150		100	130	150		100	130
HGM50L	100			130	150			130	150			130
Upstream Circuit Breaker	HGP100				HGP160							
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200
Enhanced Breaking Capacity												
HGM30E	35	65	70	70	70	65	70	70	70	70	70	70
HGM30S	50	65	70	70	70	65	70	70	70	70	70	70
HGM50E	35	65	85	100	100	65	85	100	85	100	100	100
HGM50S	50	65	100	130	130	65	100	130	100	130	130	130
HGM50H	85		100	130	150		100	130	150		130	150
HGM50L	100			130	150			130	150			130
Upstream Circuit Breaker	HGP250				HGP400				HGP630			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200
Enhanced Breaking Capacity												
HGM30E	35	65	70	70	70	65	70	70	65	70	70	70
HGM30S	50	65	70	70	70	65	70	70	65	70	70	70
HGM50E	35	65	85	100	100	65	85	100	100	85	100	100
HGM50S	50	65	100	130	130	65	100	130	130	65	100	130
HGM50H	85		100	130	150		100	130	150		100	130
HGM50L	100			130	150			130	150			130

* F type is for overseas sales.

Upstream : HGP125D, HGP160D, HGP250, HGP400, HGP630

Downstream : HGM60, HGM100, HGM125, HGM160, HGM250

Upstream Circuit Breaker	HGP125D				HGP160D				HGP400			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200
Downstream Breaking Capacity [Icu] (kA r.m.s.)												
HGM60E	35	65	70	70	65	70	70	70	65	70	70	70
HGM60S	50	65	70	70	65	70	70	70	65	70	70	70
HGM60H	50	65	70	70	65	70	70	70	65	70	70	70
HGM60L	50	65	70	70	65	70	70	70	65	70	70	70
HGM100E	35	65	70	70	65	70	70	70	65	70	70	70
HGM100S	50	65	70	70	65	70	70	70	65	70	70	70
HGM100H	50	65	70	70	65	70	70	70	65	70	70	70
HGM100L	50	65	70	70	65	70	70	70	65	70	70	70
HGM125E	50	65	85	100	65	85	100	100				
HGM125S	65		100	130	130		100	130				
HGM125H	85		100	130	150		100	130	150			
HGM125L	100			130	150			130	150			

Upstream Circuit Breaker	HGP160				HGP250				HGP400				HGP630				
	F*	S	H	X													
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200	65	100	130	200	
Downstream Breaking Capacity [Icu] (kA r.m.s.)																	
HGM60E	35	65	70	70	65	70	70	70	65	70	70	70	65	70	70	70	
HGM60S	50	65	70	70	65	70	70	70	65	70	70	70	65	70	70	70	
HGM60H	50	65	70	70	65	70	70	70	65	70	70	70	65	70	70	70	
HGM60L	50	65	70	70	65	70	70	70	65	70	70	70	65	70	70	70	
HGM100E	35	65	70	70	65	70	70	70	65	70	70	70	65	70	70	70	
HGM100S	50	65	70	70	65	70	70	70	65	70	70	70	65	70	70	70	
HGM100H	50	65	70	70	65	70	70	70	65	70	70	70	65	70	70	70	
HGM100L	50	65	70	70	65	70	70	70	65	70	70	70	65	70	70	70	
HGM125E	50	65	85	100	65	85	100	100	65	85	100	100	65	85	100	100	
HGM125S	65		100	130	130		100	130	130		100	130	130		100	130	130
HGM125H	85		100	130	150		100	130	150		100	130	150		100	130	150
HGM125L	100			130	150			130	150			130	150			130	150

Upstream Circuit Breaker	HGP160D				HGP250				HGP400				
	F*	S	H	X	F*	S	H	X	F*	S	H	X	
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200	
Downstream Breaking Capacity [Icu] (kA r.m.s.)													
HGM160E	50	65	85	100	100	65	85	100	100	65	85	100	100
HGM160S	65		100	130	130		100	130	130		100	130	130
HGM160H	85		100	130	150		100	130	150		100	130	150
HGM160L	100			130	150			130	150			130	150
HGM250E	50									65	85	100	100
HGM250S	65										100	130	130
HGM250H	85										100	130	150
HGM250L	100											130	150

* F type is for overseas sales.

Technical Data (HGP)

Cascading Table

AC 220/240 V

Upstream : HGP400, HGP630, HGP800

Downstream : HGM160, HGM250, HGM400, HGM600, HGM800

Upstream Circuit Breaker	HGP400				HGP630				HGP800			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200
Downstream Breaking Capacity [Icu] (kA r.m.s.)												
HGM160E	50	65	85	100	100	65	85	100	100			
HGM160S	65		100	130	130		100	130	130			
HGM160H	85		100	130	150		100	130	150			
HGM160L	100			130	150			130	150			
HGM250E	50	65	85	100	100	65	85	100	100	65	85	100
HGM250S	65		100	130	130		100	130	130		100	130
HGM250H	85		100	130	150		100	130	150		100	130
HGM250L	100			130	150			130	150			130

Upstream Circuit Breaker	HGP400				HGP630				HGP800			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200
Downstream Breaking Capacity [Icu] (kA r.m.s.)												
HGM400E	50	65	100	130	150	65	100	130	150	65	100	130
HGM400S	75		100	130	150		100	130	150		100	130
HGM400H	100			130	200			130	200			130
HGM400L	125			130	200			130	200			130
HGM600E	50					65	100	130	150	65	100	130
HGM600S	75						100	130	150		100	130
HGM600H	100							130	200			130
HGM600L	125							130	200			130
HGM800S	75										100	130
HGM800H	100											130
HGM800L	125											130

※ * F type is for overseas sales.

Upstream : HGP50D, HGP125D, HGP160D, HGP250, HGP400, HGP630, HGP800
 Downstream : HGP50D, HGP125D, HGP160D, HGP250, HGP400, HGP630, HGP800

Upstream Circuit Breaker	HGP50D				HGP125D				HGP160D				
	F*	S	H	X	F*	S	H	X	F*	S	H	X	
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200	
Downstream Breaking Capacity [Icu] (kA r.m.s.)													
HGP50D/125D/160D F*	65		100	130	150		100	130	150		100	130	150
HGP50D/125D/160D S	100		130	200			130	200			130	200	
HGP50D/125D/160D H	130			200				200				200	

Upstream Circuit Breaker	HGP100				HGP160				HGP250				
	F*	S	H	X	F*	S	H	X	F*	S	H	X	
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200	
Downstream Breaking Capacity [Icu] (kA r.m.s.)													
HGP50D F*	65		100	130	150		100	130	150		100	130	150
HGP50D S	100		130	200			130	200			130	200	
HGP50D H	130			200				200				200	
HGP125D F*	65		100	130	150		100	130	150		100	130	150
HGP125D S	100		130	200			130	200			130	200	
HGP125D H	130			200				200				200	
HGP160D F*	65		100	130	150		100	130	150		100	130	150
HGP160D S	100		130	200			130	200			130	200	
HGP160D H	130			200				200				200	
HGP100 F*	65		100	130	150		100	130	150		100	130	150
HGP100 S	100		130	200			130	200			130	200	
HGP100 H	130			200				200				200	
HGP160 F*	65						100	130	150		100	130	150
HGP160 S	100						130	200			130	200	
HGP160 H	130							200				200	
HGP250 F*	65										100	130	150
HGP250 S	100										130	200	
HGP250 H	130											200	

Upstream Circuit Breaker	HGP400				HGP630				HGP800				
	F*	S	H	X	F*	S	H	X	F*	S	H	X	
Breaking Capacity [Icu] (kA r.m.s.)	65	100	130	200	65	100	130	200	65	100	130	200	
Downstream Breaking Capacity [Icu] (kA r.m.s.)													
HGP50D/125D/160DF*	65		100	130	150		100	130	150		100	130	150
HGP50D/125D/160DS	100		130	200			130	200			130	200	
HGP50D/125D/160DH	130			200				200				200	
HGP100 F*	65		100	130	150		100	130	150		100	130	150
HGP100 S	100		130	200			130	200			130	200	
HGP100 H	130			200				200				200	
HGP160 F*	65		100	130	150		100	130	150		100	130	150
HGP160 S	100		130	200			130	200			130	200	
HGP160 H	130			200				200				200	
HGP250 F*	65		100	130	150		100	130	150		100	130	150
HGP250 S	100		130	200			130	200			130	200	
HGP250 H	130			200				200				200	
HGP400/630 F*	65		100	130	150		100	130	150		100	130	150
HGP400/630 S	100		130	200			130	200			130	200	
HGP400/630 H	130			200				200				200	
HGP800 F*	65										100	130	150
HGP800 S	100										130	200	
HGP800 H	130											200	

* F type is for overseas sales.

Technical Data (HGP)

Cascading Table

AC 440/460 V

Upstream : HGP50D, HGP125D, HGP160D, HGP250, HGP400, HGP630

Downstream : HGD32 *, HGD63 *, HGD125 *, HGM30, HGM50

Upstream Circuit Breaker	HGP50D				HGP125D				HGP160D			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	65	85	150	36	65	85	150
Enhanced Breaking Capacity												
HGD63E *	3	10	15	15	15	10	15	15	15	10	15	15
HGD63S *	4.5	14	15	20	20	15	20	20	20	15	20	20
HGD32NS *, HGD63N/M *	6	20	26	26	26	20	26	26	26	20	26	26
HGD63H/P *	10	20	30	30	30	20	30	30	30	20	30	30
HGD100S/125 *	10	20	30	30	30	20	30	30	30	20	30	30

Upstream Circuit Breaker	HGP100				HGP160				HGP250			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	65	85	150	36	65	85	150
Enhanced Breaking Capacity												
HGD63E *	3	10	15	15	15	10	15	15	15	10	15	15
HGD63S *	4.5	15	20	20	20	15	20	20	20	15	20	20
HGD32NS *, HGD63N/M *	6	20	26	26	26	20	26	26	26	20	26	26
HGD63H/P *	10	20	30	30	30	20	30	30	30	20	30	30
HGD100S/125 *	10				20	30	30	30	20	30	30	30

Upstream Circuit Breaker	HGP50D				HGP125D				HGP160D			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	65	85	150	36	65	85	150
Enhanced Breaking Capacity												
HGM30 E	16	26	38	38	38	26	38	38	38	26	38	38
HGM30 S	20	30	38	38	38	30	38	38	38	30	38	38
HGM50 E	16	26	38	38	38	26	38	38	38	26	38	38
HGM50 S	20	30	38	38	38	30	38	38	38	30	38	38
HGM50 H	38		50	70	85		50	70	85		50	70
HGM50 L	55		65	70	85		65	70	85		65	70

Upstream Circuit Breaker	HGP100				HGP160			
	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	70	85	150
Enhanced Breaking Capacity								
HGM30 E	16	26	38	38	38	26	38	38
HGM30 S	20	30	38	38	38	30	38	38
HGM50 E	16	26	38	38	38	26	38	38
HGM50 S	20	30	38	38	38	30	38	38
HGM50 H	38		50	70	85		50	70
HGM50 L	55		65	70	85		65	70

Upstream Circuit Breaker	HGP250				HGP400				HGP630			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	70	85	150	36	70	85	150
Enhanced Breaking Capacity												
HGM30 E	16	26	38	38	38	26	38	38	38	26	38	38
HGM30 S	20	30	38	38	38	30	38	38	38	30	38	38
HGM50 E	16	26	38	38	38	26	38	38	38	26	38	38
HGM50 S	20	30	38	38	38	30	38	38	38	30	38	38
HGM50 H	38		50	70	85		50	70	85		50	70
HGM50 L	55		65	70	85		65	70	85		65	70

Upstream : HGP125D, HGP160D, HGP250, HGP400, HGP630

Downstream : HGM60, HGM100, HGM125, HGM160, HGM250

Upstream Circuit Breaker	HGP125D				HGP160D				HGP100			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	65	85	150	36	65	85	150
Downstream Breaking Capacity [Icu] (kA r.m.s.)												
HGM60 E	16	26	38	38	38	26	38	38	38	26	38	38
HGM60 S	20	30	38	38	38	30	38	38	38	30	38	38
HGM60 H	26	36	50	50	55	36	50	50	55	36	50	50
HGM60 L	30	36	50	50	55	36	50	50	55	36	50	55
HGM100 E	16	26	38	38	38	26	38	38	38	26	38	38
HGM100 S	20	30	38	38	38	30	38	38	38	30	38	38
HGM100 H	26	36	50	50	55	36	50	50	55	36	50	55
HGM100 L	30	36	50	50	55	36	50	50	55	36	50	55
HGM125 E	20	36	50	50	50	36	50	50	50			
HGM125 S	26	36	50	50	50	36	50	50	50			
HGM125 H	38		50	70	85		50	70	85			
HGM125 L	55		65	70	85		65	70	85			

Upstream Circuit Breaker	HGP160				HGP250				HGP400				HGP630				
	F*	S	H	X													
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	65	85	150	36	70	85	150	36	70	85	150	
Downstream Breaking Capacity [Icu] (kA r.m.s.)																	
HGM60 E	16	26	38	38	38	26	38	38	26	38	38	38	26	38	38	38	
HGM60 S	20	30	38	38	38	30	38	38	30	38	38	38	30	38	38	38	
HGM60 H	26	36	50	50	55	36	50	50	55	36	50	50	55	36	50	50	55
HGM60 L	30	36	50	50	55	36	50	50	55	36	50	50	55	36	50	50	55
HGM100 E	16	26	38	38	38	26	38	38	26	38	38	38	26	38	38	38	
HGM100 S	20	30	38	38	38	30	38	38	30	38	38	38	30	38	38	38	
HGM100 H	26	36	50	50	55	36	50	50	55	36	50	50	55	36	50	50	55
HGM100 L	30	36	50	50	55	36	50	50	55	36	50	50	55	36	50	50	55
HGM125 E	20	36	50	50	50	36	50	50	36	50	50	50	36	50	50	50	
HGM125 S	26	36	50	50	50	36	50	50	36	50	50	50	36	50	50	50	
HGM125 H	38		50	70	85		50	70	85		50	70	85		50	70	85
HGM125 L	55		65	70	85		65	70	85		65	70	85		65	70	85

Upstream Circuit Breaker	HGP160D				HGP100				HGP160				HGP250			
	F*	S	H	X	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	65	85	150	36	65	85	150	36	65	85	150
Downstream Breaking Capacity [Icu] (kA r.m.s.)																
HGM160 E	20	36	50	50	50				36	50	50	50	36	50	50	50
HGM160 S	26	36	50	50	50				36	50	50	50	36	50	50	50
HGM160 H	38		50	70	85				50	70	85		50	70	85	
HGM160 L	55		65	70	85				65	70	85		65	70	85	
HGM250 E	20												36	50	50	50
HGM250 S	26												36	50	50	50
HGM250 H	38												50	70	85	
HGM250 L	55												65	70	85	

※ * F type is for overseas sales.

Technical Data (HGP)

Cascading Table

AC 440/460 V

Upstream : HGP400, HGP630, HGP800

Downstream : HGM160, HGM250, HGM400, HGM600, HGM800

Upstream Circuit Breaker	HGP400				HGP630				HGP800			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	36	70	85	150	36	70	85	150	36	70	85	150
Downstream Breaking Capacity [Icu] (kA r.m.s.)												
HGM160 E	20	36	50	50	50	36	50	50	50			
HGM160 S	26	36	50	50	50	36	50	50	50			
HGM160 H	38		50	70	85		50	70	85			
HGM160 L	55		65	70	85		65	70	85			
HGM250 E	20	36	50	50	50	36	50	50	50	36	50	50
HGM250 S	26	36	50	50	50	36	50	50	50	36	50	50
HGM250 H	38		50	70	85		50	70	85		50	70
HGM250 L	55		65	70	85		65	70	85		65	70

Upstream Circuit Breaker	HGP400				HGP630				HGP800			
	F*	S	H	X	F*	S	H	X	F*	S	H	X
Breaking Capacity [Icu] (kA r.m.s.)	36	70	85	150	36	70	85	150	36	70	85	150
Downstream Breaking Capacity [Icu] (kA r.m.s.)												
HGM400 E	38		70	85	100		70	85	100		70	85
HGM400 S	50		70	85	100		70	85	100		70	85
HGM400 H	70			85	100			85	100			85
HGM400 L	85				100				100			100
HGM600 E	38						70	85	100		70	85
HGM600 S	50						70	85	100		70	85
HGM600 H	70							85	100			85
HGM600 L	85								100			100
HGM800 S	50										70	85
HGM800 H	70											85
HGM800 L	85											100

※ * F type is for overseas sales.

Upstream : HGP50D, HGP125D, HGP160D, HGP250, HGP400, HGP630, HGP800
 Downstream : HGP50D, HGP125D, HGP160D, HGP250, HGP400, HGP630, HGP800

Upstream Circuit Breaker	HGP50D				HGP125D				HGP160D				
	F*	S	H	X	F*	S	H	X	F*	S	H	X	
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	65	85	150	36	65	85	150	
Downstream Breaking Capacity [Icu] (kA r.m.s.)													
HGP50D/125D/160D F*	38		65	85	100		65	85	100		65	85	100
HGP50D/125D/160D S	70			85	150			85	150			85	150
HGP50D/125D/160D H	85				150				150				150

Upstream Circuit Breaker	HGP100				HGP160				HGP250				
	F*	S	H	X	F*	S	H	X	F*	S	H	X	
Breaking Capacity [Icu] (kA r.m.s.)	36	65	85	150	36	65	85	150	36	65	85	150	
Downstream Breaking Capacity [Icu] (kA r.m.s.)													
HGP50D F*	36		65	85	100		65	85	100		65	85	100
HGP50D S	65			85	150			85	150			85	150
HGP50D H	85				150								150
HGP125D F*	36						65	85	100		65	85	100
HGP125D S	65							85	150			85	150
HGP125D H	85								150				150
HGP160D F*	36						65	85	100		65	85	100
HGP160D S	65							85	150			85	150
HGP160D H	85								150				150
HGP100 F*	36		65	85	100		65	85	100		65	85	100
HGP100 S	65			85	150			85	150			85	150
HGP100 H	85				150								150
HGP160 F*	36						65	85	100		65	85	100
HGP160 S	65							85	150			85	150
HGP160 H	85								150				150
HGP250 F*	36										65	85	100
HGP250 S	65											85	150
HGP250 H	85												150

Upstream Circuit Breaker	HGP400				HGP630				HGP800				
	F*	S	H	X	F*	S	H	X	F*	S	H	X	
Breaking Capacity [Icu] (kA r.m.s.)	36	70	85	150	36	70	85	150	36	70	85	150	
Downstream Breaking Capacity [Icu] (kA r.m.s.)													
HGP50D/125D/160D F*	36		65	85	100		65	85	100		65	85	100
HGP50D/125D/160D S	65			85	150			85	150			85	150
HGP50D/125D/160D H	85				150								150
HGP100 F*	36		65	85	100		65	85	100		65	85	100
HGP100 S	65			85	150			85	150			85	150
HGP100 H	85				150								150
HGP160 F*	36		65	85	100		65	85	100		65	85	100
HGP160 S	65			85	150			85	150			85	150
HGP160 H	85				150								150
HGP250 F*	36		65	85	100		65	85	100		65	85	100
HGP250 S	65			85	150			85	150			85	150
HGP250 H	85				150								150
HGP400/630 F*	36		65	85	100		65	85	100		65	85	100
HGP400/630 S	70			85	150			85	150			85	150
HGP400/630 H	85				150								150
HGP800 F*	36										65	85	100
HGP800 S	70											85	150
HGP800 H	85												150

※ * F type is for overseas sales.

Technical Data (HGP)

Discrimination Table

Ue < AC 460 V

Upstream : HGP50D ~ HGP800

Downstream : HGD32, HGD63, HGD125

Model	Trip Unit	HGP160D F*/S/H/X													
		Thermal Magnetic													
		Rated Current (A)	16	20	25	32	40	50	63	75	80	100	125	150	160
HGD32 - B, C, D Curve	1	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	3	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	5	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	6	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	10	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	16		0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	20			0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	25				0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	32					0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	40						0.4	0.5	0.6	0.64	0.8	1	T	T	
HGD63 - B, C, D Curve	1	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	2	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	3	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	4	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	5	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	6	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	10	0.19	0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	13		0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T	
	15			0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T
	16			0.32	0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T
	20				0.32	0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T
	25					0.32	0.32	0.4	0.5	0.6	0.64	0.8	1	T	T
	32						0.32	0.4	0.5	0.6	0.64	0.8	1	T	T
	40							0.4	0.5	0.6	0.64	0.8	1	T	T
HGD125 B, C, D Curve	50								0.5	0.6	0.64	0.8	1	T	T
	63									0.6	0.64	0.8	1	T	T
	63										0.64	0.8	2.4	2.4	2.4
	80											0.8	2.4	2.4	2.4
	100												2.4	2.4	2.4
	125												2.4	2.4	2.4

T Total Discrimination, Up to the Breaking Capacity of the Downstream Circuit Breaker

4 Discrimination Limit = 4 kA

No Discrimination

※ * F type is for overseas sales.

Upstream : HGP50D ~ HGP800

Downstream : HGD32, HGD63, HGD125

Model	Trip Unit	HGP250 F*/S/H/X																HGP400 F*/S/H/X	HGP630 F*/S/H/X	HGP800 F*/S/H/X		
		Thermal Magnetic & Electronic																				
		Rated Current (A)	40	50	63	75	80	100	125	150	160	175	200	225	250	300	350	400	500	630	700	800
HGD32 - B, C, D Curve	1	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	3	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	5	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	6	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	10	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	16	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	20	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	25	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	32	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	40	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
HGD63 - B, C, D Curve	1	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	2	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	3	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	4	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	5	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	6	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	10	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	13	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	15	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	16	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
HGD125 B, C, D Curve	20	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	25	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	32	0.32	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	40	0.4	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	50	0.5	0.6	0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
HGD125 B, C, D Curve	63				0.64	0.8	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T	T
	63					0.64	0.8	2.4	2.4	2.4	T	T	T	T	T	T	T	T	T	T	T	T
	80						0.8	2.4	2.4	2.4	T	T	T	T	T	T	T	T	T	T	T	T
	100							2.4	2.4	2.4	T	T	T	T	T	T	T	T	T	T	T	T
	125							2.4	2.4	2.4	T	T	T	T	T	T	T	T	T	T	T	T

T Total Discrimination, Up to the Breaking Capacity of the Downstream Circuit Breaker

4 Discrimination Limit = 4 kA

No Discrimination

※ * F type is for overseas sales.

Technical Data (HGP)

Discrimination Table

Ue < AC 460 V

Upstream : HGP50D ~ HGP800

Downstream : HGM30 ~ HGM800

		HGP160D F*/S/H/X													
Model	Trip Unit	Thermal Magnetic													
		Rated Current (A)	16	20	25	32	40	50	63	75	80	100	125	160	
HGM30 E/S HGM50 E/S HGM60 E/S/H/L HGM100 E/S/H/L	16								0.5	0.6	0.64	0.8	1	1.25	1.25
	20								0.5	0.6	0.64	0.8	1	1.25	1.25
	25								0.5	0.6	0.64	0.8	1	1.25	1.25
	32								0.5	0.6	0.64	0.8	1	1.25	1.25
	40										0.64	0.8	1	1.25	1.25
	50										0.64	0.8	1	1.25	1.25
	63										0.8	1	1.25	1.25	
	75											1	1.25	1.25	
	80											1	1.25	1.25	
	100													1.25	
HGM125 E/S/H/L	16								0.5	0.6	0.64	0.8	1	1.25	1.25
	20								0.5	0.6	0.64	0.8	1	1.25	1.25
	25								0.5	0.6	0.64	0.8	1	1.25	1.25
	32								0.5	0.6	0.64	0.8	1	1.25	1.25
	40										0.64	0.8	1	1.25	1.25
	50										0.64	0.8	1	1.25	1.25
	63										0.8	1	1.25	1.25	
	75											1	1.25	1.25	
	80											1	1.25	1.25	
	100													1.25	
HGM160 E/S/H/L HGM250 E/S/H/L	125														
	100														
	125														
	150														
	160														
	175														
	200														
	225														
	250														
	250														
HGM400 E/S/H/L	300														
	350														
HGM630 E/S/H/L HGM800 S/H/L	400														
	500														
	630														
	700														
	800														

T Total Discrimination, Up to the Breaking Capacity of the Downstream Circuit Breaker

4 Discrimination Limit = 4 kA

No Discrimination

* F type is for overseas sales.

Upstream : HGP50D ~ HGP800
 Downstream : HGM30 ~ HGM800

Model	Trip Unit	HGP250 F*/S/H/X														HGP400 F*/S/H/X	HGP630 F*/S/H/X	HGP800 F*/S/H/X					
		Thermal Magnetic & Electronic																					
		Rated Current (A)	40	50	63	75	80	100	125	150	160	175	200	225	250	300	350	400	500	630	700	800	
HGM30 E/S HGM50 E/S HGM60 E/S/H/L HGM100 E/S/H/L	16				0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	20				0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	25				0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	32				0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	40					0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	50						0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	63							0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	75								1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	80								1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	100										1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
HGM125 E/S/H/L	16				0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	20				0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	25				0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	32				0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	40					0.6	0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	50						0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	63							0.8	1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	75								1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	80								1	1.25	1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	100										1.25	1.4	1.6	1.8	2	T	T	T	T	T	T	T	
HGM160 E/S/H/L HGM250 E/S/H/L	125											1.4	1.6	1.8	2	T	T	T	T	T	T	T	
	100											1.25	1.4	1.6	1.8	2	2.4	2.8	3.8	4	5	T	T
	125											1.4	1.6	1.8	2	2.4	2.8	3.8	4	5	T	T	
	150												1.6	1.8	2	2.4	2.8	3.8	4	5	T	T	
	160													1.6	1.8	2	2.4	2.8	3.8	4	5	T	T
	175														2.4	2.8	3.8	4	5	T	T		
	200															2.4	2.8	3.8	4	5	T	T	
	225																2.8	3.8	4	5	T	T	
	250																	3.8	4	5	T	T	
	250																		4	5	5.6	6.4	
HGM400 E/S/H/L	300																		4	5	5.6	6.4	
	350																		5	5.6	6.4		
HGM630 E/S/H/L HGM800 S/H/L	400																		5	5.6	6.4		
	500																			5.6	6.4		
	630																				6.4		
	700																						
	800																						

※ * F type is for overseas sales.

Technical Data (HGP)

Discrimination Table

Ue < AC 460 V

Upstream : HGP50D ~ HGP800

Downstream : HGP50D ~ HGP800

Model	Trip Unit	HGP160D F*/S/H/X													
		Thermal Magnetic													
		Rated Current (A)	16	20	25	32	40	50	63	75	80	100	125	150	160
HGP50D		16							0.5	0.6	0.64	0.8	1	1.25	1.25
F*/S/H/X		20							0.5	0.6	0.64	0.8	1	1.25	1.25
HGP125D		25							0.5	0.6	0.64	0.8	1	1.25	1.25
F*/S/H/X		32							0.5	0.6	0.64	0.8	1	1.25	1.25
HGP160D		40									0.64	0.8	1	1.25	1.25
F*/S/H/X		50									0.64	0.8	1	1.25	1.25
HGP250		63										0.8	1	1.25	1.25
F*/S/H/X		75											1	1.25	1.25
HGP400		80											1	1.25	1.25
F*/S/H/X		100												1.25	
HGP630		125													
F*/S/H/X		150													
HGP800		160													
F*/S/H/X		100													
		125													
		150													
		160													
		100													
		125													
		150													
		160													
		175													
		200													
		225													
		250													
		300													
		350													
		400													
		500													
		630													
		700													
		800													

T Total Discrimination, Up to the Breaking Capacity of the Downstream Circuit Breaker

4 Discrimination Limit = 4 kA

No Discrimination

※ * F type is for overseas sales.

Upstream : HGP50D ~ HGP800

Downstream : HGP50D ~ HGP800

Model	Trip Unit	HGP250 F*/S/H/X															HGP400 F*/S/H/X			HGP630 F*/S/H/X				
		Thermal Magnetic & Electronic																						
	Rated Current (A)	40	50	63	75	80	100	125	150	160	175	200	225	250	300	350	400	500	630	700	800			
HGP50D F*/S/H/X	16			0.5	0.6	0.64	0.8	1	1.25	36	36	36	36	T	T	T	T	T	T	T	T			
	20			0.5	0.6	0.64	0.8	1	1.25	1.25	36	36	36	T	T	T	T	T	T	T	T			
	25			0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	36	36	T	T	T	T	T	T	T	T			
	32			0.5	0.6	0.64	0.8	1	1.25	1.25	1.4	36	36	T	T	T	T	T	T	T	T			
	40					0.64	0.8	1	1.25	1.25	1.4	36	36	T	T	T	T	T	T	T	T			
	50						0.64	0.8	1	1.25	1.25	1.4	36	36	T	T	T	T	T	T	T	T		
	63							0.8	1	1.25	1.25	1.4	36	36	T	T	T	T	T	T	T	T		
	75								1	1.25	1.25	1.4	36	36	T	T	T	T	T	T	T	T		
	80									1	1.25	1.25	1.4	36	36	T	T	T	T	T	T	T	T	
	100										1.25	1.4	1.6	36	36	T	T	T	T	T	T	T	T	
	125											1.6	1.8	36	T	T	T	T	T	T	T	T	T	
	150												1.8	2	T	T	T	T	T	T	T	T	T	
	160													2	T	T	T	T	T	T	T	T	T	
HGP250 F*/S/H/X	40					0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	36	36	36	T	T	T	T	T		
	50						0.64	0.8	1	1.25	1.25	1.4	1.6	1.8	2	36	36	36	T	T	T	T	T	
	63							0.8	1	1.25	1.25	1.4	1.6	1.8	2	36	36	36	T	T	T	T	T	
	75								1	1.25	1.25	1.4	1.6	1.8	2	36	36	36	T	T	T	T	T	
	80									1	1.25	1.25	1.4	1.6	1.8	2	36	36	36	T	T	T	T	T
	100										1.25	1.4	1.6	36	36	T	T	T	T	T	T	T	T	
	125											1.6	1.8	36	T	T	T	T	T	T	T	T	T	
	150												1.8	2	T	T	T	T	T	T	T	T	T	
	160													2	T	T	T	T	T	T	T	T	T	
	175														2.4	2.8	36	36	36	T	T	T	T	
	200															2.4	2.8	3.8	36	36	T	T	T	
	225																2.8	3.8	36	36	T	T	T	
	250																	3.8	4	36	T	T	T	
HGP400 F*/S/H/X	300																		4	5	36	36		
	350																			5	36	36		
	400																			5	5.6	36		
	500																				5.6	6.4		
HGP630 F*/S/H/X	630																						6.4	
	700																							
	800																							

T Total Discrimination, Up to the Breaking Capacity of the Downstream Circuit Breaker

4 Discrimination Limit = 4 kA

No Discrimination

※ * F type is for overseas sales.


Technical Data (HGP)

Type 2 Coordination (IEC 60947-4-1)

AC 440 V

Performance : Ue = 440 V

Circuit breakers	F *	S	H
HGP100/250	36	65	85
HGP400/630	36	65	85
HGP800	36	65	85



Motor	Circuit Breakers			Contactors		Thermal o/l relays		
	P (kW)	I (A) 440V	Ie Max (A)	Type	Rating (A)	Ii (A)	Type	
0.37	1.1	1.6	1.6	HGP100	2.5	32.5	HGT18 ¹⁾	0.8 ~ 1.2
0.55	1.4	1.6	1.6	HGP100	2.5	32.5	HGT18 ¹⁾	1.1 ~ 1.6
0.75	1.7	2.5 ²⁾	2.5 ²⁾	HGP100	2.5	32.5	HGT18 ¹⁾	1.5 ~ 2.1 ²⁾
1.1	2.4	2.5	2.5	HGP100	3.2	41.6	HGT18 ¹⁾	2 ~ 3
1.5	3.1	4	4	HGP100	6.3	81.9	HGT18 ^{1), 4)}	2.8 ~ 4.2
2.2	4.5	6	6	HGP100	6.3	81.9	HGT18 ^{1), 4)}	4 ~ 6
3	5.8	6	6	HGP100	6.3	81.9	HGT18 ^{1), 4)}	5.6 ~ 8
4	8	8	8	HGP100	12.5	163	HGT65 ^{1), 4)}	6 ~ 9
5.5	10.5	12.5 ³⁾	12.5 ³⁾	HGP100	12.5	163	HGT65 ^{1), 4)}	8 ~ 12 ³⁾
7.5	13.7	18	18	HGP100	32	416	HGT65 ¹⁾	12 ~ 18
10	19	25	25	HGP100	32	416	HGT100 ¹⁾	17 ~ 25
11	20	25	25	HGP100	32	320	HGT100 ¹⁾	17 ~ 25
15	26.5	32	32	HGP100	50	650	HGT100	22 ~ 32
18.5	33	40	40	HGP100	50	650	HGT100	28 ~ 40
22	39	40	40	HGP100	50	650	HGT100	34 ~ 50
30	52	63	63	HGP100	100	1300	HGT150	48 ~ 80
37	63	63	63	HGP100	100	1300	HGT150	48 ~ 80
45	76	80	80	HGP250	125	1250	HGT150	48 ~ 80
55	90	100	100	HGP250	160	1600	HGT150	69 ~ 115
75	125	150	150	HGP250	200	2000	HGT150	90 ~ 150
90	140	150	150	HGP250	200	2000	HGT150	111 ~ 185
110	178	185	185	HGP250	250	2500	HGT265	135 ~ 225
132	210	265	265	HGP400	350	3500	HGT265	180 ~ 300
160	256	265	265	HGP400	350	3500	HGT265	180 ~ 300
200	310	320	320	HGP630	400	4000	HGT500	240 ~ 400
220	353	400	400	HGP630	630	6300	HGT500	300 ~ 500
250	400	500	500	HGP630	700	7000	HGT500	300 ~ 500
		500		HGP800	700	7000	HGT800	378 ~ 630
300	460	630	630	HGP800	800	8000	HGT800	378 ~ 630
335	540	630	630	HGP800	800	8000	HGT800	378 ~ 630
375	575	630	630	HGP800	800	8000	HGT800	378 ~ 630

※ 1) Iq < 50 kA

2) TOR Thermal Maximum Rating 2.1 A

3) TOR Thermal Maximum Rating 12 A

4) Type 1 Only for Thermal Relay

* F type is for overseas sales.

Installation


Insulation Distance (Safety Clearance)

For safety, insulation distance must be secured at installation. In case of installing a circuit breaker, safety clearances must be secured between breakers or between the circuit breaker and panel, bus bar and other adjacent devices. When the circuit breaker interrupts a short circuit, high temperature ionized gas is generated and the gas is discharged through the discharge outlet from the circuit breaker. As this gas can cause short-circuit accidents and grounding accidents, sufficient insulation distance is required between the circuit breaker and the panel.


※ In case insulation barrier is not installed between the circuit breaker terminals, secondary short-circuit accident may occur so it must be used.

The insulation barrier must be installed towards the both directions of the circuit breaker's line / load indication part.


Separation distance in case the circuit breaker is installed side by side




Up/down/left/right distance in case of metallic panel



Front/back distance in case of metallic panel



Distance with circuit breaker in case the live part is exposed



※ In case of using the minimum separation distance(A1 = 0), terminal cover and phase to phase barrier must be assembled between the product. And pay attention to the tolerances of the enclosure dimensions.

※ If the distance between the live parts is less than 60 mm, the exposed part must be insulated.

HGP Type's Minimum Insulation Distance

Type	Minimum Clearance (mm)													
	460 V						240 V							
	A1	B1	B2	B3	C1	C2	D1	A1	B1	B2	B3	C1	C2	D1
HGP50D F*/S	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP50D H/X	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP125D F*/S	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP125D H/X	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP160D F*/S	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP160D H/X	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP100 F*/S	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP100 H/X	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP160 F*/S	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP160 H/X	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP250 F*/S	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP250 H/X	0	10	50	50	0	8	350	0/50	10	50	50	0	8	350
HGP400 F*/S	0	40	116	116	0	8	350	0/50	15	116	116	0	8	350
HGP400 H/X	0	40	116	116	0	8	350	0/50	15	116	116	0	8	350
HGP630 F*/S	0	40	116	116	0	8	350	0/50	15	116	116	0	8	350
HGP630 H/X	0	40	116	116	0	8	350	0/50	15	116	116	0	8	350
HGP800 F*/S	0	45	115	115	0	8	350	0/50	20	115	115	0	8	350
HGP800 H/X	0	45	115	115	0	8	350	0/50	20	115	115	0	8	350


※ * F type is for overseas sales.

Technical Data (HGP)

Installation


Installation Angle

The HGP Type of circuit breakers can be installed vertically or horizontally without changing any characteristics and as for the detailed installation direction, please refer to the figure below.



Direction of Power Supply


As for the HGP Type circuit breaker, the breaking power of circuit breaker does not drop even if power is supplied to the load side. So, power can be supplied to any direction regardless of the line side/load side for use. With regards to the use in reverse connection, HGP got DEKRA Certificate under IEC 60947-2.



Standard Configuration


HGP Type

HGP50D, HGP125D, HGP160D, HGP100, HGP160, HGP250



MCCB	Part			
HGP50D, HGP125D, HGP160D	3P	4 EA (M4×L85)	6 EA (PH Screw P·S/W M8×L18)	4 EA
	4P	5 EA (M4×L85)	8 EA (PH Screw P·S/W M8×L18)	6 EA
HGP100, HGP160, HGP250	3P	4 EA (M4×L85)	6 EA (Hex Socket P·S/W M8×L20)	4 EA
	4P	6 EA (M4×L85)	8 EA (Hex Socket P·S/W M8×L20)	6 EA

HGP400, HGP630, HGP800




MCCB	Part			
HGP400, HGP630	3P	4 EA (M5×L98)	6 EA (Hex Socket P·S/W M10×L30)	4 EA
	4P	5 EA (M5×L98)	8 EA (Hex Socket P·S/W M10×L30)	6 EA
HGP800	3P	4 EA (M6×L110)	6 EA (Hex Socket P·S/W M12×L35)	4 EA
	4P	6 EA (M6×L110)	8 EA (Hex Socket P·S/W M12×L35)	6 EA

Technical Data (HGP)


MCCB Assembly and Terminal Mounting Specification

HGP Type









HGP Type circuit breaker can be mounted directly on the panel by using a screw. In case there is a bus bar or terminal at the back of the panel, insulation distance requires your attention. The wire and bus bar have to be wired according to the terminal part's specification for power supply of circuit breaker and fastened according to the specified tightening torque.



Panel Installation




Terminal Connection

No	Type	Panel Mounting		Connection Terminal	
		Screw Specification	Terminal Connection Method and Dimensions (mm)	Conductor Processing	Tightening Torque
1	HGP50D HGP125D HGP160D	M4 : 13 kgf.cm			M8 : 50 ~ 70 kgf·cm
2	HGP100 HGP160 HGP250	M4 : 13 kgf.cm			M8 : 80 ~ 130 kgf·cm
3	HGP400 HGP630	M5 : 28.5 kgf·cm			M10 : 140 ~ 270 kgf.cm
4	HGP800	M6 : 45 kgf.cm			M12 : 350 ~ 470 kgf.cm


Operation Characteristic Curve

HGM/HGE100 (16 ~ 32 A)

• HGM/HGE30, 50E/S, 60, 100




Ambient Temperature Derating Curve




HGM/HGE100 (40 ~ 100 A)

• HGM/HGE50E/S, 60, 100





Ambient Temperature Derating Curve



Operation Characteristic Curve



HGM/HGE125 (16 ~ 32 A)

• HGM/HGE50H/L, 125




HGM/HGE125 (40 ~ 125 A)

• HGM/HGE50H/L, 125




HGM/HGE250 (100 ~ 250 A)


• HGM/HGE160, 250




Ambient Temperature Derating Curve

**HGM400**

• HGM400





Ambient Temperature Derating Curve



Operation Characteristic Curve



HGM800 (500 ~ 800 A)

• HGM630, 800




HGE400

• HGE400




HGE800 (500 ~ 800 A)

• HGE630, 800




Ambient Temperature Derating Curve



Current & Energy-Limiting Characteristic Curve


Current-Limiting Characteristic Curve

• Based on 400/460 V



Energy-Limiting Characteristic Curve



• Based on 400/460 V



Operation Characteristic Curve (HGP Thermal Magnetic Type)



HGP160D (16 ~ 32 A)

• HGP50D, 125D




HGP160D (40 ~ 160 A)

• HGP50D, 125D, 160D




HGP250

• HGP100, 160, 250





Ambient Temperature Derating Curve



Operation Characteristic Curve (HGP Thermal Magnetic Type)



HGP630 (300 ~ 630 A)

• HGP400, 630



HGP800 (700 ~ 800 A)


• HGP800



Operation Characteristic Curve (HGP for Motor Protection)


HGP100 (2.5 ~ 100 A)

• HGP100



HGP250 (125 ~ 250 A)


• HGP250



Operation Characteristic Curve (HGP for Motor Protection)


HGP630 (300 ~ 630 A)

• HGP400, 630



HGP800 (700 ~ 800 A)

• HGP800




Operation Characteristic Curve (HGP for Electronic)

ETU-N Type

• HGP100, 160, 250, 400, 630, 800

- Long-Time Protection [L]
- Short-Time Protection [S]
- Instantaneous Protection [I]




Operation Characteristic Curve (HGP for Electronic)

ETU-D/A/E Type (L,S,I)

• HGP100, 160, 250, 400, 630, 800


- Long-Time Protection [L]
- Short-Time Protection [S]
- Instantaneous Protection [I]



ETU-D/A/E Type (G)

• HGP100, 160, 250, 400, 630, 800


- Ground-Fault Protection [G]



Current & Energy-Limiting Characteristic Curve (HGP)


Current-Limiting Characteristic Curve

• Based on 400/460 V




Energy-Limiting Characteristic Curve

• Based on 400/460 V




Current-Limiting Characteristic Curve

Based on 480/500 V

**Energy-Limiting Characteristic Curve**

Based on 480/500 V




Dimensions

Front Connection HGM100

• HGM30, 50E/S, 60, 100


External Dimension

Unit : mm




※ The insulation barrier at the line side is provided as default.

Panel Installation Dimension



Detail Drawing of Terminal Part/Connecting Conductor




100 AF


Specification of Mounting Screw : M4 x L70 P/W

Specification of Terminal Mounting Screw : (Below 50 A) M5 x L15 S/W
(Above 50 A) M8 x L15 S/W P/W

Dimension of Panel Cover Cutting - Handle Exposure



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure


※ When installing the product in close contact, please consider tolerances for external dimensions.

Front Connection HGM125

• HGM50H/L, 125


External Dimension

Unit : mm




※ The insulation barrier at the line side is provided as default.

Panel Installation Dimension




Detail Drawing of Terminal Part/Connecting Conductor




125 AF

Specification of Mounting Screw : M4 x L70 P/W
Specification of Terminal Mounting Screw : M8 x L15 S/W P/W


Dimension of Panel Cover Cutting - Handle Exposure



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Front Connection HGM250

• HGM160, 250


External Dimension

Unit : mm




※ The insulation barrier at the line side is provided as default.

Panel Installation Dimension



Detail Drawing of Terminal Part/Connecting Conductor




250 AF


Specification of Mounting Screw : M4 x L70 P/W

Specification of Terminal Mounting Screw : Hex Socket Bolt M8 x L18 W/W


Dimension of Panel Cover Cutting - Handle Exposure



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure




※ When installing the product in close contact, please consider tolerances for external dimensions.

Front Connection HGM400


• HGM400

External Dimension




※ The insulation barrier at the line side is provided as default.


Panel Installation Dimension




Detail Drawing of Terminal Part/Connecting Conductor




Dimension of Panel Cover Cutting - Handle Exposure



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Front Connection HGM800

• HGM630, 800


External Dimension

Unit : mm




※ The insulation barrier at the line side is provided as default.


Panel Installation Dimension




Detail Drawing of Terminal Part/Connecting Conductor




Dimension of Panel Cover Cutting - Handle Exposure



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure




※ When installing the product in close contact, please consider tolerances for external dimensions.

Front Connection HGE100

• HGE30, 50E/S, 60, 100

External Dimension


Unit : mm





※ The insulation barrier at the line side is provided as default.

Panel Installation Dimension



Detail Drawing of Terminal Part/Connecting Conductor



Dimension of Panel Cover Cutting - Handle Exposure



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Front Connection HGE125

• HGE50H/L, 125

External Dimension


Unit : mm




※ The insulation barrier at the line side is provided as default.

Panel Installation Dimension


Detail Drawing of Terminal Part/Connecting Conductor



Dimension of Panel Cover Cutting - Handle Exposure



Dimension of Panel Cover Cutting - Handle/Test Button Exposure




※ When installing the product in close contact, please consider tolerances for external dimensions.

Front Connection HGE250

• HGE160, 250

External Dimension


Unit : mm





※ The insulation barrier at the line side is provided as default.

Panel Installation Dimension



Detail Drawing of Terminal Part/Connecting Conductor



Dimension of Panel Cover Cutting - Handle Exposure



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Front Connection HGE400

• HGE400

External Dimension


Unit : mm




※ The insulation barrier at the line side is provided as standard product.

Panel Installation Dimension

Detail Drawing of Terminal Part/Connecting Conductor



Dimension of Panel Cover Cutting




※ When installing the product in close contact, please consider tolerances for external dimensions.

Front Connection HGE800

• HGE630, 800

External Dimension


Unit : mm




※ The insulation barrier at the line side is provided as standard product.

Panel Installation Dimension

Detail Drawing of Terminal Part/Connecting Conductor



Dimension of Panel Cover Cutting



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Front Connection HGP160D


• HGP50D, 125D, 160D

External Dimension


Unit: mm



Panel Installation Dimension




Detail Drawing of Terminal Part/Connecting Conductor




Dimension of Panel Cover Cutting


Handle/Test Button Exposure



Handle/Trip Unit Exposure



3P




4P

Front Connection HGP250

• HGP100, 160, 250


External Dimension

Unit : mm



Panel Installation Dimension


Detail Drawing of Terminal Part/Connecting Conductor





※ Screw Applied : M4×L85 S/W (For Circuit Breaker Mounting),
M8×L18 S/W P/W (For Terminal Mounting)

Dimension of Panel Cover Cutting

Handle/Test Button Exposure



Handle/Trip Unit Exposure



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Front Connection HGP630

• HGP400, 630


External Dimension

Unit : mm




Panel Installation Dimension


Detail Drawing of Terminal Part/Connecting Conductor



Terminal Part




Connecting Conductor





Dimension of Panel Cover Cutting

Handle/Test Button Exposure



Handle/Trip Unit Exposure




Front Connection HGP800


• HGP800

External Dimension


Unit : mm



Panel Installation Dimension




Detail Drawing of Terminal Part/Connecting Conductor





Dimension of Panel Cover Cutting

Handle/Test Button Exposure



Handle/Trip Unit Exposure




※ When installing the product in close contact, please consider tolerances for external dimensions.

Dimensions

Rear Connection (Flat Type) HGM100


• HGM30, 50E/S, 60, 100

External Dimension




Unit: mm


Panel Installation Dimension



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure







※ When assembling the RCT, remove the back barrier beforehand.

※ When installing the product in close contact, please consider tolerances for external dimensions.

Rear Connection (Flat Type) HGM125

• HGM50H/L, 125

External Dimension**Panel Installation Dimension****Dimension of Panel Cover Cutting - Handle/Test Button Exposure****Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure**

※ When assembling the RCT, remove the back barrier beforehand.


※ When installing the product in close contact, please consider tolerances for external dimensions.

Dimensions

Rear Connection (Flat Type) HGM250


• HGM160, 250

External Dimension




Unit : mm


Panel Installation Dimension



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure




※ When assembling the RCT, remove the back barrier beforehand.

※ When installing the product in close contact, please consider tolerances for external dimensions.

Rear Connection (Flat Type) HGM400


• HGM400

External Dimension




Unit : mm


Panel Installation Dimension



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure



※ When assembling the RCT, remove the back barrier beforehand.

※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Rear Connection (Flat Type) HGM800


• HGM630, 800

External Dimension


Unit : mm




Panel Installation Dimension



Dimension of Panel Cover Cutting - Handle/Test Button Exposure



Dimension of Panel Cover Cutting - Handle/Trip Unit Exposure



※ When assembling the RCT, remove the back barrier beforehand.


※ When installing the product in close contact, please consider tolerances for external dimensions.

Rear Connection (Rear Type) HGP160D


• HGP50D, 125D, 160D

External Dimension

Unit : mm




Panel Installation Dimension




Dimension of Panel Cover Cutting


Handle/Test Button Exposure



Handle/Trip Unit Exposure



3P



4P


Dimensions

Rear Connection (Rear Type) HGP250


• HGP250

External Dimension

Unit: mm




Panel Installation Dimension





Dimension of Panel Cover Cutting

Handle/Test Button Exposure



Handle/Trip Unit Exposure




Rear Connection (Rear Type) HGP630

• HGP400, 630


External Dimension

Unit : mm




Panel Installation Dimension

3P




4P





Dimension of Panel Cover Cutting

Handle/Test Button Exposure



Handle/Trip Unit Exposure




Dimensions

Rear Connection (Rear Type) HGP800


• HGP800

External Dimension

Unit: mm




Panel Installation Dimension




Dimension of Panel Cover Cutting


Handle/Test Button Exposure



Handle/Trip Unit Exposure



3P




Plug-in Type HGM100

• HGM30, 50E/S, 60, 100


External Dimension (TDM Type)

Unit : mm




Panel Installation Dimension and Cover Cutting Dimension


Detailed Drawing of Connection



Mounting Drawing



Process Criterion of
Connecting Conductor



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Plug-in Type HGM100

• HGM30, 50E/S, 60, 100


External Dimension (TDA D Type)

Unit : mm




Panel Installation Dimension and Cover Cutting Dimension


Mounting Drawing



Mounting Drawing



Process Criterion of Connecting Conductor




Plug-in Type HGM100

• HGM30, 50E/S, 60, 100


External Dimension (TDA S Type)

Unit : mm



Panel Installation Dimension and Cover Cutting Dimension

Mounting Drawing



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Plug-in Type HGM100

• HGM30, 50E/S, 60, 100


External Dimension (TDF Type)

Unit: mm




Panel Installation Dimension and Cover Cutting Dimension

Mounting Drawing



Process Criterion of
Connecting Conductor




Plug-in Type HGM125

• HGM50H/L, 125


External Dimension (TDM Type)

Unit : mm




Panel Installation Dimension and Cover Cutting Dimension


Detailed Drawing of Connection



Mounting Drawing



Process Criterion of Connecting Conductor



Dimensions

※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Plug-in Type HGM125

• HGM50H/L, 125


External Dimension (TDA D Type)

Unit : mm



Panel Installation Dimension and Cover Cutting Dimension

Mounting Drawing




※ When installing the product in close contact, please consider tolerances for external dimensions.

Plug-in Type HGM125

• HGM50H/L, 125


External Dimension (TDA S Type)

Unit : mm




Panel Installation Dimension and Cover Cutting Dimension

Mounting Drawing



Process Criterion of Connecting Conductor



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Plug-in Type HGM125

• HGM50H/L, 125

External Dimension (TDF Type)


Unit: mm



Panel Installation Dimension and Cover Cutting Dimension

Mounting Drawing

Process Criterion of
Connecting Conductor




※ When installing the product in close contact, please consider tolerances for external dimensions.

Plug-in Type HGM250

• HGM160, 250


External Dimension (TDM Type)

Unit : mm




Panel Installation Dimension and Cover Cutting Dimension


Mounting Drawing



Dimension of Front Cover Cutting



Process Criterion of
Connecting Conductor



Dimensions

※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Plug-in Type HGM400

• HGM400


External Dimension (TDM Type)

Unit : mm




Panel Installation Dimension and Cover Cutting Dimension


Mounting Drawing



Dimension of Front Cover Cutting



Process Criterion of
Connecting Conductor




Plug-in Type HGM800

• HGM630, 800


External Dimension (TDM Type)

Unit : mm




Panel Installation Dimension and Cover Cutting Dimension


Mounting Drawing



Dimension of Front Cover Cutting



Process Criterion of
Connecting Conductor



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Plug-in Type HGP160D

• HGP50D, 125D, 160D


External Dimension

Unit: mm



Panel Installation Dimension and TDM Cover Cutting Dimension

Dimensions




※ When installing the product in close contact, please consider tolerances for external dimensions.

Plug-in Type HGP250

• HGP100, 160, 250


External Dimension

Unit : mm




Panel Installation Dimension and TDM Cover Cutting Dimension


Mounting Drawing



Dimension of Front Cover Cutting



Process Criterion of
Connecting Conductor



Dimensions

※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Plug-in Type HGP630

• HGP400, 630


External Dimension

Unit : mm



Panel Installation Dimension and TDM Cover Cutting Dimension

Dimensions




※ When installing the product in close contact, please consider tolerances for external dimensions.

Plug-in Type HGP800

• HGP800


External Dimension

Unit : mm




Panel Installation Dimension and TDM Cover Cutting Dimension


Mounting Drawing



Dimension of Front Cover Cutting



Process Criterion of Connecting Conductor



Dimensions

※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

External Rotary Handle HGM100

• HGM30, 50E/S, 60, 100


External Dimension - Front Contact Type

Unit: mm




※ 1) Note that the LOCK PLATE may need to be positioned for combined operation with the handle.

External Dimension – Extension Type



Panel Installation Dimension

Dimensions




※ When installing the product in close contact, please consider tolerances for external dimensions.

External Rotary Handle HGM125

• HGM50H/L, 125


External Dimension - Front Contact Type

Unit : mm




※ 1) Note that the LOCK PLATE may need to be positioned for combined operation with the handle.

External Dimension – Extension Type



Panel Installation Dimension



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

External Rotary Handle HGM250

• HGM160, 250


External Dimension - Front Contact Type

Unit : mm




※ 1) Note that the LOCK PLATE may need to be positioned for combined operation with the handle.

External Dimension – Extension Type



Panel Installation Dimension

Dimensions




※ When installing the product in close contact, please consider tolerances for external dimensions.

External Rotary Handle HGM400


• HGM400

External Dimension - Front Contact Type

Unit : mm




External Dimension – Extension Type




Panel Installation Dimension

Front Contact Type



Extension Type



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

External Rotary Handle HGM800


• HGM630, 800

External Dimension - Front Contact Type


Unit : mm



External Dimension – Extension Type



Panel Installation Dimension




※ When installing the product in close contact, please consider tolerances for external dimensions.

External Rotary Handle HGP160D

• HGP50D, 125D, 160D


External Dimension - Front Contact Type

Unit : mm




※ 1) Note that the LOCK PLATE may need to be positioned for combined operation with the handle.

External Dimension – Extension Type



Panel Installation Dimension



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

External Rotary Handle HGP250

• HGP100, 160, 250


External Dimension - Front Contact Type

Unit : mm




※ 1) Note that the LOCK PLATE may need to be positioned for combined operation with the handle.

External Dimension – Extension Type



Panel Installation Dimension




※ When installing the product in close contact, please consider tolerances for external dimensions.

External Rotary Handle HGP630


• HGP400, 630

External Dimension - Front Contact Type



Unit : mm



External Dimension – Extension Type



Panel Installation Dimension



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

External Rotary Handle HGP800


• HGP800

External Dimension - Front Contact Type


Unit : mm



External Dimension – Extension Type



Panel Installation Dimension






※ When installing the product in close contact, please consider tolerances for external dimensions.

Mechanical Interlock HGM100

• HGM30, 50E/S, 60, 100

External Dimension

Unit : mm

**Panel Installation Dimension****Dimension of Panel Cover Cutting**

※ 1) Padlock not included.

※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Mechanical Interlock HGM125


• HGM50H/L, 125

External Dimension


Unit: mm



Panel Installation Dimension



Dimension of Panel Cover Cutting




Mechanical Interlock HGM250

• HGM160, 250


External Dimension

Unit : mm




Panel Installation Dimension

2/3P




4P (RSTN/NRST)




Dimension of Panel Cover Cutting

2/3P



4P (RSTN/NRST)



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Mechanical Interlock HGM400

• HGM400

External Dimension


Unit : mm



Panel Installation Dimension

2/3P


4P (RSTN/NRST)



Dimension of Panel Cover Cutting

2/3P

4P (RSTN/NRST)




Mechanical Interlock HGM800

• HGM630, 800

External Dimension


Unit : mm



Panel Installation Dimension

2/3P


4P (RSTN/NRST)



Dimension of Panel Cover Cutting

2/3P

4P (RSTN/NRST)



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Mechanical Interlock HGP160D

• HGP50D, 125D, 160D


External Dimension

Unit: mm




Panel Installation Dimension

3P




4P




Dimension of Panel Cover Cutting

3P



4P




Mechanical Interlock HGP250


• HGP100, 160, 250

External Dimension


Unit : mm



Panel Installation Dimension



Dimension of Panel Cover Cutting



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Mechanical Interlock HGP630


• HGP400, 630

External Dimension


Unit: mm



Panel Installation Dimension



Dimension of Panel Cover Cutting




Mechanical Interlock HGP800

• HGP800


External Dimension

Unit : mm




Panel Installation Dimension

3P




4P




Dimension of Panel Cover Cutting

3P



4P




※ When installing the product in close contact, please consider tolerances for external dimensions.

Dimensions


Terminal Cover HGM100

• HGM30, 50E/S, 60, 100



Long Type



Short Type




Unit: mm




Terminal Cover HGM125

• HGM50H/L, 125



Long Type



Short Type




Unit: mm




Terminal Cover HGM250

• HGM160, 250

Long Type



Short Type




Unit : mm


Terminal Cover HGM400

• HGM400

Long Type



Short Type



Unit : mm

Dimensions


※ When installing the product in close contact, please consider tolerances for external dimensions.

Dimensions


Terminal Cover HGM800

• HGM630, 800



Long Type



Short Type





Unit : mm





Terminal Cover HDB100 (for Distribution Panel)

• HDB/HDG30, 50, 100 (for Distribution Panel)

Short Type 2P



Short Type 3P




단위 : mm


Terminal Cover HGP50D, 125D, 160D

• HGP50D, 125D, 160D



Long Type 3P/4P



Short Type 3P




Unit : mm


**Terminal Cover HGP250**

• HGP100, 160, 250



Long Type 3P/4P



Short Type 3P



Unit : mm





※ When installing the product in close contact, please consider tolerances for external dimensions.

Dimensions



Terminal Cover HGP400, 630

• HGP400, 630

Long Type 3P/4P



Short Type 3P





Unit: mm



Terminal Cover HGP800

• HGP800

Long Type 3P/4P



Short Type 3P




Unit: mm


Motor Operator

HGM30, 50E/S, 60, 100


Unit : mm



HGM50H/L, 125



HGM160, 250




※ When installing the product in close contact, please consider tolerances for external dimensions.

Dimensions


Motor Operator

HGM400

Unit: mm







HGM630, 800



※ When installing the product in close contact, please consider tolerances for external dimensions.

HGP50D, 125D, 160D

Unit : mm

**HGP100, 160, 250****HGP400, 630****HGP800**


※ When installing the product in close contact, please consider tolerances for external dimensions.

Dimensions


LUG Terminal

HGM30, 50E/S, 60, 100


Unit: mm



HGM50H/L, 125



HGM160, 250




※ When using CTB, in case the Line/Load Insulation Barrier is not mounted, insulation tube or insulation tape does not provide complete insulation between bare conductors which may cause secondary short-circuit accidents so it must be used.


※ When installing the product in close contact, please consider tolerances for external dimensions.

HGM400

Unit : mm



HGM630, 800



Dimensions


※ When using CTB, in case the Line/Load Insulation Barrier is not mounted, insulation tube or insulation tape does not provide complete insulation between bare conductors which may cause secondary short-circuit accidents so it must be used.

※ When installing the product in close contact, please consider tolerances for external dimensions.

Dimensions


LUG Terminal

HGP50D, 125D, 160D




Unit: mm

HGP100, 160, 250




HGP400, 630



Dimensions

HGP800




※ When installing the product in close contact, please consider tolerances for external dimensions.

Series Busbar(SBB) HGP250


• HGP100, 160, 250

External Dimension


Unit : mm



Detail Drawing of Terminal Part



Detail Drawing of SBB




Series Busbar(SBB) HGP630


• HGP400, 630

External Dimension


Unit : mm



Detail Drawing of Terminal Part



Detail Drawing of SBB



※ When installing the product in close contact, please consider tolerances for external dimensions.


Dimensions

Series Busbar(SBB) HGP800


• HGP800

External Dimension


Unit: mm



Detail Drawing of Terminal Part



Detail Drawing of SBB




DIN Rail Adaptor

• HGM100

Dimension of DIN Rail Mounting Hole

Unit: mm



※ When assembling the DRA, remove the back barrier beforehand.
 ※ When installing the product in close contact, please consider tolerances for external dimensions.

Order Code

HGM Type of Molded Case Circuit Breaker, Earth Leakage Circuit Breaker

HGM		50		E		3P		T4		S	
Model Name		Frame Size		Short-Circuit Breaking Category Code		No. of Poles (Category per Circuit Breaker)		Product Category		Connection Method	
HGM	Molded Case Circuit Breaker	30	32 AF	E	E Type	General Type of MCCB/ELCB		MCCB : Ambient Temperature		S	Front Connection
		50	50 AF	S	S Type					BS ³⁾	Terminal Bus Bar (Straight Type)
HGE	Earth Leakage Circuit Breaker	60	63 AF	H	H Type	2P	2 Pole	T4	40/45 °C	BE ⁴⁾	Terminal Bus Bar (Spreader Type)
		100	100 AF	L	L Type	3P	3 Pole	T5	50 °C	P	Plug-in
		125	125 AF	NA	Switch-Disconnector	4P	4 Pole (RSTN)	ELCB : Adjustable Residual Current		F	Line Side : Plug-in Load Side : Front Connection
		160	160 AF			4PN	4 Pole (NRST)	G4	30 mA	X	PC/CBM Not Attached
		250	250 AF			ZCT Embedded Type of MCCB		G5 ¹⁾	100 mA		
		400	400 AF			2Z	2 Pole	Instantaneous Circuit Breaker			
		630	630 AF			3Z	3 Pole	MO ²⁾	Instantaneous Switch-Disconnector		
		800	800 AF			4Z	4 Pole	DS	Switch-Disconnector		

※ 1) In case of 100/300/500/1,000 mA adjustable and time delay type, place order as 100 mA.

2) As for instantaneous products, only 3P can be ordered.

3) Only for 400 ~ 800 AF.

4) Only for 400 AF.

5) Rated current of instantaneous products : Above 40 A

00	00	C	00016	F	
Signal Device (AUX/ALT)		Trip Device Characteristics (Applicable To MCCB Only)			
00	Not Attached	HGM/HGE 30 ~ 250 AF	C	For Protecting Overload Short-Circuit	
10	AUX 1C	00 Not Attached		- Thermal Fixed/ Instantaneous Fixed	
20	AUX 2C	S1 SHT AC 100 - 120 V			
01	ALT 1C	S2 SHT AC 200 - 250 V			
11	AUX 1C + ALT 1C	S3 -			
21	AUX 2C + ALT 1C	S4 SHT AC 380 - 480 V			
		S5 SHT DC 24 V	00016	Thermal Adjustable/ Instantaneous Fixed	
		S6 SHT DC 100 - 120 V	00020	Instantaneous	
		S7 SHT DC 48 V			
		S8 SHT DC 60 V			
		S9 SHT DC 125 V			
		U1 UVT AC 100 - 120 V	00800		
		U2 UVT AC 200 - 230 V			
		U3 UVT AC 380 - 415 V			
		U4 UVT AC 440 - 480 V			
		U5 UVT DC 24 V			
		U6 UVT DC 100 - 110 V			
		U7 UVT DC 48 V			
		HGM/HGE 400 ~ 800 AF			
		00 Not Attached			
		S1 SHT AC 100 - 120 V			
		S2 SHT AC 200 - 230 V			
		S3 SHT AC 380 - 415 V			
		S4 SHT AC 440 - 480 V			
		S5 SHT DC 24 V			
		S6 SHT DC 100 - 110 V			
		U1 UVT AC 100 - 120 V			
		U2 UVT AC 200 - 230 V			
		U3 UVT AC 380 - 415 V			
		U4 UVT AC 440 - 480 V			
		U5 UVT DC 24 V			
		U6 UVT DC 100 - 110 V			

Order Code

HGP Type of Molded Case Circuit Breaker / Switch Disconnector

HGP		250	X	-G	3P	T4	S	
		Model Name	Frame Size	Short-Circuit Breaking Category Code ¹⁾	Classification-250 AF	No. of Poles & Voltage	Product Category	Connection Method
HGP	Molded Case Circuit Breaker / Earth Leakage Circuit Breaker	50D	50 AF	AC	- Terminal Height (24-26 mm) ¹⁰⁾ - New Type Terminal Height (21.5 mm)	3P AC 3 pole	Molded Case Circuit Breaker	S Front Connection
		125D	125 AF	F ⁸⁾ 36 kA		4P AC 4 pole	T4 ⁹⁾ Ambient Temperature of 40 °C	BS ⁴⁾ Straight Type of Bus Bar Packaging
		160D	160 AF	S 65 ⁶⁾ /70 ⁷⁾ kA		D3 DC 3 pole	T5 Ambient Temperature of 50 °C	BE ¹¹⁾ Spreader Type of Bus Bar Packaging
		100	100 AF	H 85 kA		D4 DC 4 pole	Electronic ³⁾ Motor Protection	P Plug-in PC/CBM Attached
		160	160 AF	X 150 kA			EN Normal	F Line Side: Plug-in Load Side: Front Connection
		250	250 AF	NA Switch-Disconnector			ED Display	
		400	400 AF	DC			EA Ammeter	
		630	630 AF	F 10 kA			EE Energy Meter	
		800	800 AF	S 55 kA			MP For Motor Protection	
				H 85 kA			DS Switch-Disconnector	
				X 100 kA				

※ 1) Based on AC 440/460 V

2) Applicable to HGP100,160,250

3) 50D, 125D, 160D : Electronic type N/A

4) Applicable to both Line part / Load part, HGP400~800

5) Applicable to HGP400 ~ 800

6) HGP50D, 125D, 160D, 100, 160, 250 AF

7) HGP400, 630, 800 AF

8) F type is for overseas and ship.

9) For DC products, only T4 is applicable.

10) Discontinued March 2020

11) Applicable to both Line part / Load part, HGP400

12) For DC products

00	00	C	00016	F
Signal Device (AUX/ALT)		Trip Device (SHT/UVT)	Frequency	
00	Not Attached	S1	C	Rated Current
10	AUX 1C	S2	AC(50/60 Hz)	002.5 2.5 A
20	AUX 2C	S3	Z ¹²⁾	006.3 6.3 A
01	ALT 1C	S4	DC	00800 800 A
11	AUX 1C + ALT 1C	S5		
21	AUX 2C + ALT 1C	S6		
31 ⁵⁾	AUX 3C + ALT 1C	U1		
32 ⁵⁾	AUX 3C + ALT 2C	U2		
		U3		
		U4		
		U5		
		U6		
				For Protecting Overload Short-Circuit
				- Thermal Fixed/Instantaneous Fixed (MTM - FF)
				F Thermal Adjustable/Instantaneous Fixed (MTM - JF)
				H Thermal Adjustable/Instantaneous Adjustable (MTM - JJ)
				N Thermal Fixed/Instantaneous Fixed (MTM - FF) + 4P N Phase Protection
				FN Thermal Adjustable/Instantaneous Fixed (MTM - JF) + 4P N Phase Protection
				HN Thermal Adjustable/Instantaneous Adjustable (MTM - JJ) + 4P N Phase Protection
				Electronic
				- Not Applicable (ETU)
				Motor Protection
				- No Thermal/Instantaneous Adjustable (MCP - OJ)
				Switch-Disconnector
				- No Protection Function (DSU)

Order Code of Accessories

HGM/HGE Type of Accessory Unit

HGM/HGE30, 50E/S, 60, 100

Connection Method

		2 Pole	3 Pole	4 Pole
Plug-in	TDM (LINE/LOAD)	-	TDM 10GM P3	-
	TDM (LINE Only)	-	TDM 10GM F3	-
	TDF (LINE Only)	-	TDF 10GM 3	-
	TDA (1 row)	-	TDA 10GM S3	-
	TDA (2 rows)	TDA 10GM D2	TDA 10GM D3	-
Conn. Block (CBM)		CBM 10GM 2P UNIT	CBM 10GM UNIT	-
CBB BLOCK UNIT		-	CBB BLOCK UNIT CBB BLOCK UNIT2C	-
CBB PLATE		-	CBBPLATE 10GM	-
PC MALE		-	PCMALE 10GM 50 A (\leq 50 A) PCMALE 10GM 100 A ($>$ 50 A)	-
Terminal Busbar (TBB)	Straight Busbar	-	-	-
	Spreader Busbar	-	-	-
Rear Connection Terminal (RCT)	LINE/LOAD (\leq 50 A)	RCT 05GM F2	RCT 05GM F3	RCT 05GM F4
	LINE/LOAD ($>$ 50 A)	RCT 10GM F2	RCT 10GM F3	RCT 10GM F4
Cage Terminal (CTB)	(\leq 50 A) inch	CTB 10GM 2S50	CTB 10GM 3S50	CTB 10GM 4S50
	($>$ 50 A) inch	CTB 10GM 2S100	CTB 10GM 3S100	CTB 10GM 4S100
	(\leq 50 A) mm	CTB 10GM 2S50-MM	CTB 10GM 3S50-MM	CTB 10GM 4S50-MM
	($>$ 50 A) mm	CTB 10GM 2S100-MM	CTB 10GM 3S100-MM	CTB 10GM 4S100-MM
Din Rail Adaptor (DRA)		DRA 10GM	DRA 10GM	DRA 10GM

Internal Accessory

	Auxiliary Switch (AUX)	Alarm Switch (ALT)	Auxiliary/Alarm (AXT)
Indication Contacts	AUX 10GM C1 AUX 10GM C2	ALT 10GM L1 ALT 10GM R1	AXT 10GM L1 AXT 10GM R1
	Shunt Trip (SHT)	Under-Voltage Trip (UVT)	
	SHT 10GM DC 24 V SHT 10GM DC 100 - 120 V SHT 10GM DC 48 V SHT 10GM DC 60 V SHT 10GM DC 125 V SHT 10GM AC 100 - 120 V SHT 10GM AC 200 - 250 V SHT 10GM AC 380 - 480 V	UVT 10GM DC 24 V UVT 10GM DC 100 - 110 V UVT 10GM DC 48 V UVT 10GM AC 100 - 120 V UVT 10GM AC 200 - 230 V UVT 10GM AC 380 - 415 V UVT 10GM AC 440 - 480 V	
Remote Tripping			-

External Accessory

		Front Contact (TFG)		Extension (TFH)	
		2 Pole		3 Pole	
		Upper Line	TFG 10GM U	TFG 10GM R	TFH 10GM
Rotary Handle	Right Line	-	-	-	TFH 10GM
	Left Line	-	-	-	TFH 10GM
Motor Operator ¹⁾		-	-	MOT 10GM DC 24 V	
		-	-	MOT 10GM AC/DC 110 V	
		-	-	MOT 10GM AC/DC 240 V	
Terminal Cover	Short	TCF 10GM S2	TCF 10GM S3	TCF 10GM S4	
	Long	TCF 10GM L2	TCF 10GM L3	TCF 10GM L4	
Locking Device	Padlock	PLD 10GM	PLD 10GM	PLD 10GM	
	Mechanical Interlock	MIF 10GM 2	MIF 10GM 3	MIF 10GM R4 / MIF 10GM N4	
		2 Pole	3 Pole	4 Pole RSTN / NRST	
Interpole Barrier		TQQ 10GM 2	TQQ 10GM 3	TQQ 10GM 4	
Auxiliary Handle			-		

¹⁾ For HGM only.

HGM/HGE50H/L, 125**Connection Method**

		2 Pole	3 Pole	4 Pole
Plug-in	TDM (LINE/LOAD)	-	TDM 12GM P3	-
	TDM (LINE Only)	-	TDM 12GM F3	-
	TDF (LINE Only)	-	TDF 12GM 3	-
	TDA (1 row)	-	TDA 12GM S3	-
	TDA (2 rows)	-	TDA 12GM D3	-
Conn. Block (CBM)		-	CBM 10GM UNIT	-
CBB BLOCK UNIT		-	CBB BLOCK UNIT CBB BLOCK UNIT2C	-
CBB PLATE		-	CBBPLATE 10GM	-
PC MALE		-	PCMALLE 12GM	-
Terminal Busbar (TBB)	Straight Busbar	-	-	-
	Spreader Busbar	-	-	-
Rear Connection Terminal (RCT)	LINE/LOAD	RCT 12GM F2	RCT 12GM F3	RCT 12GM F4
Cage Terminal (CTB)	inch	CTB 12GM 2S	CTB 12GM 3S	CTB 12GM 4S
	mm	CTB 12GM 2S-MM	CTB 12GM 3S-MM	CTB 12GM 4S-MM
Din Rail Adaptor (DRA)		-	-	-

Internal Accessory

	Auxiliary Switch (AUX)	Alarm Switch (ALT)	Auxiliary/Alarm (AXT)
Indication Contacts	AUX 10GM C1 AUX 10GM C2	ALT 10GM L1 ALT 10GM R1	AXT 10GM L1 AXT 10GM R1
	Shunt Trip (SHT)	Under-Voltage Trip (UVT)	
	SHT 10GM DC 24 V SHT 10GM DC 100 - 120 V SHT 10GM DC 48 V SHT 10GM DC 60 V SHT 10GM DC 125 V SHT 10GM AC 100 - 120 V SHT 10GM AC 200 - 250 V SHT 10GM AC 380 - 480 V	UVT 10GM DC 24 V UVT 10GM DC 100 - 110 V UVT 10GM DC 48 V UVT 10GM AC 100 - 120 V UVT 10GM AC 200 - 230 V UVT 10GM AC 380 - 415 V UVT 10GM AC 440 - 480 V	
Remote Tripping			

External Accessory

Rotary Handle	Front Contact (TFG)			Extension (TFH)		
	Upper Line	TFG 12GM U	TFG 12GM R	TFG 12GM L	TFH 12GM	TFH 12GM
	Right Line	TFG 12GM R	TFG 12GM L	TFG 12GM U	TFH 12GM	TFH 12GM
Motor Operator ¹⁾		2 Pole	3 Pole	4 Pole		
		-	-	MOT 12GM DC 24 V	MOT 12GM AC/DC 110 V	MOT 12GM AC/DC 240 V
Terminal Cover	Short	TCF 12GM S2	TCF 12GM S3	TCF 12GM S4		
	Long	TCF 12GM L2	TCF 12GM L3	TCF 12GM L4		
Locking Device	Padlock	PLD 10GM	PLD 10GM	PLD 10GM		
	Mechanical Interlock	MIF 12GM 2	MIF 12GM 3	MIF 12GM 4	MIF 12GM R4 / MIF 12GM N4	
Interpole Barrier		TQQ 10GM 2	TQQ 10GM 3	TQQ 10GM 4		
Auxiliary Handle			-			

※ ¹⁾ For HGM only.

Order Code of Accessories

HGM/HGE Type of Accessory Unit

HGM/HGE160, 250

Connection Method

		2 Pole	3 Pole	4 Pole
Plug-in	TDM (LINE/LOAD)	-	TDM 25GM P3	-
	TDM (LINE Only)	-	TDM 25GM F3	-
	TDF (LINE Only)	-	-	-
	TDA (1 row)	-	-	-
	TDA (2 rows)	-	-	-
Conn. Block (CBM)		-	CBM 10GM UNIT	-
CBB BLOCK UNIT		-	CBB BLOCK UNIT CBB BLOCK UNIT2C	-
CBB PLATE		-	CBBPLATE 10GM	-
PC MALE		-	PCMALE 25GM	-
Terminal Busbar (TBB)	Straight Busbar	TBB 25GP 2S	TBB 25GP 3S	TBB 25GP 4S
	Spreader Busbar	-	TBB 25GP 3E45	TBB 25GP 4E45
Rear Connection Terminal (RCT)	LINE/LOAD	RCT 25GM F2	RCT 25GM F3	RCT 25GM F4
Cage Terminal (CTB)	inch	CTB 25GM 2S	CTB 25GM 3S	CTB 25GM 4S
	mm	CTB 25GM 2S-MM	CTB 25GM 3S-MM	CTB 25GM 4S-MM
Din Rail Adaptor (DRA)		-	-	-

Internal Accessory

	Auxiliary Switch (AUX)	Alarm Switch (ALT)	Auxiliary/Alarm (AXT)
Indication Contacts	AUX 10GM C1	ALT 10GM L1	AXT 10GM L1
	AUX 10GM C2	ALT 10GM R1	AXT 10GM R1
Shunt Trip (SHT)			Under-Voltage Trip (UVT)
Remote Tripping	SHT 10GM DC 24 V	UVT 10GM DC 24 V	
	SHT 10GM DC 100 - 120 V	UVT 10GM DC 100 - 110 V	
	SHT 10GM DC 48 V	UVT 10GM DC 48 V	
	SHT 10GM DC 60 V	UVT 10GM AC 100 - 120 V	
	SHT 10GM DC 125 V	UVT 10GM AC 200 - 230 V	
	SHT 10GM AC 100 - 120 V	UVT 10GM AC 380 - 415 V	
	SHT 10GM AC 200 - 250 V	UVT 10GM AC 440 - 480 V	
	SHT 10GM AC 380 - 480 V	-	

External Accessory

	Front Contact (TFG)	Extension (TFH)	
	2 Pole	3 Pole	4 Pole
Rotary Handle	Upper Line	TFG 25GM U	TFH 25GM
	Right Line	TFG 25GM R	TFH 25GM
	Left Line	TFG 25GM L	TFH 25GM
Motor Operator ¹⁾	-	-	MOT 25GM DC 24 V
	-	-	MOT 25GM AC/DC 110 V
	-	-	MOT 25GM AC/DC 240 V
Terminal Cover	Short	TCF 25GM S3	TCF 25GM S4
	Long	TCF 25GM L3	TCF 25GM L4
Locking Device	Padlock	PLD 10GM	PLD 10GM
	Mechanical Interlock	MIF 25GM 3	MIF 25GM R4 / MIF 25GM N4
Interpole Barrier		2 Pole	3 Pole
		TQQ 25GM 2	TQQ 25GM 3
Auxiliary Handle			4 Pole
			TQQ 25GM 4

¹⁾ For HGM only.

HGM/HGE400**Connection Method**

		2 Pole	3 Pole	4 Pole
Plug-in	TDM (LINE/LOAD)	-	TDM 40GM P3	-
	TDM (LINE Only)	-	TDM 40GM F3	-
Conn. Block (CBM)		-	CBM 10GM UNIT	-
CBB BLOCK UNIT		-	CBB BLOCK UNIT CBB BLOCK UNIT2C	-
CBB PLATE		-	CBBPLATE 40GM	-
PC MALE		-	PCM40GM	-
Terminal Busbar (TBB)	Straight Busbar	TBB 40GM 2S	TBB 40GM 3S	TBB 40GM 4S
	Spreader Busbar	-	TBB 40GM 3E59	TBB 40GM 4E59
Rear Connection Terminal (RCT)	LINE	-	RCT 40GM F3 LINE	RCT 40GM F4 LINE
	LOAD	-	RCT 40GM F3 LOAD	RCT 40GM F4 LOAD
Cage Terminal (CTB)	1 Hole	-	CTB 40GM 3S1H	CTB 40GM 4S1H
	2 Hole	-	CTB 40GM 3S	CTB 40GM 4S

Internal Accessory

	Auxiliary Switch (AUX)	Alarm Switch (ALT)
Indication Contacts	AUX 40GM C1	ALT 40GM L1
	Shunt Trip (SHT)	Under-Voltage Trip (UVT)
	SHT 40GM DC 24 V	UVT 40GM DC 24 V
	SHT 40GM DC 100 - 110 V	UVT 40GM DC 100 - 110 V
Remote Tripping	SHT 40GM AC 100 - 120 V	UVT 40GM AC 100 - 120 V
	SHT 40GM AC 200 - 230 V	UVT 40GM AC 200 - 230 V
	SHT 40GM AC 380 - 415 V	UVT 40GM AC 380 - 415 V
	SHT 40GM AC 440 - 480 V	UVT 40GM AC 440 - 480 V

External Accessory

	Front Contact (TFG)	Extension (TFH)	
Rotary Handle	Upper Line	TFH 40GM	
	Right Line	TFH 40GM	
	Left Line	TFH 40GM	
	2 Pole	3 Pole	4 Pole
Motor Operator ¹⁾	-	MOT 40GM DC 24 V	
	-	MOT 40GM AC/DC 110 V	
	-	MOT 40GM AC/DC 240 V	
Terminal Cover	Short	TCF 40GM S3	TCF 40GM S4
	Long	TCF 40GM L3	TCF 40GM L4
Locking Device	Padlock	PLD 40GM	PLD 40GM
	Mechanical Interlock	MIF 40GM 3	MIF 40GM R4 / MIF 40GM N4
Interpole Barrier		TQQ 40GM 2	TQQ 40GM 3
Auxiliary Handle			THA 48GM

※ 1) For HGM only.

Order Code of Accessories

HGM/HGE Type of Accessory Unit

HGM/HGE630, 800

Connection Method

		2 Pole	3 Pole	4 Pole
Plug-in	TDM (LINE/LOAD)	-	TDM 80GM P3	-
	TDM (LINE Only)	-	TDM 80GP F3	-
Conn. Block (CBM)		-	CBM 10GM UNIT	-
CBB BLOCK UNIT		-	CBB BLOCK UNIT CBB BLOCK UNIT2C	-
CBB PLATE		-	CBBPLATE 80GM	-
PC MALE		-	PCMALE 80GM	-
Terminal Busbar (TBB)	Straight Busbar	TBB 63GM 2S (HGM/HGE630) TBB 80GM 2S (HGM/HGE800)	TBB 63GM 3S (HGM/HGE630) TBB 80GM 3S (HGM/HGE800)	TBB 63GM 4S (HGM/HGE630) TBB 80GM 4S (HGM/HGE800)
	Spreader Busbar	-	-	-
Rear Connection Terminal (RCT)	LINE	-	RCT 80GM F3 LINE	RCT 80GM F4 LINE
	LOAD	-	RCT 80GM F3 LOAD	RCT 80GM F4 LOAD
Cage Terminal (CTB)		-	CTB 80GM 3S	CTB 80GM 4S

Internal Accessory

	Auxiliary Switch (AUX)	Alarm Switch (ALT)
Indication Contacts	AUX 40GM C1	ALT 40GM L1
	Shunt Trip (SHT)	Under-Voltage Trip (UVT)
	SHT 40GM DC 24 V	UVT 40GM DC 24 V
	SHT 40GM DC 100 - 110 V	UVT 40GM DC 100 - 110 V
Remote Tripping	SHT 40GM AC 100 - 120 V	UVT 40GM AC 100 - 120 V
	SHT 40GM AC 200 - 230 V	UVT 40GM AC 200 - 230 V
	SHT 40GM AC 380 - 415 V	UVT 40GM AC 380 - 415 V
	SHT 40GM AC 440 - 480 V	UVT 40GM AC 440 - 480 V

External Accessory

	Front Contact (TFG)	Extension (TFH)	
	2 Pole	3 Pole	4 Pole
Rotary Handle	Upper Line	TFG 80GM U	TFH 80GM
	Right Line	TFG 80GM R	TFH 80GM
	Left Line	TFG 80GM L	TFH 80GM
Motor Operator ¹⁾		-	MOT 80GM DC 24 V
		-	MOT 80GM AC/DC 110 V
		-	MOT 80GM AC/DC 240 V
Terminal Cover	Short	TCF 80GM S3	TCF 80GM S4
	Long	TCF 80GM L3	TCF 80GM L4
Locking Device	Padlock	PLD 40GM	PLD 40GM
	Mechanical Interlock	MIF 80GM 3	MIF 80GM R4 / MIF 80GM N4
Interpole Barrier	TQQ 40GM 2	TQQ 40GM 3	TQQ 40GM 4
Auxiliary Handle		THA 48GM	

¹⁾ For HGM only.

Order Code of Accessories

HGP Type of Accessory Unit

HGP50/125/160D

Connection Method

Plug-in		3 Pole	4 Pole
TDM (LINE/LOAD)		TDM 16GP P3	-
TDM (LINE Only)		TDM 16GP F3	-
Conn. Block (CBM)		CBM 10GM UNIT	-
CBB BLOCK UNIT		CBB BLOCK UNIT CBB BLOCK UNIT2C	-
CBB PLATE		CBBPLATE 16GP	-
PC MALE		PCMALE 16GP	-
Terminal Busbar (TBB)	Straight Busbar Spreader Busbar	- -	- -
Rear Connection Terminal (RCT)	LINE/LOAD	RCT 16GP F3	RCT 16GP F4
Cage Terminal (CTB)		CTB 16GP 3	CTB 16GP 4

Internal Accessory

	Auxiliary Switch (AUX)	Alarm Switch (ALT)
Indication Contacts	AUX 16GP R1 AUX 16GP R2	ALT 16GP L1 -
	Shunt Trip (SHT)	Under-Voltage Trip (UVT)
	SHT 16GP DC 24 V SHT 16GP DC 100 - 110 V SHT 16GP AC 100 - 120 V SHT 16GP AC 200 - 230 V SHT 16GP AC 380 - 415 V SHT 16GP AC 440 - 480 V	UVT 16GP DC 24 V UVT 16GP DC 100 - 110 V UVT 16GP AC 100 - 120 V UVT 16GP AC 200 - 230 V UVT 16GP AC 380 - 415 V UVT 16GP AC 440 - 480 V
Remote Tripping		

External Accessory

	Extended (TFH)	Front Contact (TFG)	Extension (TFH)
Rotary Handle	Upper Line Right Line Left Line	TFG 16GP U TFG 16GP R TFG 16GP L	TFH 16GP TFH 16GP TFH 16GP
			3 Pole / 4 Pole
Motor Operator		MOT 16GP DC 24 V MOT 16GP AC/DC 110 V MOT 16GP AC/DC 240 V	
			3 Pole
Terminal Cover	Short Long	TCF 16GP S3 TCF 16GP L3	- TCF 16GP L4
Locking Device	Padlock Mechanical Interlock	PLD 16GP MIF 16GP 3	PLD 16GP MIF 16GP R4
Interpole Barrier		TQQ 16GP 3	TQQ 16GP 4
Auxiliary Handle			-

HGP100/160/250**Connection Method**

Plug-in		3 Pole	4 Pole
TDM (LINE/LOAD)		TDM 25GM P3	-
TDM (LINE Only)		TDM 25GM F3	-
Conn. Block (CBM)		CBM 10GM UNIT	-
CBB BLOCK UNIT		CBB BLOCK UNIT	-
CBB PLATE		CBBPLATE 10GM	-
PC MALE		PCMALE 25GP-G	-
Terminal Busbar (TBB)	Straight Busbar Spreader Busbar	TBB 25GP 3S TBB 25GP 3E45	TBB 25GP 4S TBB 25GP 4E45
Rear Connection Terminal (RCT)	LINE/LOAD	RCT 25GP-G F3	RCT 25GP-G F4
Cage Terminal (CTB)		CTB 25GP 3	CTB 25GP 4
Series Busbar (SBB)		SBB 25 GP	SBB 25 GP
Terminal Height Compensation Terminal (STP) ⁶⁾		STP 25GP-G 3T2.5 STP 25GP-G 3T4.5	STP 25GP-G 4T2.5 STP 25GP-G 4T4.5

Internal Accessory

	Auxiliary Switch (AUX)		Alarm Switch (ALT)
	Indication Contacts		
Remote Tripping	AUX 25GP L1 AUX 25GP R2		ALT 25GP L1 ALT 25GP R2
	Shunt Trip (SHT)		Under-Voltage Trip (UVT)
	SHT 25GP-G DC 24 V SHT 25GP-G DC 100 - 110 V SHT 25GP-G AC 100 - 120 V SHT 25GP-G AC 200 - 230 V SHT 25GP-G AC 380 - 415 V SHT 25GP-G AC 440 - 480 V		UVT 25GP-G DC 24 V UVT 25GP-G DC 100 - 110 V UVT 25GP-G AC 100 - 120 V UVT 25GP-G AC 200 - 230 V UVT 25GP-G AC 380 - 415 V UVT 25GP-G AC 440 - 480 V
Electronic Internal Option	Indicator fault alarm LED DC 24 V POWER CABLE ²⁾ DC 24 V TERMINAL BLOCK ³⁾ DC 3.6 V BATTERY	FAL 25GP ¹⁾ PWC 25GP DC 24 V TB 25GP DC 24 V BAT 25GP 1 EA ⁴⁾ BAT 25GP 1 EA ⁵⁾	

External Accessory

	Front Contact (TFG)		Extension (TFH)
	Rotary Handle	Upper Line Right Line Left Line	TFG 25GP U TFG 25GP R TFG 25GP L
	Motor Operator		MOT 25GP DC 24 V MOT 25GP AC/DC 110 V MOT 25GP AC/DC 240 V
Terminal Cover	Short Long	TCF 25GP-G S3 TCF 25GP-G L3	3 Pole / 4 Pole - TCF 25GP-G L4
Locking Device	Padlock Mechanical Interlock	PLD 25GP MIF 25GP 3	PLD 25GP MIF 25GP R4 TQQ 25GP-G 4
Interpole Barrier		TQQ 25GP-G 3	-
Auxiliary Handle		-	-
Electronic External Option	TEST KIT NFC MODULE		TESTKIT 25GP NFCMD 25GP

※ 1) FAL option for Electronic MCCB replace installation space of SHT/UVT 1 + AUX1 in MCCB internal accessory diagram of 81 page.

2) Applicable to ETU "A", "E" type only, length : 1.5 m

3) Applicable to ETU "A", "E" type only

4) 10 EA plastic wrapped

5) 1 EA plastic wrapped

6) Match of terminal height between old and new model (T2.5 : height 2.5 mm / T4.5 : height 4.5 mm, 3 Pole 3 EA / 4 Pole 4 EA)

7) 1 EA

Order Code of Accessories

HGP Type of Accessory Unit

HGP400/630

Connection Method

Plug-in		3 Pole	4 Pole
TDM (LINE/LOAD)		TDM 63GP P3	-
TDM (LINE Only)		TDM 63GP F3	-
Conn. Block (CBM)		CBM 10GM UNIT	-
CBB BLOCK UNIT		CBB BLOCK UNIT CBB BLOCK UNIT2C	-
CBB PLATE		CBBPLATE 63GP	-
PC MALE		PCMALE 63GP	-
Terminal Busbar (TBB)	Straight Busbar	TBB 63GP 3S	TBB 63GP 4S
	Spreader Busbar	TBB 63GP 3E61.5	TBB 63GP 4E61.5
Rear Connection Terminal (RCT)	LINE	RCT 63GP F3 LINE	RCT 63GP F4 LINE
	LOAD	RCT 63GP F3 LOAD	RCT 63GP F4 LOAD
Cage Terminal (CTB)		CTB 63GP 3	CTB 63GP 4
Series Busbar (SBB)		SBB 63 GP	SBB 63 GP

Internal Accessory

	Auxiliary Switch (AUX)	Alarm Switch (ALT)
Indication Contacts	AUX 63GP L1 AUX 63GP L2 AUX 63GP L3	ALT 63GP R1 -
		-
Remote Tripping	Shunt Trip (SHT) SHT 63GP DC 24 V SHT 63GP DC 100 - 110 V SHT 63GP AC 100 - 120 V SHT 63GP AC 200 - 230 V SHT 63GP AC 380 - 415 V SHT 63GP AC 440 - 480 V	Under-Voltage Trip (UVT) UVT 63GP DC 24 V UVT 63GP DC 100 - 110 V UVT 63GP AC 100 - 120 V UVT 63GP AC 200 - 230 V UVT 63GP AC 380 - 415 V UVT 63GP AC 440 - 480 V
Electronic Internal Option	Indicator fault alarm LED DC 24 V POWER CABLE ²⁾ DC 24 V TERMINAL BLOCK ³⁾ DC 3.6 V BATTERY	FAL 25GP ¹⁾ PWC 25GP DC 24 V TB 25GP DC 24 V BAT 25GP 10 EA ⁴⁾ BAT 25GP 1 EA ⁵⁾

External Accessory

	Front Contact (TFG)	Extension (TFH)
Rotary Handle	Upper Line Right Line Left Line	TFH 63GP TFH 63GP TFH 63GP
Motor Operator	3 Pole/4 Pole MOT 63GP DC 24 V MOT 63GP AC/DC 110 V MOT 63GP AC/DC 240 V	MOT 63GP DC 24 V MOT 63GP AC/DC 110 V MOT 63GP AC/DC 240 V
Terminal Cover	Short Long	3 Pole TCF 63GP S3 TCF 63GP L3
Locking Device	Padlock Mechanical Interlock	4 Pole PLD 63GP MIF 63GP 3
Interpole Barrier		TQQ 63GP 4
Auxiliary Handle		THA 63GP
Electronic External Option	TEST KIT NFC MODULE	TESTKIT 25GP NFCMD 25GP

※ 1) FAL option for Electronic MCCB replace installation space of SHT/UVT 1 + AUX1 in MCCB internal accessory diagram of 81 page.

2) Applicable to ETU "A", "E" type only, length : 1.5 m

3) Applicable to ETU "A", "E" type only

4) 10 Ea plastic wrapped

5) 1 Ea plastic wrapped

HGP800**Connection Method**

Plug-in		3극	4극
TDM (LINE/LOAD)		TDM 80GP P3	-
TDM (LINE Only)		TDM 80GP F3	-
Conn. Block (CBM)		CBM 10GM UNIT	-
CBB BLOCK UNIT		CBB BLOCK UNIT CBB BLOCK UNITC	-
CBB PLATE		CBBPLATE 80GP	-
PC MALE		PCMALLE 80GP	-
Terminal Busbar (TBB)	Straight Busbar Spreader Busbar	TBB 80GP 3S -	TBB 80GP 4S -
Rear Connection Terminal (RCT)	LINE LOAD	RCT 80GP F3 LINE RCT 80GP F3 LOAD	RCT 80GP F4 LINE RCT 80GP F4 LOAD
Cage Terminal (CTB)		CTB 80GP 3	CTB 80GP 4
Series Busbar (SBB)		SBB 80 GP	SBB 80 GP

Internal Accessory

Indication Contacts	Auxiliary Switch (AUX)		Alarm Switch (ALT)
	AUX 63GP L1	AUX 63GP L2	ALT 63GP R1
	AUX 63GP L3		-
Remote Tripping	Shunt Trip (SHT)	Under-Voltage Trip (UVT)	
	SHT 63GP DC 24 V	UVT 63GP DC 24 V	
	SHT 63GP DC 100 - 110 V	UVT 63GP DC 100 - 110 V	
	SHT 63GP AC 100 - 120 V	UVT 63GP AC 100 - 120 V	
	SHT 63GP AC 200 - 230 V	UVT 63GP AC 200 - 230 V	
	SHT 63GP AC 380 - 415 V	UVT 63GP AC 380 - 415 V	
Electronic Internal Option	SHT 63GP AC 440 - 480 V	UVT 63GP AC 440 - 480 V	
	Indicator fault alarm LED	FAL 25GP ¹⁾	
	DC 24 V POWER CABLE ²⁾	PWC 25GP DC 24 V	
	DC 24 V TERMINAL BLOCK ³⁾	TB 25GP DC 24 V	
	DC 3.6 V BATTERY	BAT 25GP 10 EA ⁴⁾	BAT 25GP 1 EA ⁵⁾

External Accessory

	Front Contact (TFG)		Extension (TFH)
	Upper Line	TFG 80GP U	TFH 80GP
	Right Line	TFG 80GP R	TFH 80GP
Motor Operator	Left Line	TFG 80GP L	TFH 80GP
	3 Pole / 4 Pole		
		MOT 80GP DC 24 V	
Terminal Cover		MOT 80GP AC/DC 110 V	
		MOT 80GP AC/DC 240 V	
Locking Device	3 Pole	4 Pole	
	Short	TCF 80GP S3	-
	Long	TCF 80GP L3	TCF 80GP L4
Interpole Barrier	Padlock	PLD 80GP	PLD 80GP
	Mechanical Interlock	MIF 80GP 3	MIF 80GP R4
Auxiliary Handle		TQQ 80GP 3	TQQ 80GP 4
		THA 80GP	THA 80GP
Electronic External Option	TEST KIT	TESTKIT 25GP	
	NFC MODULE	NFCMD 25GP	

* 1) FAL option for Electronic MCCB replace installation space of SHT/UVT 1 + AUX1 in MCCB internal accessory diagram of 81 page.

2) Applicable to ETU "A", "E" type only, length : 1.5 m

3) Applicable to ETU "A", "E" type only

4) 10 EA plastic wrapped

5) 1 EA plastic wrapped

Handling and Maintenance Inspection

Storage and Transportation

Storage Precaution

| Ambient Temperature | - 20 ~ + 60 °C

| Altitude | Below 1,000 m above sea level

| Relative Humidity | Within 45 % ~ 85 %

The surrounding environment may affect the insulation function and Endurance of the molded case and earth leakage circuit breakers so the environment condition for usage must accurately be checked before application.



- Do not store in places with corrosive gas
Do not leave it around gas containing sulfurous gas or sulfur or ammonia gas and others.



- Do not store in places with high humidity for a long period of time



- Do not leave under direct sunlight for a long period of time.



- Avoid places with a lot of dust
Do not store in exposed places and use cover or packing material to prevent dust from piling up on the circuit breaker.




- Avoid storage in high or low temperature
Storage temperature must be maintained between - 20 °C ~ + 60 °C.
(Exceptionally, the HGM/HGP-MCCB in the original packing can be stored up to - 40 °C.)

Transportation Precautions

Caution

- Do not apply impact during transportation. Dropping or applying strong impact may cause defect.
- Do not handle while holding the circuit breaker's accessory or the external plug-in wire of the accessory. It may cause injury in the handler or a malfunction of the circuit breaker.



- Hold the main unit of the circuit breaker during transportation
Do not handle while holding the external guide line of the accessory or the terminal bar.



- Pay attention when handling metal accessories
Sharp planes or edges in the metal accessory may cause injury.



- Do not apply impact during transportation
Dropping or applying strong impact may cause defect.




- Pay attention to the packaging of the circuit breaker before transportation
Inappropriate packaging may cause damage in the circuit breaker during transportation.

Installation

As for the detailed dimension of each part required for installation, refer to the external structure.

⚠ Caution

- Electrical works shall only be conducted by a person qualified for electrical works.
- For wiring works, the upper circuit breaker must be cut off (OFF) and execute the work after checking that it is not charged.
- In case of disconnecting cable or terminal bar, tighten the terminal screw firmly at the standard tightening torque.
In case the terminal screw is tightened loosely, it may cause damage and fire due to overheating.
- Strictly insulate up to the circuit breaker's portion with terminal barrier, insulating tube, insulating tape and others between bare conductors with regards to the front connection of the circuit breaker.
In case it is not insulated, it may cause short circuit.



- Secure sufficient arc space (Insulation distance) so that the arc gas discharge outlet is not blocked.
In case this discharge outlet is blocked, the current may not be blocked.
- Do not install the circuit breaker in abnormal environment such as high temperature, high humidity, dust, corrosive gas, vibration, impact and others. It may cause fire or abnormal trip.
- Install so that foreign substances (Metal powder, concrete powder etc.), rainwater and others do not enter the circuit breaker.
Such foreign substances in the circuit breaker may cause fire or malfunction.
- In case of 4 pole circuit breaker, the neutral wire of 3 phase 4 wire must be connected to the N phase (Right end part of the circuit breaker).
- When mounting the product, the live part (LINE) signal must be connected to the live part and the load part (LOAD) signal must be connected to the load part. Wrong connection may cause damage in product and electric shock.
- In case the insulation barrier is not mounted between the circuit breaker terminals, it may cause secondary short-circuit accidents so it must be used.

Handling and Maintenance Inspection

Installation

Installation Precautions

- Install the circuit breaker in a place that satisfies the following environment conditions

Installing the circuit breaker in places and environment other than the following may cause malfunction of circuit breaker, fire and others.

- Ambient temperature should be within -5 °C to +50 °C degrees.
(The default MCCB based on 40 °C ambient temperature.
50 °C products have a separate code and temperature correction table. If the ambient temperature is -40 °C to -5 °C, the HGM/HGP MCCB can be used under limited conditions.)
- Relative humidity to be within 45 ~ 85 %
- Excessive vibration or impact to be avoided
- True height to be below 2,000 m
- To be used in an environment without excessive water vapor, oil vapor, smoke, dust, alkaline, corrosive material and others
- To avoid direct sunlight



- Arc gas exhaust hole must not be blocked
It may drop the breaking capacity.



- Attention to be paid to dust, metal fragments and others
After installation, protection cover and covers to be covered during work



- The insulation plate attached to the bottom of the circuit breaker must not be separated
It may destroy insulation and drop the insulation performance.

Connection Precautions




- When fastening the terminal screw, it should be fastened according to the specified torque
Incomplete fastening of terminal screw may cause overheating so each terminal screw must be fastened completely according to the specified torque. In addition, excessive fastening torque may cause damage in the terminal screw and the circuit breaker case.



- Use of lubricant at the terminal screw part is prohibited
Lubricant reduces the friction of the screw, causing the screw to loosen, ultimately leading to an increase in temperature.



- Exposed conductor must be insulated
Insulating tube or insulating tape must be used for complete insulation between the bare conductors of the MCCB.
In case the terminals are not insulated, it may cause secondary short-circuit during short-circuit accidents.



- Stud must not be deformed
Excessive force must not be applied to the stud at the conductor connecting part of the rear connection type.
In addition, stud must not be deformed during wiring.



- In case of 4 pole circuit breaker, the neutral wire of 3 phase 4 wire must be connected to the N phase.
It may not function in overcurrent which may cause fire.



- The conductor must be fixed firmly on a flat state.
As for the connecting conductor, electromagnetic force between conductors is generated by extremely big fault current so it must be fixed firmly.

Connection Precautions


The following table is the impact electromagnetic force generated by fault current.

Impact Electromagnetic Force per 1 m Conductor

Regulated Short-Circuit Current kA (Power Factor)	Electromagnetic Force (In Case of 3 Phase Short Circuit) N (kgf)	
	10 cm Conductor Interval	20 cm Conductor Interval
10 (0.4)	490 (50)	245 (25)
18 (0.3)	1,863 (190)	932 (95)
25 (0.2)	4,412 (450)	2,206 (225)
35 (0.23)	8,630 (880)	4,315 (440)
42 (0.2)	12,455 (1,270)	6,277 (635)
50 (0.2)	17,652 (1,800)	8,826 (900)
65 (0.2)	29,910 (3,050)	14,955 (1,525)
85 (0.2)	51,190 (5,220)	25,595 (2,510)
100 (0.2)	70,804 (7,220)	35,402 (3,610)
125 (0.2)	110,815 (11,300)	55,408 (5,650)


- Contact surface must be clean**

Dust and others must be removed from the contact surface to prevent increase in connection resistance at the contact surface.



- Conductor must be connected so that it has direct contact with the contact surface**

Do not use bolt or nut between the contact surfaces of the conductor.
If there is no direct contact between conductors, it may cause increase in temperature and fire.



- Do not overlap the conductors**

When numerous conductors are connected to the terminal bar, do not overlap and assemble.
Assemble at both ends of the terminal bar.

Maintenance Inspection

Initial Inspection

- Residues of steel plate, grinded materials of the wire, other conductor's foreign substances and others must not be left around the terminal of the circuit breaker
- There must be no crack and damage in the cover and base
- The fastening status of the terminal fastening part must be checked
- Check must be made if the rated voltage and breaking capacity of the circuit breaker are correct
- When the insulation resistance is measured using a 500 V insulation-resistance tester, it must be above $5\text{ M}\Omega$

Withstand Voltage

Main Circuit		Auxiliary Circuit or Control Circuit ¹⁾	
Rated Insulation Voltage	Test Voltage (Effective Value of Interchange)	Rated Insulation Voltage of Operational Circuit	Test Voltage (Effective Value of Interchange)
$Ui \leq 300\text{ V}$	2,000 V for 1 min	$U_{is} \leq 60\text{ V}$	1,000 V for 1 min
$300 < Ui \leq 600\text{ V}$	2,500 V for 1 min	$60\text{ V} < U_{is} \leq 600\text{ V}$	$2 \cdot U_{is}$ 1,000 V (최소 1,500 V) for 1 min

※ Based on the above mentioned table, do not conduct withstand voltage test above it.

¹⁾ Between terminal and grounding

Handling and Maintenance Inspection

Maintenance Inspection

Regular Inspection

Inspection shall be conducted once in 1 month before/after the commencement of the equipment operation in order to maintain the performance of the circuit breaker and to prevent unexpected accidents. After that, regular inspection is required depending on the environment.

Standard of Inspection Period

Extent	Environment	Standard of Inspection Period
Standard Usage State	Clean and dry state of air	Less than 10 years after installation - Once in 2 ~ 3 years More than 10 years after installation - Once a year More than 15 years after installation - Once in 6 months Less than 10 years after installation - Once a year
	Place without corrosive gas even though there is dust inside	More than 10 years after installation - Once in 6 months More than 15 years after installation - Once a month
	Place containing sulfuric acid, hydrogen sulfide, salinity, vapor and others	Less than 5 years after installation - Once in 6 months More than 5 years after installation - Once a year
	Places with specially more corrosive gas	Once a month
Bad Environment		

Regular Inspection Item

Inspection Item	Procedure	Countermeasure
Tightening of Terminal Screw	• Inspect tightening of terminal screw, conductor connecting screw	• Tighten according to the specified torque Ensure that it is not tightened excessively
Dust and Foreign Substance	• Check for foreign substance such as dust on the circuit breaker's surface, especially the top of the live part. There must be no dust or foreign substance to secure insulation distance	• Remove dust, foreign substance and others using cloth with clean surface types (Do not use thinner or detergent)
Damage in Mold Case	• Check for damage or crack on the circuit breaker's cover and base	• Replace circuit breaker
Arc Exhaust Hole	• Check for pollution in the arc exhaust hole	• If there are burns or excessive pollution due to melted metal particles and others, replace the circuit breaker
Switch Operation	<ul style="list-style-type: none"> • If the circuit breaker was maintained at closed state at normal times, operate the switch multiple times. Friction caused by hardened grease and others will be reduced and the contact resistance can be stabilized • Press the trip button to trip the circuit breaker multiple times • If internal options were installed in mccb, the options should be checked when mccb is in switch operation 	<ul style="list-style-type: none"> • If there is a problem in the switch operation of the circuit breaker, replace or contact the nearest store • If the specified limit value of the switch operation has exceeded, replace • If there is a internal option problem in the switch operation, replace
Discoloration of Terminal Part	<ul style="list-style-type: none"> • Check for severe discoloration in the terminal part or conductor part • If there is severe discoloration in the copper conductor or silver coated part, check the insulation performance caused by thermal damage 	<ul style="list-style-type: none"> • Slight discoloration in the silver coated part is not a problem. If there is a problem in insulation due to thermal damage, replace the circuit breaker
Insulation Resistance	• Separate all conductors connected to the circuit breaker and measure the insulation resistance between the poles, terminals and groundings	• If the insulation resistance is not more than 5 MΩ, replace

Inspection and Processing after Blocking Fault Current

In case the circuit breaker has blocked the fault current, determine whether it can be re-used or whether it has to be replaced with a new product depending on the size of the fault current.

- In case the arc exhaust hole is not polluted or there are no other abnormalities, it can be reused.
- In case there is pollution such as dark burns around the arc exhaust hole and in case the insulation resistance is above 5 MΩ, there is no dielectric breakdown when the specified withstand voltage is applied and in case there is no excessive temperature increase in the terminal part, it can be reused.
- If there are burns at the handle part, severe pollution around the arc exhaust hole, melted metal particles and others, replace the circuit breaker immediately.

Detailed inspection and management of items when installed and used on a ship

- Special : A situation where fault current is cut off or abnormal trip occurs
- Usually : Within 2 years of installation
- Thorough : More than 3 years after installation

Inspection Part	Inspection Items	Inspection Cycle			Inspection Details	Note
		Special	Usually	Thorough		
Terminal and mold of MCCB	Inspection of appearance	After the fault current cut off	1 month		1) Procedures : Check for damage and dust of mold cover near the terminal of MCCB 2) Judgement : There must be no crack and damage	Inspect under power outage
ETU	Measuring test	After the fault current cut off	1 month		1) Procedures : Compare the measured value of the phase current with the measured value of ETU using the phase current meter 2) Judgement : Within a 5% margin of measurement error	Inspect while energized
AUX/ALT	Inspection of operating		1 month		1) Procedures : When the mechanism is in ON/OFF/Trip status, check for normal operation under each condition 2) Judgement : Normal operations under each condition	Inspect under power outage
SHT			1 year		1) Procedures : When applying the SHT voltage of 70%, check for trip of MCCB 2) Judgement : MCCB must be tripped normally	Inspect under power outage
UVT			1 year		1) Procedures : - When applying the UVT voltage of 35%, check for a trip - When applying the UVT voltage of 85%, check for a operation of the RESET/ON/OFF function 2) Judgement : Normal operations under each condition	Inspect under power outage
ETU		After the fault current cut off	1 year		1) Procedures : Please use the ETU TEST KIT and check for trip of MCCB 2) Judgement : MCCB must be tripped normally	Inspect under power outage
Mechanism		After the fault current cut off	1 year		1) Procedures : - ON/OFF operation test, correct positioning when OFF, and test of energization status - Check the operation of the trip button and ensure it is in the correct position 2) Judgement : Normal operations under each condition	Inspect under power outage
Terminal of MCCB	Tightening torque	After the fault current cut off	1 year		1) Procedures : Check and mark the engagement using the torque gauge 2) Judgement : It shall conform to the torque criteria - Round-headed cross-groove screw M5 : 28.5kg·cm - InHex M8 : 60kg·cm - Hex M8 : 110kg·cm - Hex M10 : 200kg·cm - Hex M12 : 400kg·cm	Inspect under power outage
Terminal of MCCB	Temperature	After the fault current cut off		3 years	1) Procedures : Please use a contact thermometer (Type K) to measure the exposed part of the line/load terminal 2) Judgement : A rise in temperature : 80K, Maximum temperature within. 120°C	Inspect while energized
Terminal and mold of MCCB	Insulation characteristics	After the fault current cut off		3 years	1) Procedures : Please use a insulation resistance measuring device (DC 1000V) to test the insulation resistance between the poles, terminals, and groundings 2) Judgement : insulation resistance \geq 5 MΩ.	Inspect under power outage
Contacts and arc extinguishing part		After the fault current cut off		3 years	1) Procedures : Please use the impulse voltage measuring device to measure the leakage current of each phase after switching off the circuit breaker 2) Judgement : Leakage current \leq 1mA	Remove the panel and inspect it under power outage

Handling and Maintenance Inspection

Maintenance Inspection

Countermeasures with Regards to Abnormal Phenomenon

In case there is abnormal phenomenon during the use of circuit breakers, take appropriate action according to the following table.

Type of Abnormality	Phenomenon	Assumed Cause	Action to be Taken
Abnormal Heating	Heating at terminal part	<ul style="list-style-type: none"> • Loose terminal screw, conductor connecting screw • Increased resistance of contact 	Re-tighten according to the specified torque Replace circuit breaker
	Damage in insulation material at terminal part	<ul style="list-style-type: none"> • Loose terminal screw, conductor connecting screw • Defect in contact between circuit breaker's terminal and terminal bar or cable lugs due to loose screw tightening and interference caused by foreign substance 	Replace circuit breaker
	Abnormal heating in the circuit breaker's external case	<ul style="list-style-type: none"> • Increased resistance of contact • Loosening at the internal connection part • Increased current density due to disconnection • Big consumption at contact 	Replace circuit breaker
Defect in Current Flow	Abnormal voltage at load side	<ul style="list-style-type: none"> • Foreign substance between contacts • Fusing at conductive part (Excessive opening/closing and corrosion due to corrosive gas) 	Replace circuit breaker
Does Not Function	ON does not function	<ul style="list-style-type: none"> • No reset in trip state • Damage in trip mechanism due to excessive opening/closing • Demagnetized state of under-voltage trip device • Fusing at contact 	ON after reset Replace circuit breaker Apply specified voltage Replace circuit breaker Apply specified voltage Reset after sufficient cooling
	OFF does not function	<ul style="list-style-type: none"> • Demagnetized state of under-voltage trip device • Bimetal has not been cooled sufficiently • Corrosion or deformation of bimetal • Abnormality in mechanism • Can't be used due to excessive opening/closing • Damage in mechanism due to excessive breaking current 	Replace circuit breaker Lower the ambient temperature using wind and others
	RESET does not function	<ul style="list-style-type: none"> • High ambient temperature (Above 40 °C) • Abnormal heating due to loosening of screw at terminal part • Internal heating at the circuit breaker • In case the cross sectional area of connecting conductor is smaller than the regulation • Trip in running inrush current • Trip during switching at Y-Δ operation • Trip during switching in reversible operation 	Replace circuit breaker Change the connecting conductor or change the circuit breaker's rated current Change the instantaneous trip current setting or replace with circuit breaker with bigger rated current
	Trip under rated current	<ul style="list-style-type: none"> • Trip in big running current • Trip in long running current • Short circuit between motor layer • Wrong connection of SHT/UVT's operational circuit 	Replace with circuit breaker with bigger rated current Repair or replace motor Inspect wiring
Overcurrent does Not Function	Does not function above specified operational current	<ul style="list-style-type: none"> • When current limiting breaking of upper fuse or cooperation with upper circuit breaker is low • When the ambient temperature is significantly low • Inappropriate rated current 	Review cooperation again Check the compensating current Check the rated current Check the rated voltage Maintain the rated voltage
	Abnormal operation of shunt trip device (SHT)	<ul style="list-style-type: none"> • Abnormal voltage of operational circuit • Does not function due to voltage drop in operational circuit • Coil damage due to difference in the coil's rated voltage, non-operation of damage prevention switch and others 	Replace accessory Replace accessory Check the rated voltage Replace and check disconnection Replace and check the micro switch load Replace and repair accessory
Abnormality in Accessory	Abnormal operation of under-voltage trip device (UVT)	<ul style="list-style-type: none"> • Defect in mechanism • Difference in voltage used • Damage in UVT controller • Contact damage due to excessive micro switch rating • Defect in mechanism 	Replace accessory Check the rated voltage Replace and check disconnection Replace and check the micro switch load Replace and repair accessory
	Abnormal operation of auxiliary switch (AUX) and alarm switch (ALT)		

Current Status of Acquired Standards

Approvals & Certificates

MCCB

Type of Certification	Approvals			Certificates	
Type of Standard	Safety Certificate	KS	IEC	GB	DEKRA
Mark					
Testing Institute	KETI	KS	CE	GB 1984	DEKRA
Certification Country	Korea	Korea	Europe	China	Netherlands
HGM30	E S	● ●	● ●	● ●	● ●
HGM50	E S H L	● ● ● ●	● ● ● ●	● ● ● ●	● ● ● ●
HGM60	E S H L	● ● ● ●	● ● ● ●	● ● ● ●	● ● ● ●
HGM100	E S H L	● ● ● ●	● ● ● ●	● ● ● ●	● ● ● ●
HGM125	E S H L	● ● ● ●	● ● ● ●	● ● ● ●	● ● ● ●
HGM160	E S H L	● ● ● ●	● ● ● ●	● ● ● ●	● ● ● ●
HGM250	E S H L	● ● ● ●	● ● ● ●	● ● ● ●	● ● ● ●
HGM400	E S H L	● ● ● ●	● ● ● ●	● ● ● ●	● ● ● ●
HGM630	E S H L	● ● ● ●	● ● ● ●	● ● ● ●	● ● ● ●
HGM800	E S H L	● ● ● ●	● ● ● ●	● ● ● ●	● ● ● ●

Current Status of Acquired Standards

Approvals & Marine Certificates

MCCB

Approvals & Certificates

ELCB

Type of Certification	Approvals			Certificates
Type of Standard	Safety Certificate	KS	IEC	IEC
Mark				
Testing Institute	KETI	KS	CE	DEKRA
Certification Country	Korea	Korea	Europe	Netherlands
HGE30	E S	● ●	● ●	● ●
HGE50	E S H L	● ● ● ●	● ● ● ●	● ● ● ●
HGE60	E S H L	● ● ● ●	● ● ● ●	● ● ● ●
HGE100	E S H L	● ● ● ●	● ● ● ●	● ● ● ●
HGE125	E S H L	● ● ● ●	● ● ● ●	● ● ● ●
HGE160	E S H L	● ● ● ●	● ● ● ●	● ● ● ●
HGE250	E S H L	● ● ● ●	● ● ● ●	● ● ● ●
HGE400	E S H L	● ● ● ●	● ● ● ●	
HGE630	E S H L	● ● ● ●	● ● ● ●	
HGE800	S H L	● ● ●	● ● ●	

Current Status of Acquired Standards

Approvals & Certificates

MCCB

Type of Certification	Approvals				Certificates
Type of Standard	Safety Certificate	KS	IEC	GB	IEC
Mark					
Testing Institute	KETI	KS	CE	GB	DEKRA
Certification Country	Korea	Korea	Europe	China	Netherlands
F*			●	●	●
HGP50D	●	●	●	●	●
S	●	●	●	●	●
H	●	●	●	●	●
X	●	●	●	●	●
F*			●	●	●
HGP125D	●	●	●	●	●
S	●	●	●	●	●
H	●	●	●	●	●
X	●	●	●	●	●
F*			●	●	●
HGP160D	●	●	●	●	●
S	●	●	●	●	●
H	●	●	●	●	●
X	●	●	●	●	●
F*			●	●	●
HGP100	●	●	●	●	●
S	●	●	●	●	●
H	●	●	●	●	●
X	●	●	●	●	●
F*			●	●	●
HGP160	●	●	●	●	●
S	●	●	●	●	●
H	●	●	●	●	●
X	●	●	●	●	●
F*			●	●	●
HGP250	●	●	●	●	●
S	●	●	●	●	●
H	●	●	●	●	●
X	●	●	●	●	●
F*			●	●	●
HGP400	●	●	●	●	●
S	●	●	●	●	●
H	●	●	●	●	●
X	●	●	●	●	●
F*			●	●	●
HGP630	●	●	●	●	●
S	●	●	●	●	●
H	●	●	●	●	●
X	●	●	●	●	●
F*			●	●	●
HGP800	●	●	●	●	●
S	●	●	●	●	●
H	●	●	●	●	●
X	●	●	●	●	●

* F type is for overseas sales.

* Please refer to the certificate for specifications of certified products.

Approvals & Marine Certificates

MCCB

Type of Certification	Vessel							
Type of Standard	Korea	U.K	France	U.S.A	Germany	Italy	Japan	Russia
Mark								
Testing Institute	KR	LR	BV	ABS	DNV-GL	RINA	NK	RMRS
Certification Country	Korea	U.K	France	USA	Germany	Italy	Japan	Russia
HGP50D	F*	●	●	●	●	●	●	●
	S	●	●	●	●	●	●	●
	H	●	●	●	●	●	●	●
	X	●	●	●	●	●	●	●
HGP125D	F*	●	●	●	●	●	●	●
	S	●	●	●	●	●	●	●
	H	●	●	●	●	●	●	●
	X	●	●	●	●	●	●	●
HGP160D	F*	●	●	●	●	●	●	●
	S	●	●	●	●	●	●	●
	H	●	●	●	●	●	●	●
	X	●	●	●	●	●	●	●
HGP100	F*	●	●	●	●	●	●	●
	S	●	●	●	●	●	●	●
	H	●	●	●	●	●	●	●
	X	●	●	●	●	●	●	●
HGP160	F*	●	●	●	●	●	●	●
	S	●	●	●	●	●	●	●
	H	●	●	●	●	●	●	●
	X	●	●	●	●	●	●	●
HGP250	F*	●	●	●	●	●	●	●
	S	●	●	●	●	●	●	●
	H	●	●	●	●	●	●	●
	X	●	●	●	●	●	●	●
HGP400	F*	●	●	●	●	●	●	●
	S	●	●	●	●	●	●	●
	H	●	●	●	●	●	●	●
	X	●	●	●	●	●	●	●
HGP630	F*	●	●	●	●	●	●	●
	S	●	●	●	●	●	●	●
	H	●	●	●	●	●	●	●
	X	●	●	●	●	●	●	●
HGP800	F*	●	●	●	●	●	●	●
	S	●	●	●	●	●	●	●
	H	●	●	●	●	●	●	●
	X	●	●	●	●	●	●	●

※ * F type is for overseas sales.



Korea

Head Office 477, Bundangsuseo-ro, Bundang-gu, Seongnam-si,
Gyeonggi-do, Republic of Korea Tel: +82-2-479-9180 Fax : +82-2-500-4958

Factory 53, Je3gongdan 3-gil, Seoun-myeon, Anseong-si,
Gyeonggi-do, 17605, Republic of Korea Tel : +52-202-8179 Fax : +82-52-202-8100

Branch Offices

London 50-68 High Street, Weybridge, KT13 8BL, United Kingdom Tel : +44-7979-125051

Frankfurt Eschborner Landstrasse 55, 60489 Frankfurt am Main, Germany Tel : +49-69-7490-3934

Moscow World Trade Center, Ent.6, #412, Krasnopresnenskaya Nab.12,
Moscow, 123610, Russia Tel : +7-495-258-1381

Riyadh Office 404, 4th Floor Akaria-2 Bldg., Olaya St., PO Box
9187, Riyadh 11413, KSA Tel : +966-(0)11-210-1107

Dubai Unit 205, Emaar Square Building NO.4 Sheikh Zayed Road,
Dubai 252458, U.A.E Tel : +971-4-425-7995 Fax : +971-4-425-7996

Bangkok 19th Floor, Unit 1908, Sathorn Square Office Tower, 98 North
Sathorn Road, Silom, Bangrak, Bangkok 10500, Thailand Tel : +66-02-115-7920 Fax : +66-2-115-7898

Ho Chi Minh Centec Tower #1405, 72 Nguyễn Thị Minh Khai, Phường 6, Quận 3,
Thành phố Hồ Chí Minh, Vietnam Tel : +84-28-3535-0465

Osaka 1-Room 5th Floor Nagahori Plaza Bldg. 2-4-8 Minami Senba,
chuo-ku, Osaka 542-0081, Japan Tel : +81-6-6261-5766~7 Fax : +81-6-6261-5818
